

Package ‘arctgisutils’

September 18, 2025

Title R-ArcGIS Bridge Utility Functions

Version 0.4.0

Description Developer oriented utility functions designed to be used as the building blocks of R packages that work with ArcGIS Location Services. It provides functionality for authorization, Esri JSON construction and parsing, as well as other utilities pertaining to geometry and Esri type conversions. To support 'ArcGIS Pro' users, authorization can be done via 'arctgisbinding'. Installation instructions for 'arctgisbinding' can be found at <https://developers.arcgis.com/r-bridge/installation/>.

License Apache License (>= 2)

URL <https://github.com/R-ArcGIS/arctgisutils>,
<https://developers.arcgis.com/r-bridge/api-reference/arctgisutils/>

BugReports <https://github.com/R-ArcGIS/arctgisutils/issues>

Depends R (>= 4.2)

Imports cli, httr2 (>= 1.0.5), R6, RcppSimdJson, rlang, S7, sf, utils,
yyjsonr, lifecycle

Suggests arctgisbinding, collapse (>= 2.0.0), data.table, jsonify,
testthat (>= 3.0.0), curl, vctrs

Config/rextendr/version 0.4.2

Config/testthat/edition 3

Encoding UTF-8

Language en

RoxygenNote 7.3.2

SystemRequirements Cargo (Rust's package manager), rustc >= 1.67, xz

NeedsCompilation yes

Author Josiah Parry [aut, cre] (ORCID:

<https://orcid.org/0000-0001-9910-865X>),

Kenneth Vernon [ctb] (ORCID: <https://orcid.org/0000-0003-0098-5092>),

Martha Bass [ctb] (ORCID: <https://orcid.org/0009-0004-0268-5426>),

Eli Pousson [ctb] (ORCID: <https://orcid.org/0000-0001-8280-1706>)

Maintainer Josiah Parry <josiah.parry@gmail.com>

Repository CRAN

Date/Publication 2025-09-18 05:10:35 UTC

Contents

arc_agent	3
arc_base_req	3
arc_form_params	4
arc_gp_job	5
arc_group	7
arc_host	8
arc_item	9
arc_item_data	10
arc_job_status	11
arc_paginate_req	11
arc_portal_resources	12
arc_portal_servers	13
arc_portal_urls	14
arc_portal_users	14
arc_token	16
arc_user	18
arc_user_self	18
as_esri_geometry	19
as_extent	21
as_features	22
as_featureset	24
as_fields	26
as_layer	28
auth_code	31
compact	33
content	34
detect_errors	35
determine_dims	36
determine_esri_geo_type	37
fetch_layer_metadata	38
gp_params	39
is_date	42
parse_esri_json	43
portal_types	44
rbind_results	45
search_items	46
self	48
url	49
validate_crs	50

Index

52

arc_agent	<i>Set user-agent for arcgisutils</i>
-----------	---------------------------------------

Description

Override the default user-agent set by httr2 to indicate that a request came from arcgisutils.

Usage

```
arc_agent(req)
```

Arguments

req an httr2 request

Value

an httr2 request object

Examples

```
req <- httr2::request("http://example.com")
arc_agent(req)
```

arc_base_req	<i>Generate base request</i>
--------------	------------------------------

Description

This function takes a url and creates a basic httr2 request that adds the user-agent and adds an authorization token to the X-Esri-Authorization header.

Usage

```
arc_base_req(
  url,
  token = NULL,
  path = NULL,
  query = NULL,
  error_call = rlang::caller_env()
)
```

Arguments

url	a valid url that is passed to <code>httr2::request()</code>
token	an object of class <code>httr2_token</code> as generated by <code>auth_code()</code> or related function
path	a character vector of paths to be appended to url using <code>httr2::req_url_path_append()</code>
query	a named vector or named list of query parameters to be appended to the url using <code>httr2::req_url_query()</code>
error_call	the caller environment to be used when propagating errors.

Value

an `httr2_request` with the X-Esri-Authorization header and User-Agent set.

Examples

```
arc_base_req("https://arcgis.com")
```

arc_form_params	<i>Form request parameters</i>
-----------------	--------------------------------

Description

ArcGIS endpoints make extensive use of form encoded data for the body of http requests. Form requests require that each element has a name and is encoded as a single string—often as json.

Usage

```
arc_form_params(params = list())
```

```
as_form_params(x)
```

Arguments

params	a named list with scalar character elements
x	for <code>as_form_params()</code> , a named list to convert to form parameters

Details

The `arc_form_params` class provides validation of form body parameters ensuring that each element is a scalar string. It uses a named list internally to store the parameters.

The helper function `as_form_params()` converts a named list to form parameters by automatically JSON-encoding each element using `yyjsonr::write_json_str()` with `auto_unbox = TRUE`.

Value

an object of class `arc_form_params`

See Also

Other geoprocessing: [arc_gp_job](#), [arc_job_status\(\)](#), [gp_params](#)
Other geoprocessing: [arc_gp_job](#), [arc_job_status\(\)](#), [gp_params](#)

Examples

```
arc_form_params(  
  list(f = "json", outFields = "*", where = "1 = 1")  
)
```

arc_gp_job	Create a Geoprocessing Service Job
------------	------------------------------------

Description

The `arc_gp_job` class is used to interact with Geoprocessing Services in ArcGIS Online and Enterprise.

Usage

```
new_gp_job(base_url, params = list(), token = arc_token())
```

Arguments

- `base_url` the URL of the job service (without `/submitJob`)
- `params` a named list where each element is a scalar character
- `token` default [arc_token\(\)](#). The token to be used with the job.

Details

The `arc_gp_job` uses S7 classes for the job request parameters and job status via [arc_form_params\(\)](#) and [arc_job_status\(\)](#) respectively. Importantly, [arc_form_params\(\)](#) ensures that parameters provided to a geoprocessing service are all character scalars as required by the form body.

Value

An object of class `arc_gp_job`.

Public fields

- `base_url` the URL of the job service (without `/submitJob`)
- `id` the ID of the started job. NULL `self$start()` has not been called.

Active bindings

`params` returns an S7 object of class `arc_form_params` (see [arc_form_params\(\)](#)) the list can be accessed via `self$params@params`.

`status` returns the status of the geoprocessing job as an S7 object of class `gp_job_status` (see [arc_job_status\(\)](#)) by querying the `/jobs/{job-id}` endpoint.

`results` returns the current results of the job by querying the `/jobs/{job-id}/results` endpoint.

Methods

Public methods:

- [arc_gp_job\\$new\(\)](#)
- [arc_gp_job\\$start\(\)](#)
- [arc_gp_job\\$cancel\(\)](#)
- [arc_gp_job\\$await\(\)](#)
- [arc_gp_job\\$clone\(\)](#)

Method `new()`:

Usage:

```
arc_gp_job$new(
  base_url,
  params = list(),
  result_fn = NULL,
  token = arc_token(),
  error_call = rlang::caller_call()
)
```

Arguments:

`base_url` the URL of the job service (without `/submitJob`)

`params` a named list where each element is a scalar character

`result_fn` Default NULL. An optional function to apply to the results JSON. By default parses results using `RcppSimdJson::fparse()`.

`token` default [arc_token\(\)](#). The token to be used with the job.

`error_call` default `rlang::caller_call()` the calling environment.

Method `start()`: Starts the job by calling the `/submitJob` endpoint. This also sets the public field `id`.

Usage:

```
arc_gp_job$start()
```

Method `cancel()`: Cancels a job by calling the `/cancel` endpoint.

Usage:

```
arc_gp_job$cancel()
```

Method `await()`: Waits for job completion and returns results.

Usage:

```
arc_gp_job$await(interval = 0.1, verbose = FALSE)
```

Arguments:

interval polling interval in seconds (default 0.1)

verbose whether to print status messages (default FALSE)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
arc_gp_job$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other geoprocessing: [arc_form_params\(\)](#), [arc_job_status\(\)](#), [gp_params](#)

Examples

```
url <- paste0(
  "https://logistics.arcgis.com/arcgis/",
  "rest/services/World/ServiceAreas/",
  "GPService/GenerateServiceAreas"
)
job <- new_gp_job(url, list(f = "json"))
job

# extract params S7 class
params <- job$params
params

# view underlying list
params@params
```

arc_group

Fetch Group Information

Description

Fetches metadata about a group based on a provided group_id.

Usage

```
arc_group(group_id, host = arc_host(), token = arc_token())
```

Arguments

group_id	the unique group identifier. A scalar character.
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an httr2_token as created by auth_code() or similar

Details

[Experimental]

Value

a list with group metadata

See Also

Other portal organization: [arc_user\(\)](#)

Examples

```
arc_group("2f0ec8cb03574128bd673cefab106f39")
```

arc_host	<i>Determines Portal Host</i>
----------	-------------------------------

Description

Returns a scalar character indicating the host to make requests to.

Usage

```
arc_host()
```

Details

By default, the host is ArcGIS Online <<https://www.arcgis.com>>. If the environment variable ARCGIS_HOST is set, it will be returned.

Value

A scalar character, "<https://www.arcgis.com>" by default.

Examples

```
arc_host()
```

arc_item	<i>Portal Item Metadata</i>
----------	-----------------------------

Description

Given the unique ID of a content item, fetches the item's metadata from a portal.

Usage

```
arc_item(item_id, host = arc_host(), token = arc_token())
```

Arguments

item_id	the ID of the item to fetch. A scalar character.
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an httr2_token as created by auth_code() or similar

Details

See [API Reference](#) for more information.

[Experimental]

Value

an object of class PortalItem which is a list with the item's metadata.

See Also

Other portal item: [arc_item_data\(\)](#)

Examples

```
arc_item("9df5e769bfe8412b8de36a2e618c7672")
```

`arc_item_data`*Download an Item's Data*

Description

Download the data backing a portal item. This function always returns a raw vector as the type of the data that is downloaded cannot always be known.

Usage

```
arc_item_data(item, host = arc_host(), token = arc_token())
```

Arguments

<code>item</code>	the item ID or the result of <code>arc_item()</code> .
<code>host</code>	default <code>"https://www.arcgis.com"</code> . The host of your ArcGIS Portal.
<code>token</code>	an <code>httr2_token</code> as created by <code>auth_code()</code> or similar

Details

[Experimental]

Value

a raw vector containing the bytes of the data associated with the item. If the response is `application/json` then the json string is returned without parsing.

See Also

Other portal item: [arc_item\(\)](#)

Examples

```
arc_item_data("9df5e769bfe8412b8de36a2e618c7672")
```

arc_job_status	<i>Geoprocessing Job Status</i>
----------------	---------------------------------

Description

Represents the status of a geoprocessing job.

Usage

```
arc_job_status(status = character(0))
```

Arguments

status a scalar character. Must be one of "esriJobSubmitted", "esriJobWaiting", "esriJobExecuting", "esriJobSucceeded", "esriJobFailed", "esriJobTimedOut", "esriJobCancelling", or "esriJobCancelled".

Value

an object of class arc_job_status

See Also

Other geoprocessing: [arc_form_params\(\)](#), [arc_gp_job](#), [gp_params](#)

Examples

```
arc_job_status("esriJobSubmitted")
```

arc_paginate_req	<i>Paginate ArcGIS Requests</i>
------------------	---------------------------------

Description

Many API endpoints provide common **pagination properties**. `arc_paginate_request()` automatically applies pagination to an input request.

Usage

```
arc_paginate_req(req, page_size = 10, max_pages = Inf, .progress = TRUE)
```

Arguments

req an http2_request ideally created with arc_base_req
page_size a scalar integer between 1 and 100 indicating the number of responses per page.
max_pages the maximum number of pages to fetch. By default fetches all pages.
.progress default TRUE. Whether to display a progress bar for requests.

Value

a list of `httr2_response`.

References

[API Documentation](#)

See Also

[arc_base_req\(\)](#)

arc_portal_resources *Portal File Resources*

Description

The resources endpoint lists all file resources for the organization.

Usage

```
arc_portal_resources(
  id = arc_portal_self(token)[["id"]],
  page_size = 50,
  max_pages = Inf,
  .progress = TRUE,
  host = arc_host(),
  token = arc_token()
)
```

Arguments

<code>id</code>	the portal ID. By default it fetches the <code>id</code> from arc_portal_self() .
<code>page_size</code>	a scalar integer between 1 and 100 indicating the number of responses per page.
<code>max_pages</code>	the maximum number of pages to fetch. By default fetches all pages.
<code>.progress</code>	default <code>TRUE</code> . Whether to display a progress bar for requests.
<code>host</code>	default <code>"https://www.arcgis.com"</code> . The host of your ArcGIS Portal.
<code>token</code>	an object of class <code>httr2_token</code> as generated by auth_code() or related function

Value

a `data.frame` of resources available to your portal.

References

[API Reference](#)

See Also

Other portal: [arc_portal_urls\(\)](#), [arc_portal_users\(\)](#), [self](#)

Examples

```
## Not run:
  set_arc_token(auth_user())
  arc_portal_resources()

## End(Not run)
```

arc_portal_servers	<i>List ArcGIS Enterprise Servers</i>
--------------------	---------------------------------------

Description

The servers resource lists the ArcGIS Server sites that have been federated with the portal.

Usage

```
arc_portal_servers(
  id = arc_portal_self(token)[["id"]],
  host = arc_host(),
  token = arc_token()
)
```

Arguments

id	the portal ID. By default it fetches the id from arc_portal_self() .
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an object of class httr2_token as generated by auth_code() or related function

Value

a data.frame of servers

Examples

```
## Not run:
  set_arc_token(auth_user())
  arc_portal_servers()

## End(Not run)
```

arc_portal_urls	<i>Organization's URLs</i>
-----------------	----------------------------

Description

Returns the URLs of an organizations services.

Usage

```
arc_portal_urls(host = arc_host(), token = arc_token())
```

Arguments

host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an httr2_token as created by auth_code() or similar

Details

See [API Reference](#) for more information. **[Experimental]**

Value

a data.frame

See Also

Other portal: [arc_portal_resources\(\)](#), [arc_portal_users\(\)](#), [self](#)

Examples

```
arc_portal_urls()
```

arc_portal_users	<i>Portal Users</i>
------------------	---------------------

Description

This function lists all users in a portal.

Usage

```
arc_portal_users(
  id = arc_portal_self(token)[["id"]],
  sort_field = NULL,
  provider = NULL,
  sort_order = NULL,
  role = NULL,
  fullname = NULL,
  username = NULL,
  firstname = NULL,
  lastname = NULL,
  filter_intersection = NULL,
  page_size = 50,
  max_pages = Inf,
  .progress = TRUE,
  host = arc_host(),
  token = arc_token()
)
```

Arguments

id	the portal ID. By default it fetches the id from arc_portal_self() .
sort_field	optional field to sort by. It must be one of "username", "fullname", "created", "lastlogin", "mfaenabled", "level", "role".
provider	optional filter users based on their identity provider. Must be one of "arcgis", "enterprise", "facebook", "google", "apple", or "github".
sort_order	optional order to sort by. It must be one of "asc" or "desc".
role	optional role to filter down to. It must be one of "org_admin", "org_publisher", "org_user".
fullname	optional string of the user's fullanme to search for.
username	optional string of the user's user name to search for.
firstname	optional string of the user's first name to search for.
lastname	optional string of the user's last name to search for.
filter_intersection	optional boolean value. If TRUE mutiple filters are treated as an "and" condition. If FALSE, treated as an "or".
page_size	a scalar integer between 1 and 100 indicating the number of responses per page.
max_pages	the maximum number of pages to fetch. By default fetches all pages.
.progress	default TRUE. Whether to display a progress bar for requests.
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an object of class httr2_token as generated by auth_code() or related function

Value

a data.frame of users.

References

[API Reference](#)

See Also

Other portal: [arc_portal_resources\(\)](#), [arc_portal_urls\(\)](#), [self](#)

Examples

```
## Not run:
set_arc_token(auth_user())
arc_portal_users()

## End(Not run)
```

arc_token	<i>Manage authorization tokens</i>
-----------	------------------------------------

Description

These functions are used to set, fetch, and check authorization tokens.

Usage

```
arc_token(token = "ARCGIS_TOKEN")

set_arc_token(token, ...)

unset_arc_token(token = NULL)

obj_check_token(token, call = rlang::caller_env())

check_token_has_user(token, call = rlang::caller_env())
```

Arguments

- | | |
|-------|---|
| token | for <code>arc_token()</code> , the name of a token to fetch. For <code>set_arc_token()</code> , it is an <code>httr2_token</code> that will be set. For <code>unset_arc_token()</code> , a character vector of token names to be unset. |
| ... | named arguments to set <code>httr2_token</code> . Must be valid names and must be an <code>httr2_token</code> . |

call The execution environment of a currently running function, e.g. `call = caller_env()`. The corresponding function call is retrieved and mentioned in error messages as the source of the error.

You only need to supply `call` when throwing a condition from a helper function which wouldn't be relevant to mention in the message.

Can also be `NULL` or a [defused function call](#) to respectively not display any call or hard-code a code to display.

For more information about error calls, see [Including function calls in error messages](#).

Details

It is possible to have multiple authorization tokens in one session. These functions assist you in managing them.

`arc_token()` is used to fetch tokens by name. The default token is `ARCGIS_TOKEN`. However, they can be any valid character scalar. `set_arc_token()` will create store a token with the name `ARCGIS_TOKEN`. However, you can alternatively set the tokens by name using a key-value pair. The key is what you would pass to `arc_token()` to fetch the `httr2_token` object. To remove a token that has been set, use `unset_arc_token()`.

`obj_check_token()` is a developer oriented function that can be used to check if an object is indeed an `httr2_token`. To check if a token has expired, [validate_or_refresh_token\(\)](#) will do so.

`check_token_has_user()` is a developer oriented function that checks to see if a token has a `username` field associated with it.

For developers:

`set_arc_token()` uses a package level environment to store the tokens. The tokens are fetched from the environment using `arc_token()`.

Examples

```
# create fake tokens
token_a <- httr2::oauth_token("1234", arcgis_host = arc_host())
token_b <- httr2::oauth_token("abcd", arcgis_host = arc_host())

# set token to the default location
set_arc_token(token_a)

# fetch token from the default location
arc_token()

# set token by name
set_arc_token(org_a = token_a, org_b = token_b)

# fetch token by name
arc_token("org_a")
arc_token("org_b")

# unset tokens
unset_arc_token()
unset_arc_token(c("org_a", "org_b"))
```

arc_user	<i>User Information</i>
----------	-------------------------

Description

Fetch a user’s metadata based on username.

Usage

```
arc_user(username, host = arc_host(), token = arc_token())
```

Arguments

- username the username to fetch. A scalar character.
- host default "https://www.arcgis.com". The host of your ArcGIS Portal.
- token an http2_token as created by auth_code() or similar

Details

[Experimental]

Value

a list of class PortalUser

See Also

Other portal organization: [arc_group\(\)](#)

Examples

```
arc_user("esri_en")
```

arc_user_self	<i>Discover Authenticated User Metadata</i>
---------------	---

Description

Given an authentication token, return a list of user-specific information such as the user ID, user-name, available credits, email, groups, last login date and more.

Usage

```
arc_user_self(  
  host = arc_host(),  
  token = arc_token(),  
  error_call = rlang::caller_call()  
)
```

Arguments

host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an http2_token as created by auth_code() or similar
error_call	the caller environment to be used when propagating errors.

Value

a list of the authenticated user's metadata

References

[API Reference](#)

Examples

```
## Not run:  
if (interactive()) {  
  arc_user_self(token = auth_user())  
}  
  
## End(Not run)
```

as_esri_geometry

Create Esri JSON Geometry Objects

Description

as_esri_geometry() converts an sfg object to a EsriJSON Geometry object as a string.

Usage

```
as_esri_geometry(x, crs = NULL, call = rlang::caller_env())
```

Arguments

x	an object of class sfg. Must be one of "POINT", "MULTIPOINT", "LINESTRING", "MULTILINESTRING", "POLYGON", or "MULTIPOLYGON".
crs	the coordinate reference system. It must be interpretable by <code>sf::st_crs()</code> .
call	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Details

See `as_featureset()` and `as_features()` for converting sfc and sf objects into EsriJSON.

Value

a scalar string

References

[API Reference](#)

Examples

```
library(sf)
# POINT
# create sfg points
xy <- st_point(c(1, 2))
xyz <- st_point(c(1, 2, 3))
xym <- st_point(c(1, 2, 3), dim = "XYM")
xyzm <- st_point(c(1, 2, 3, 4))

as_esri_geometry(xy)
as_esri_geometry(xyz)
as_esri_geometry(xym)
as_esri_geometry(xyzm)

# MULTIPOINT
# vector to create matrix points
set.seed(0)
x <- rnorm(12)

xy <- st_multipoint(matrix(x, ncol = 2))
xyz <- st_multipoint(matrix(x, ncol = 3))
xym <- st_multipoint(matrix(x, ncol = 3), dim = "XYM")
xyzm <- st_multipoint(matrix(x, ncol = 4), dim = "XYM")
```

```

as_esri_geometry(xy)
as_esri_geometry(xyz)
as_esri_geometry(xym)
as_esri_geometry(xyzm)

# LINESTRING
xy <- st_linestring(matrix(x, ncol = 2))
xyz <- st_linestring(matrix(x, ncol = 3))
xym <- st_linestring(matrix(x, ncol = 3), dim = "XYM")
xyzm <- st_linestring(matrix(x, ncol = 4), dim = "XYM")

as_esri_geometry(xy)
as_esri_geometry(xyz)
as_esri_geometry(xym)
as_esri_geometry(xyzm)

# MULTILINESTRING
as_esri_geometry(st_multilinestring(list(xy, xy)))
as_esri_geometry(st_multilinestring(list(xyz, xyz)))
as_esri_geometry(st_multilinestring(list(xym, xym)))
as_esri_geometry(st_multilinestring(list(xyzm, xyzm)))

# POLYGON
coords <- rbind(
  c(0, 0, 0, 1),
  c(0, 1, 0, 1),
  c(1, 1, 1, 1),
  c(1, 0, 1, 1),
  c(0, 0, 0, 1)
)

xy <- st_polygon(list(coords[, 1:2]))
xyz <- st_polygon(list(coords[, 1:3]))
xym <- st_polygon(list(coords[, 1:3]), dim = "XYM")
xyzm <- st_polygon(list(coords))

as_esri_geometry(xy)
as_esri_geometry(xyz)
as_esri_geometry(xym)
as_esri_geometry(xyzm)

# MULTIPOLYGON
as_esri_geometry(st_multipolygon(list(xy, xy)))
as_esri_geometry(st_multipolygon(list(xyz, xyz)))
as_esri_geometry(st_multipolygon(list(xym, xym)))
as_esri_geometry(st_multipolygon(list(xyzm, xyzm)))

```

Description

Given an sf or sfc object create a list that represents the extent of the object. The result of this function can be parsed directly into json using `jsonify::to_json(x, unbox = TRUE)` or included into a list as the extent component that will be eventually converted into json using the above function.

Usage

```
as_extent(x, crs = sf::st_crs(x), call = rlang::caller_env())
```

Arguments

x	an sf or sfc object
crs	the CRS of the object. Must be parsable by <code>sf::st_crs()</code>
call	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply call when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be NULL or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Value

An extent json object. Use `jsonify::to_json(x, unbox = TRUE)` to convert to json.

Examples

```
nc <- sf::st_read(system.file("shape/nc.shp", package = "sf"), quiet = TRUE)
as_extent(nc)
```

as_features

Create Esri Features

Description

These functions create an array of Esri Feature objects. Each feature consists of a geometry and attribute field. The result of `as_esri_features()` is a JSON array of Features whereas `as_features()` is a list that represents the same JSON array. Using `jsonify::to_json(as_features(x), unbox = TRUE)` will result in the same JSON array.

Usage

```
as_features(x, crs = sf::st_crs(x), call = rlang::caller_env())
```

```
as_esri_features(x, crs = sf::st_crs(x), call = rlang::caller_env())
```

Arguments

x	an object of class sf, data.frame, or sfc.
crs	the coordinate reference system. It must be interpretable by <code>sf::st_crs()</code> .
call	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Value

Either a scalar string or a named list.

References

[API Reference](#)

Examples

```
library(sf)
# POINT
# create sfg points
xy <- st_sfc(st_point(c(1, 2)))
xyz <- st_sfc(st_point(c(1, 2, 3)))
xym <- st_sfc(st_point(c(1, 2, 3), dim = "XYM"))

as_esri_features(xy)
as_esri_features(xyz)
as_esri_features(xym)

# MULTIPOINT
# vector to create matrix points
set.seed(0)
x <- rnorm(12)

xy <- st_sfc(st_multipoint(matrix(x, ncol = 2)))
xyz <- st_sfc(st_multipoint(matrix(x, ncol = 3)))
xym <- st_sfc(st_multipoint(matrix(x, ncol = 3), dim = "XYM"))

as_esri_features(xy)
as_esri_features(xyz)
as_esri_features(xym)

# LINESTRING
xy <- st_sfc(st_linestring(matrix(x, ncol = 2)))
xyz <- st_sfc(st_linestring(matrix(x, ncol = 3)))
```

```

xym <- st_sfc(st_linestring(matrix(x, ncol = 3), dim = "XYM"))

as_esri_features(xy)
as_esri_features(xyz)
as_esri_features(xym)

# MULTILINESTRING
as_esri_features(st_sfc(st_multilinestring(list(xy[[1]], xy[[1]]))))
as_esri_features(st_sfc(st_multilinestring(list(xyz[[1]], xyz[[1]]))))
as_esri_features(st_sfc(st_multilinestring(list(xym[[1]], xym[[1]]))))

# POLYGON
coords <- rbind(
  c(0, 0, 0, 1),
  c(0, 1, 0, 1),
  c(1, 1, 1, 1),
  c(1, 0, 1, 1),
  c(0, 0, 0, 1)
)

xy <- st_sfc(st_polygon(list(coords[, 1:2])))
xyz <- st_sfc(st_polygon(list(coords[, 1:3])))
xym <- st_sfc(st_polygon(list(coords[, 1:3]), dim = "XYM"))

as_esri_features(xy)
as_esri_features(xyz)
as_esri_features(xym)

# MULTIPOLYGON
as_esri_features(st_sfc(st_multipolygon(list(xy[[1]], xy[[1]]))))
as_esri_features(st_sfc(st_multipolygon(list(xyz[[1]], xyz[[1]]))))
as_esri_features(st_sfc(st_multipolygon(list(xym[[1]], xym[[1]]))))

```

as_featureset

Create Esri FeatureSet Objects

Description

These functions create an Esri FeatureSet object. A FeatureSet contains an inner array of features as well as additional metadata about the the collection such as the geometry type, spatial reference, and object ID field.

Usage

```
as_featureset(x, crs = sf::st_crs(x), call = rlang::caller_env())
```

```
as_esri_featureset(x, crs = sf::st_crs(x), call = rlang::caller_env())
```

Arguments

<code>x</code>	an object of class <code>sf</code> , <code>data.frame</code> , or <code>sfc</code> .
<code>crs</code>	the coordinate reference system. It must be interpretable by <code>sf::st_crs()</code> .
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Value

a list or a json string

References

[API Reference](#)

Examples

```
library(sf)
# POINT
# create sfg points
xy <- st_sfc(st_point(c(1, 2)))
xyz <- st_sfc(st_point(c(1, 2, 3)))
xym <- st_sfc(st_point(c(1, 2, 3), dim = "XYM"))

as_esri_featureset(xy)
as_esri_featureset(xyz)
as_esri_featureset(xym)

# MULTIPOINT
# vector to create matrix points
set.seed(0)
x <- rnorm(12)

xy <- st_sfc(st_multipoint(matrix(x, ncol = 2)))
xyz <- st_sfc(st_multipoint(matrix(x, ncol = 3)))
xym <- st_sfc(st_multipoint(matrix(x, ncol = 3), dim = "XYM"))

as_esri_featureset(xy)
as_esri_featureset(xyz)
as_esri_featureset(xym)

# LINESTRING
xy <- st_sfc(st_linestring(matrix(x, ncol = 2)))
xyz <- st_sfc(st_linestring(matrix(x, ncol = 3)))
```

```

xym <- st_sfc(st_linestring(matrix(x, ncol = 3), dim = "XYM"))

as_esri_featureset(xy)
as_esri_featureset(xyz)
as_esri_featureset(xym)

# MULTILINESTRING
as_esri_featureset(st_sfc(st_multilinestring(list(xy[[1]], xy[[1]]))))
as_esri_featureset(st_sfc(st_multilinestring(list(xyz[[1]], xyz[[1]]))))
as_esri_featureset(st_sfc(st_multilinestring(list(xym[[1]], xym[[1]]))))

# POLYGON
coords <- rbind(
  c(0, 0, 0, 1),
  c(0, 1, 0, 1),
  c(1, 1, 1, 1),
  c(1, 0, 1, 1),
  c(0, 0, 0, 1)
)

xy <- st_sfc(st_polygon(list(coords[, 1:2])))
xyz <- st_sfc(st_polygon(list(coords[, 1:3])))
xym <- st_sfc(st_polygon(list(coords[, 1:3]), dim = "XYM"))

as_esri_featureset(xy)
as_esri_featureset(xyz)
as_esri_featureset(xym)

# MULTIPOLYGON
as_esri_featureset(st_sfc(st_multipolygon(list(xy[[1]], xy[[1]]))))
as_esri_featureset(st_sfc(st_multipolygon(list(xyz[[1]], xyz[[1]]))))
as_esri_featureset(st_sfc(st_multipolygon(list(xym[[1]], xym[[1]]))))

```

as_fields

Esri Field Type Mapping

Description

Infers Esri field types from R objects. Use `as_fields()` to create a data.frame of valid **Esri Field Types** from an sf object or data.frame.

Usage

```

as_fields(.data, arg = rlang::caller_arg(.data), call = rlang::caller_env())

infer_esri_type(
  .data,
  arg = rlang::caller_arg(.data),
  call = rlang::caller_env()
)

```

```
fields_as_ptype_df(fields, n = 0, call = rlang::caller_env())
```

```
ptype_tbl(fields, n = 0, call = rlang::caller_env())
```

Arguments

.data	an object of class <code>data.frame</code> .
arg	An argument name in the current function.
call	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.
fields	a list or <code>data.frame</code> of field types. Requires the fields type and name to be present.
n	the number of rows to create in the prototype table

Details

[Experimental]

- `as_fields()` takes a data frame-like object and infers the Esri field type from it.
- `fields_as_ptype_df()` takes a list with type and name and creates an empty `data.frame` with the corresponding column names and types.
- `get_ptype()` takes a scalar character containing the Esri field type and returns a prototype of the pertinent R type

Field type mapping::

Esri field types are mapped as

- `esriFieldTypeSmallInteger`: integer
- `esriFieldTypeSingle`: double
- `esriFieldTypeGUID`: integer
- `esriFieldTypeOID`: integer
- `esriFieldTypeInteger`: integer
- `esriFieldTypeBigInteger`: double
- `esriFieldTypeDouble`: double
- `esriFieldTypeString`: character
- `esriFieldTypeDate`: date

R types are mapped as

- `double`: `esriFieldTypeDouble`

- integer: esriFieldTypeInteger
- character: esriFieldTypeString
- date: esriFieldTypeDate
- raw: esriFieldTypeBlob

Value

- `fields_as_ptype_df()` takes a `data.frame` with columns name and type and creates an empty `data.frame` with the corresponding columns and R types
- `as_fields()` returns a `data.frame` with columns name, type, alias, nullable, and editable columns
 - This resembles that of the fields returned by a `FeatureService`

Examples

```
inferred <- as_fields(iris)
inferred

fields_as_ptype_df(inferred)
```

as_layer

Create Esri layer objects

Description

These functions are used to generate list objects that can be converted into json objects that are used in REST API requests. Notably they are used for adding R objects as items to a portal.

Usage

```
as_layer(
  x,
  name,
  title,
  layer_definition = as_layer_definition(x, name, "object_id", infer_esri_type(x)),
  id = NULL,
  layer_url = NULL,
  legend_url = NULL,
  popup_info = NULL,
  call = rlang::caller_env()
)

as_layer_definition(
  x,
  name,
  object_id_field,
```

```

    fields = infer_esri_type(x),
    display_field = NULL,
    drawing_info = NULL,
    has_attachments = FALSE,
    max_scale = 0,
    min_scale = 0,
    templates = NULL,
    type_id_field = NULL,
    types = NULL,
    call = rlang::caller_env()
  )

  as_feature_collection(
    layers = list(),
    show_legend = TRUE,
    call = rlang::caller_env()
  )

```

Arguments

<code>x</code>	an object of class <code>data.frame</code> . This can be an <code>sf</code> object or <code>tibble</code> or any other subclass of <code>data.frame</code> .
<code>name</code>	a scalar character of the name of the layer. Must be unique.
<code>title</code>	A user-friendly string title for the layer that can be used in a table of contents.
<code>layer_definition</code>	a layer definition list as created by <code>as_layer_definition()</code> . A default is derived from <code>x</code> and the name object.
<code>id</code>	A number indicating the index position of the layer in the WMS or map service.
<code>layer_url</code>	default <code>NULL</code> . A string URL to a service that should be used for all queries against the layer. Used with hosted tiled map services on ArcGIS Online when there is an associated feature service that allows for queries.
<code>legend_url</code>	default <code>NULL</code> . A string URL to a legend graphic for the layer. Used with WMS layers. The URL usually contains a <code>GetLegendGraphic</code> request.
<code>popup_info</code>	default <code>NULL</code> . A list that can be converted into a popupInfo object defining the pop-up window content for the layer. There is no helper for <code>popupInfo</code> objects.
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code> . The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages .
<code>object_id_field</code>	a scalar character vector indicating the name of the object ID field in the dataset.

fields	a dataframe describing the fields in x. These values are inferred by default via infer_esri_type() .
display_field	default NULL. A scalar character containing the name of the field that best summarizes the feature. Values from this field are used by default as the titles for pop-up windows.
drawing_info	default NULL. See REST documentation in details for more. There are no helpers or validators for drawingInfo objects.
has_attachments	default FALSE.
max_scale	default NULL. A number representing the maximum scale at which the layer definition will be applied. The number is the scale's denominator; thus, a value of 2400 represents a scale of 1/2,400. A value of 0 indicates that the layer definition will be applied regardless of how far you zoom in.
min_scale	default NULL. A number representing the minimum scale at which the layer definition will be applied.
templates	default NULL. See REST documentation in details for more.
type_id_field	default NULL. See REST documentation in details for more.
types	An array of type objects available for the dataset. This is used when the type_id_field is populated. NOTE there are no helper functions to create type objects. Any type list objects must match the json structure when passed to <code>jsonify::to_json(x, unbox = TRUE)</code> .
layers	a list of layers as created by <code>as_layer()</code> .
show_legend	default FALSE. Logical scalar indicating if this layer should be shown in the legend in client applications.

Details

A `FeatureCollection` defines a layer of features that will be stored on a web map. It consists of an array of layers. The layer contains the features (attributes and geometries) as a `FeatureSet` (see [as_esri_featureset\(\)](#)) and additional metadata which is stored in the `LayerDefinition` object. The `LayerDefinition` most importantly documents the fields in the object, the object ID, and additional metadata such as name, title, and display scale.

Additional documentation for these json object:

- [layer](#)
- [layerDefinition](#)
- [featureCollection](#)

Value

A list object containing the required fields for each respective json type. The results can be converted to json using `jsonify::to_json(x, unbox = TRUE)`

Examples

```
ld <- as_layer_definition(iris, "iris", "objectID")
l <- as_layer(iris, "iris name", "Iris Title")
fc <- as_feature_collection(layers = list(l))
```

auth_code

*Authorization***Description**

Authorize your R session to connect to an ArcGIS Portal. See details.

Usage

```
auth_code(client = Sys.getenv("ARCGIS_CLIENT"), host = arc_host())

auth_client(
  client = Sys.getenv("ARCGIS_CLIENT"),
  secret = Sys.getenv("ARCGIS_SECRET"),
  host = arc_host(),
  expiration = 120
)

auth_binding()

auth_user(
  username = Sys.getenv("ARCGIS_USER"),
  password = Sys.getenv("ARCGIS_PASSWORD"),
  host = arc_host(),
  expiration = 60
)

auth_key(api_key = Sys.getenv("ARCGIS_API_KEY"), host = arc_host())

refresh_token(token, client = Sys.getenv("ARCGIS_CLIENT"), host = arc_host())

validate_or_refresh_token(
  token,
  client = Sys.getenv("ARCGIS_CLIENT"),
  host = arc_host(),
  refresh_threshold = 10,
  call = rlang::caller_env()
)
```

Arguments

client	an OAuth 2.0 developer application client ID. By default uses the environment variable ARCGIS_CLIENT.
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
secret	an OAuth 2.0 developer application secret. By default uses the environment variable ARCGIS_SECRET.
expiration	the duration of the token in minutes.
username	default Sys.getenv("ARCGIS_USER"). Your username to login. Do not hard code this value.
password	default Sys.getenv("ARCGIS_PASSWORD"). Your password to login. Do not hard code this value.
api_key	default Sys.getenv("ARCGIS_API_KEY"). A character scalar of an ArcGIS Developer API key.
token	an httr2_token as created by auth_code() or similar
refresh_threshold	default 10. If token expiry is within this threshold (in seconds) the token will be refreshed only if a refresh_token is available. Token refreshing is only possible with auth_code() flow.
call	The execution environment of a currently running function, e.g. call = caller_env(). The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply call when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be NULL or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Details

ArcGIS Online and Enterprise Portals utilize OAuth2 authorization via their REST APIs.

- auth_code() is the recommend OAuth2 workflow for interactive sessions
- auth_client() is the recommended OAuth2 workflow for non-interactive sessions
- auth_user() uses legacy username and password authorization using the generateToken endpoint. It is only recommended for legacy systems that do not implement OAuth2.
- auth_binding() fetches a token from the active portal set by arcgisbinding. Uses arcgisbinding::arc.check_portal to extract the authorization token. Recommended if using arcgisbinding.

Value

an httr2_token

Examples

```
## Not run:
auth_code()
auth_client()
auth_user()
auth_key()
auth_binding()

## End(Not run)
```

compact	<i>General utility functions</i>
---------	----------------------------------

Description

General utility functions

Usage

```
compact(.x)

a %||% b

check_dots_named(dots, call = rlang::caller_env())

data_frame(x, call = rlang::caller_call())
```

Arguments

.x	a list
a	an R object
b	an R object
dots	a list collected from dots via <code>rlang::list2(...)</code>
call	default <code>rlang::caller_call()</code> .
x	a data.frame

Details

- `compact()` removes any NULL list elements
- `%||%` is a special pipe operator that returns b if a is NULL

Value

- `compact()` a list
- `%||%` the first non-null item or NULL if both are NULL

Examples

```
# remove null elements
compact(list(a = NULL, b = 1))

# if NULL return rhs
NULL %||% 123

# if not NULL return lhs
123 %||% NULL
```

content

Portal Content Items

Description

For a given user or group, returns a data.frame of all content items owned by them.

Usage

```
arc_group_content(group, host = arc_host(), token = arc_token())

arc_user_content(user, host = arc_host(), token = arc_token())
```

Arguments

group	a scalar character of the group ID or a PortalGroup object created using arc_group()
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an httr2_token as created by <code>auth_code()</code> or similar
user	a scalar character of the username or a PortalUser object created using arc_user()

Value

a data.frame of content item metadata

References

- [Group Content API Reference](#)
- [User Content API Reference](#)

Examples

```
## Not run:
library(arcgis)

# authenticate
set_arc_token(auth_user())

# get your own content items
self <- arc_user_self()
arc_user_content(self$username)

# get a specific group's items
arc_group_content("2f0ec8cb03574128bd673cefab106f39")

## End(Not run)
```

detect_errors

Detect errors in parsed json response

Description

The requests responses from ArcGIS don't return the status code in the response itself but rather from the body in the json. This function checks for the existence of an error. If an error is found, the contents of the error message are bubbled up.

Usage

```
detect_errors(response, error_call = rlang::caller_env())

catch_error(response, error_call = rlang::caller_env())
```

Arguments

response	for <code>detect_errors()</code> , a list typically from <code>RcppSimdJson::fparse(httr2::resp_body_string(resp))</code> . For <code>catch_error()</code> , the string from <code>httr2::resp_body_string(resp)</code> .
error_call	default <code>rlang::caller_env()</code> . The environment from which to throw the error from.

Value

Nothing. Used for it's side effect. If an error code is encountered in the response an error is thrown with the error code and the error message.

Examples

```
## Not run:
response <- list(
  error = list(
    code = 400L,
    message = "Unable to generate token.",
    details = "Invalid username or password."
  )
)

detect_errors(response)

## End(Not run)
```

determine_dims

Determine the dimensions of a geometry object

Description

Given an sfc or sfg object determine what dimensions are represented.

Usage

```
determine_dims(x)
```

```
has_m(x)
```

```
has_z(x)
```

Arguments

x an object of class sfc or sfg

Value

determine_dims() returns a scalar character of the value "xy", "xyz", or "xyzm" depending on what dimensions are represented.

has_m() and has_z() returns a logical scalar of TRUE or FALSE if the geometry has a Z or M dimension.

Examples

```
geo <- sf::st_read(system.file("shape/nc.shp", package="sf"), quiet = TRUE)[["geometry"]]

determine_dims(geo)
has_z(geo)
has_m(geo)
```

`determine_esri_geo_type`*Determine Esri Geometry type*

Description

Takes an `sf` or `sfc` object and returns the appropriate Esri geometry type.

Usage

```
determine_esri_geo_type(x, call = rlang::caller_env())
```

Arguments

- | | |
|-------------------|---|
| <code>x</code> | an object of class <code>data.frame</code> , <code>sf</code> , <code>sfc</code> , or <code>sfg</code> . |
| <code>call</code> | <p>The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error.</p> <p>You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message.</p> <p>Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display.</p> <p>For more information about error calls, see Including function calls in error messages.</p> |

Details

Geometry type mapping:

- POINT: `esriGeometryPoint`
- MULTIPOINT: `esriGeometryMultipoint`
- LINESTRING: `esriGeometryPolyline`
- MULTILINESTRING: `esriGeometryPolyline`
- POLYGON: `esriGeometryPolygon`
- MULTIPOLYGON: `esriGeometryPolygon`

Value

returns a character scalar of the corresponding Esri geometry type

Examples

```
determine_esri_geo_type(sf::st_point(c(0, 0)))
```

fetch_layer_metadata	<i>Retrieve metadata</i>
----------------------	--------------------------

Description

Utility functions for feature service metadata.

Usage

```
fetch_layer_metadata(url, token = NULL, call = rlang::caller_env())
```

Arguments

url	the url of the item.
token	an <code>httr2_token</code> from one of the provided <code>auth_</code> functions
call	default <code>rlang::caller_env()</code> . The calling environment passed to <code>detect_errors()</code> .

Details

- `fetch_layer_metadata()` given a request, fetches the metadata by setting the query parameter `f=json`

Value

returns a list object

Examples

```
# url is broken into parts to fit within 100 characters to avoid CRAN notes
url_parts <- c(
  "https://services.arcgis.com/P3ePLMys2RVChkJx/ArcGIS/rest/services",
  "/USA_Counties_Generalized_Boundaries/FeatureServer/0"
)

furl <- paste0(url_parts, collapse = "")
meta <- fetch_layer_metadata(furl)
head(names(meta))
```

Description

Functions for converting R objects to and from ArcGIS geoprocessing parameter types. These functions handle the serialization and parsing of various data types used in ArcGIS geoprocessing services.

Usage

```
parse_gp_feature_record_set(json)

as_gp_feature_record_set(x)

parse_gp_record_set(json)

as_record_set(x)

as_gp_raster_layer(x)

gp_linear_unit(distance = integer(0), units = character(0))

as_gp_linear_unit(x)

parse_gp_linear_unit(json)

gp_areal_unit(area = integer(0), units = character(0))

as_gp_areal_unit(x)

parse_gp_areal_unit(json)

as_gp_date(x)

parse_gp_date(json)

as_spatial_reference(x)

parse_spatial_reference(json)
```

Arguments

json	raw json to parse
x	the object to convert into json
distance	a scalar number of the distance.

units	the unit of the measurement. Must be one of "esriUnknownAreaUnits", "esriSquareInches", "esriSquareFeet", "esriSquareYards", "esriAcres", "esriSquareMiles", "esriSquareMillimeters", "esriSquareCentimeters", "esriSquareDecimeters", "esriSquareMeters", "esriAres", "esriHectares", "esriSquareKilometers", "esriSquareInchesUS", "esriSquareFeetUS", "esriSquareYardsUS", "esriAcresUS", "esriSquareMilesUS".
area	a scalar number of the measurement.

Details

[Experimental]

This package provides support for the following geoprocessing parameter types:

Implemented Types:

- **GPFeatureRecordSetLayer**: Feature collections with geometry and attributes
- **GPRecordSet**: Tabular data without geometry
- **GPRasterDataLayer**: Raster datasets from Portal items, Image Servers, or URLs
- **GPLinearUnit**: Linear distance measurements with units
- **GParealUnit**: Area measurements with units
- **GPDate**: Date/time values in milliseconds since epoch
- **GPSpatialReference**: Coordinate reference systems

Not Yet Implemented:

The following types are planned for future implementation:

- **GPField**: Field definitions with name, type, and properties
- **GPMultiValue**: Arrays of values for a single data type
- **GPValueTable**: Flexible table-like objects with rows and columns
- **GPComposite**: Parameters that accept multiple data types
- **GPEnvelope**: Bounding box extents (use `as_extent()` for `GPEntent`)

Usage Patterns

Most functions follow a consistent pattern:

- `as_gp_*`(): Convert R objects to geoprocessing parameter JSON
- `parse_gp_*`(): Parse geoprocessing response JSON to R objects
- Constructor functions (e.g., `gp_linear_unit()`, `gp_areal_unit()`) create typed `S7` objects

Examples

```
# Create a linear unit
distance <- gp_linear_unit(distance = 100, units = "esriMeters")

# Convert spatial data to feature record set
as_gp_feature_record_set(my_sf_data)

# Parse a geoprocessing response
parse_gp_feature_record_set(response_json)
```

References

[API Documentation](#)

See Also

Other geoprocessing: [arc_form_params\(\)](#), [arc_gp_job](#), [arc_job_status\(\)](#)

Examples

```
# create a feature record set
fset <- as_gp_feature_record_set(iris[1,])
fset

# create fake gp feature record set to parse
fset_list <- list(
  list(
    dataType = "GPFeatureRecordSetLayer",
    paramName = "example",
    value = as_featureset(iris[1,])
  )
)

# create the json
json <- yyjsonr::write_json_str(fset_list, auto_unbox = TRUE)

# parse the record set json
parse_gp_feature_record_set(json)

# linear units
lu <- gp_linear_unit(10, "esriMeters")
lu
as_gp_linear_unit(lu)

# areal units
au <- gp_areal_unit(10, "esriSquareMeters")
au
as_gp_areal_unit(au)

# dates
json <- r"({
  \"paramName\": \"Output_Date\",
  \"dataType\": \"GPDate\",
  \"value\": 1199145600000
})"

parse_gp_date(json)
```

`is_date`*Date handling*

Description

Esri date fields are represented as milliseconds from the Unix Epoch.

Usage

```
is_date(x, tz)
```

```
date_to_ms(x, tz = "UTC")
```

```
from_esri_date(x)
```

Arguments

<code>x</code>	an object of class <code>Date</code> or <code>POSIXt</code> . In the case of <code>is_date()</code> , any R object.
<code>tz</code>	a character string. The time zone specification to be used for the conversion, <i>if one is required</i> . System-specific (see time zones), but "" is the current time zone, and "GMT" is UTC (Universal Time, Coordinated). Invalid values are most commonly treated as UTC, on some platforms with a warning.

Details

- `is_date()`: checks if an object is a `Date` or `POSIXt` class object.
- `date_to_ms()` converts a date object to milliseconds from the Unix Epoch in the specified time zone.

Value

- `is_date()` returns a logical scalar
- `date_to_ms()` returns a numeric vector of times in milliseconds from the Unix Epoch in the specified time zone.

Examples

```
today <- Sys.Date()
```

```
is_date(today)
```

```
date_to_ms(today)
```

parse_esri_json	<i>Parse Esri JSON</i>
-----------------	------------------------

Description

Parses an Esri FeatureSet JSON object into an R object. If there is no geometry present, a `data.frame` is returned. If there is geometry, an `sf` object is returned.

Usage

```
parse_esri_json(string, ..., call = rlang::caller_env())
```

Arguments

<code>string</code>	the raw Esri JSON string.
<code>...</code>	additional arguments passed to RcppSimdJson::fparse
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Value

A `data.frame`. If geometry is found, returns an `sf` object.

Examples

```
esri_json <- '{
  "geometryType": "esriGeometryPolygon",
  "spatialReference": {
    "wkid": 4326
  },
  "hasZ": false,
  "hasM": false,
  "features": [
    {
      "attributes": {
        "id": 1
      },
      "geometry": {
        "rings": [
          [
            [0.0, 0.0],
```

```

    [1.0, 0.0],
    [1.0, 1.0],
    [0.0, 1.0],
    [0.0, 0.0]
  ]
}
]
}'
parse_esri_json(esri_json)
```

portal_types	<i>Portal Item Types</i>
--------------	--------------------------

Description

Every portal item has an associated item type. Each of those item types have keywords which can be used to help narrow down search further.

Usage

```
item_type(item_type = character(0))
item_keyword(keyword = character(0))
portal_item_keywords()
portal_item_types()
```

Arguments

- item_type a scalar character of the item type. See [portal_item_types\(\)](#) for valid item types.
- keyword a scalar character of the item type keyword. See [portal_item_keywords\(\)](#).

References

[REST API Documentation](#)

rbind_results	<i>Combine multiple data.frames</i>
---------------	-------------------------------------

Description

A general function that takes a list of `data.frames` and returns a single and combines them into a single object. It will use the fastest method available. In order this is `collapse::rowbind()`, `data.table::rbindlist()`, `vctrs::list_unchop()`, then `do.call(rbind.data.frame, x)`.

Usage

```
rbind_results(x, call = rlang::current_env(), .ptype = data.frame())
```

Arguments

<code>x</code>	a list where each element is a <code>data.frame</code> or <code>NULL</code> .
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.
<code>.ptype</code>	currently unused. Reserved for a future release.

Details

If all items in the list are `data.frames`, then the result will be a `data.frame`. If all elements are an `sf` object, then the result will be an `sf` object. If the items are mixed, the result will be a `data.frame`.

If any items are `NULL`, then an attribute `null_elements` will be attached to the result. The attribute is an integer vector of the indices that were `NULL`.

Value

see details.

Examples

```
x <- head(iris)
res <- rbind_results(list(x, NULL, x))
attr(res, "null_elements")
```

search_items	<i>Search for Portal Items</i>
--------------	--------------------------------

Description

Perform full text search or use parameters to programamatically query your portal for content items.

Usage

```
search_items(  
  query = NULL,  
  filter = NULL,  
  title = NULL,  
  description = NULL,  
  snippet = NULL,  
  tags = NULL,  
  owner = NULL,  
  orgid = NULL,  
  item_type = NULL,  
  type_keywords = NULL,  
  created = NULL,  
  modified = NULL,  
  categories = NULL,  
  category_filters = NULL,  
  sort_field = NULL,  
  sort_order = NULL,  
  count_fields = NULL,  
  count_size = NULL,  
  display_sublayers = FALSE,  
  filter_logic = "and",  
  bbox = NULL,  
  page_size = 50,  
  max_pages = Inf,  
  .progress = TRUE,  
  host = arc_host(),  
  token = arc_token()  
)
```

Arguments

- query a scalar character for free text search or a valid query string as defined by the REST API.
- filter a scalar character. If provided all other arguments except query are ignored.
- title optional character vector of content item titles.
- description, snippet optional scalar character of text to check for.

tags	optional character vector of tags to search for.
owner	optional character vector of owner usernames to search for.
orgid	optional character vector of organization IDs to search for.
item_type	optional character vector of content item types. Validated with <code>item_type()</code> .
type_keywords	optional character vector of content type keywords. Validated with <code>item_keyword()</code> .
created, modified	optional length two vector which must be coercible to a date time vector. Converted using <code>as.POSIXct()</code> . Returns only items within this range.
categories	optional character vector of up to 8 organization content categories.
category_filters	optional character vector of up to 3 category terms. Items that have matching categories are returned. Exclusive with categories.
sort_field	optional character vector of fields to sort by. Can sort by title, created, type, owner, modified, avgrating, numratings, numcomments, numviews, and scorecompleteness.
sort_order	optional string. One of either asc or desc for ascending or descending order respectively.
count_fields	optional character vector of up to 3 fields to count. Must be one of c("type", "access", "contentstatus", "categories").
count_size	optional integer determines the maximum number of field values to count for each counted field in count_fields. Maximum of 200.
display_sublayers	default FALSE. Returns feature layers inside of feature services.
filter_logic	default "and" must be one of c("and", "or", "not"). Determines if parameters
bbox	unimplemented.
page_size	a scalar integer between 1 and 100 indicating the number of responses per page.
max_pages	the maximum number of pages to fetch. By default fetches all pages.
.progress	default TRUE. Whether to display a progress bar for requests.
host	default "https://www.arcgis.com". The host of your ArcGIS Portal.
token	an object of class httr2_token as generated by <code>auth_code()</code> or related function

Details

[Experimental]

Search is quite nuanced and should be handled with care as you may get unexpected results.

- Most arguments are passed as filter parameters to the API endpoint.
- If multiple values are passed to an argument such as tags, the search will use an "OR" statement.
- When multiple arguments are provided, for example tags, owner, and item_type, the search will use "AND" logic—i.e. results shown match the tags **and** owner **and** item_type.
 - Note: you can change this to "OR" behavior by setting filter_logic = "or"
- If the filter argument is provided, all other arguments except query are ignored.

Value

a data.frame.

References

[API Documentation](#)

Examples

```
crime_items <- search_items(
  query = "crime",
  item_type = "Feature Service",
  max_pages = 1
)
crime_items
```

self

Access the Portal Self Resource

Description

The function returns the [/self](#) resource from the ArcGIS REST API. The /self endpoint returns the view of the portal as seen by the current user, whether anonymous or signed in.

Usage

```
arc_self_meta(token = arc_token(), error_call = rlang::current_call())
```

```
arc_portal_self(token = arc_token(), error_call = rlang::current_call())
```

Arguments

token	an object of class httr2_token as generated by auth_code() or related function
error_call	the caller environment to be used when propagating errors.

Details

See the [endpoint documentation](#) for more details.

The Portal Self response can vary based on whether it's called by a user, an app, or both.

The response includes user and appinfo properties, and the variations in responses are primarily related to these two properties. As the names indicate, the user property includes information about the user making the call, and the appinfo property includes information pertaining to the app that made the call.

Value

A named list.

See Also

Other portal: [arc_portal_resources\(\)](#), [arc_portal_urls\(\)](#), [arc_portal_users\(\)](#)

Examples

```
## Not run:
set_arc_token(auth_code())
self <- arc_self_meta()
names(self)

## End(Not run)
```

url

Parse an ArcGIS service or content URL into its components

Description

[arc_url_parse\(\)](#) uses [http2::url_parse\(\)](#) to parse URL components and combine the components with a service or content URL type and a layer number if applicable. A layer component is only included if the type is "MapServer" or "FeatureServer" and the URL includes a trailing digit. A full url value is also included in the returned list. The url, type, and layer components are not part of the http2_url class object returned by [http2::url_parse\(\)](#).

Usage

```
arc_url_parse(url, base_url = NULL, error_call = rlang::caller_call())

arc_url_type(url, error_call = rlang::caller_call())

is_url(url, error_call = rlang::caller_call())
```

Arguments

url	A string containing the URL to parse.
base_url	Use this as a parent, if url is a relative URL.
error_call	the caller environment to be used when propagating errors.

Details

[Experimental]

Value

A named list with the following components: scheme, hostname, username, password, port, path, query, fragment, url, type, and layer.

Examples

```
arc_url_parse(
  "https://services.arcgisonline.com/arcgis/rest/services/USA_Topo_Maps/MapServer/0"
)
arc_url_parse(
  "https://geocode.arcgis.com/arcgis/rest/services/World/GeocodeServer"
)
arc_url_parse(
  "https://services.arcgisonline.com/arcgis/rest/services/WorldElevation3D/Terrain3D/ImageServer"
)
```

 validate_crs

Validate CRS object

Description

Takes a representation of a CRS and ensures that it is a valid one. The CRS is validated using `sf::st_crs()` if it cannot be validated, a null CRS is returned.

Usage

```
validate_crs(crs, arg = rlang::caller_arg(crs), call = rlang::caller_env())
```

Arguments

<code>crs</code>	a representation of a coordinate reference system.
<code>arg</code>	An argument name in the current function.
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.

Details

See `sf::st_crs()` for more details on valid representations.

Value

Returns a list of length 1 with an element named `spatialReference` which is itself a named list.

If the provided CRS returns a valid well-known ID (WKID) `spatialReference` contains a named element called `wkid` which is the integer value of the WKID. If the WKID is not known but the CRS returned is a valid well-known text representation the `wkid` field is NA and another field `wkt` contains the valid wkt.

Examples

```
# using epsg code integer or string representation
validate_crs(3857)
validate_crs("EPSG:4326")

# using a custom proj4 string
proj4string <- "+proj=longlat +datum=WGS84 +no_defs"

crs <- validate_crs(proj4string)

# using wkt2 (from above result)
crs <- validate_crs(crs$spatialReference$wkt)
```

Index

- * **content**
 - content, [34](#)
- * **geoprocessing**
 - arc_form_params, [4](#)
 - arc_gp_job, [5](#)
 - arc_job_status, [11](#)
 - gp_params, [39](#)
- * **portal item**
 - arc_item, [9](#)
 - arc_item_data, [10](#)
- * **portal organization**
 - arc_group, [7](#)
 - arc_user, [18](#)
- * **portal**
 - arc_portal_resources, [12](#)
 - arc_portal_urls, [14](#)
 - arc_portal_users, [14](#)
 - arc_user_self, [18](#)
 - content, [34](#)
 - self, [48](#)
- * **requests**
 - detect_errors, [35](#)
- * **self**
 - arc_user_self, [18](#)

arc_agent, [3](#)
arc_base_req, [3](#)
arc_base_req(), [12](#)
arc_form_params, [4](#), [7](#), [11](#), [41](#)
arc_form_params(), [5](#), [6](#)
arc_gp_job, [5](#), [5](#), [11](#), [41](#)
arc_group, [7](#), [18](#)
arc_group(), [34](#)
arc_group_content(content), [34](#)
arc_host, [8](#)
arc_item, [9](#), [10](#)
arc_item_data, [9](#), [10](#)
arc_job_status, [5](#), [7](#), [11](#), [41](#)
arc_job_status(), [5](#), [6](#)
arc_paginate_req, [11](#)
arc_portal_resources, [12](#), [14](#), [16](#), [49](#)
arc_portal_self(self), [48](#)
arc_portal_self(), [12](#), [13](#), [15](#)
arc_portal_servers, [13](#)
arc_portal_urls, [13](#), [14](#), [16](#), [49](#)
arc_portal_users, [13](#), [14](#), [14](#), [49](#)
arc_self_meta(self), [48](#)
arc_token, [16](#)
arc_token(), [5](#), [6](#)
arc_url_parse(url), [49](#)
arc_url_parse(), [49](#)
arc_url_type(url), [49](#)
arc_user, [8](#), [18](#)
arc_user(), [34](#)
arc_user_content(content), [34](#)
arc_user_self, [18](#)
as.POSIXct(), [47](#)
as_esri_features(as_features), [22](#)
as_esri_featureset(as_featureset), [24](#)
as_esri_featureset(), [30](#)
as_esri_geometry, [19](#)
as_extent, [21](#)
as_feature_collection(as_layer), [28](#)
as_features, [22](#)
as_features(), [20](#)
as_featureset, [24](#)
as_featureset(), [20](#)
as_fields, [26](#)
as_fields(), [26](#)
as_form_params(arc_form_params), [4](#)
as_gp_areal_unit(gp_params), [39](#)
as_gp_date(gp_params), [39](#)
as_gp_feature_record_set(gp_params), [39](#)
as_gp_linear_unit(gp_params), [39](#)
as_gp_raster_layer(gp_params), [39](#)
as_layer, [28](#)
as_layer_definition(as_layer), [28](#)
as_record_set(gp_params), [39](#)
as_spatial_reference(gp_params), [39](#)

auth_binding(auth_code), 31
 auth_client(auth_code), 31
 auth_code, 31
 auth_code(), 4, 12, 13, 15, 47, 48
 auth_key(auth_code), 31
 auth_user(auth_code), 31

 catch_error(detect_errors), 35
 check_dots_named(compact), 33
 check_token_has_user(arc_token), 16
 collapse::rowbind(), 45
 compact, 33
 content, 34

 data.table::rbindlist(), 45
 data_frame(compact), 33
 date_to_ms(is_date), 42
 defused function call, 17, 20, 22, 23, 25, 27, 29, 32, 37, 43, 45, 50
 detect_errors, 35
 determine_dims, 36
 determine_esri_geo_type, 37

 fetch_layer_metadata, 38
 fields_as_ptype_df(as_fields), 26
 from_esri_date(is_date), 42

 gp_areal_unit(gp_params), 39
 gp_linear_unit(gp_params), 39
 gp_params, 5, 7, 11, 39

 has_m(determine_dims), 36
 has_z(determine_dims), 36
 httr2::req_url_path_append(), 4
 httr2::req_url_query(), 4
 httr2::request(), 4
 httr2::url_parse(), 49

 Including function calls in error messages, 17, 20, 22, 23, 25, 27, 29, 32, 37, 43, 45, 50
 infer_esri_type(as_fields), 26
 infer_esri_type(), 30
 is_date, 42
 is_url(url), 49
 item_keyword(portal_types), 44
 item_keyword(), 47
 item_type(portal_types), 44
 item_type(), 47

 new_gp_job(arc_gp_job), 5

 obj_check_token(arc_token), 16

 parse_esri_json, 43
 parse_gp_areal_unit(gp_params), 39
 parse_gp_date(gp_params), 39
 parse_gp_feature_record_set(gp_params), 39
 parse_gp_linear_unit(gp_params), 39
 parse_gp_record_set(gp_params), 39
 parse_spatial_reference(gp_params), 39
 portal_item_keywords(portal_types), 44
 portal_item_keywords(), 44
 portal_item_types(portal_types), 44
 portal_item_types(), 44
 portal_types, 44
 ptype_tbl(as_fields), 26

 rbind_results, 45
 RcppSimdJson::fparse, 43
 refresh_token(auth_code), 31
 rlang::caller_call(), 33
 rlang::caller_env(), 35, 38

 search_items, 46
 self, 13, 14, 16, 48
 set_arc_token(arc_token), 16
 sf::st_crs(), 20, 23, 25, 50

 time zones, 42

 unset_arc_token(arc_token), 16
 url, 49

 validate_crs, 50
 validate_or_refresh_token(auth_code), 31
 validate_or_refresh_token(), 17
 vctrs::list_unchop(), 45