

Package ‘constructive’

September 19, 2025

Title Display Idiomatic Code to Construct Most R Objects

Version 1.3.0

Description Prints code that can be used to recreate R objects. In a sense it is similar to 'base::dput()' or 'base::deparse()' but 'constructive' strives to use idiomatic constructors.

License MIT + file LICENSE

URL <https://github.com/cynkra/constructive>,
<https://cynkra.github.io/constructive/>

BugReports <https://github.com/cynkra/constructive/issues>

Imports cli (>= 3.1.0), diffobj, methods, rlang (>= 1.0.0), waldo

Suggests bit64, blob, clipr, data.table, DiagrammeR, DiagrammeRsvg, dm, dplyr, ellmer, forcats, ggplot2, jsonlite, knitr, lubridate, pixarfilms, R6, reprex, rmarkdown, roxygen2, rstudioapi, S7, scales, sf, testthat (>= 3.0.0), tibble, tidyselect, vctrs, withr, xml2, xts, zoo

VignetteBuilder knitr

Config/Needs/website cynkra/cynkratemplate

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.3.9000

NeedsCompilation yes

Author Antoine Fabri [aut, cre],
Kirill Müller [ctb] (ORCID: <<https://orcid.org/0000-0002-1416-3412>>),
Jacob Scott [ctb],
cynkra GmbH [fnd] (ROR: <<https://ror.org/0335t7e62>>)

Maintainer Antoine Fabri <antoine.fabri@gmail.com>

Repository CRAN

Date/Publication 2025-09-19 14:00:10 UTC

Contents

.cstr_apply	4
.cstr_combine_errors	6
.cstr_construct	7
.cstr_options	8
.cstr_pipe	9
.cstr_repair_attributes	9
.cstr_wrap	10
.env	11
.xptr	11
compare_options	12
construct	13
constructive-global_options	20
construct_clip	20
construct_diff	22
construct_dput	24
construct_dump	26
construct_issues	27
construct_reprex	27
construct_signature	28
deparse_call	29
extend-constructive	30
opts_array	31
opts_AsIs	31
opts_atomic	32
opts_blob	33
opts_character	34
opts_classGeneratorFunction	35
opts_classPrototypeDef	36
opts_classRepresentation	36
opts_complex	37
opts_constructive_options	37
opts_CoordRadial	38
opts_CoordTransform	39
opts_data.frame	39
opts_data.table	40
opts_Date	41
opts_dm	42
opts_dots	43
opts_double	43
opts_ellmer_TypeArray	44
opts_ellmer_TypeBasic	45
opts_ellmer_TypeEnum	45
opts_ellmer_TypeJsonSchema	46
opts_ellmer_TypeObject	47
opts_environment	47
opts_externalptr	49

opts_FacetNull	50
opts_factor	51
opts_formula	52
opts_function	52
opts_ggplot	53
opts_ggplot2_ggplot	54
opts_ggplot2_labels	55
opts_grouped_df	55
opts_GuideAxis	56
opts_GuideAxisLogticks	57
opts_GuideAxisStack	57
opts_GuideAxisTheta	58
opts_GuideBins	59
opts_GuideColourbar	59
opts_GuideColoursteps	60
opts_GuideCustom	61
opts_GuideLegend	61
opts_GuideNone	62
opts_Guides	63
opts_hexmode	63
opts_integer	64
opts_integer64	65
opts_language	65
opts_Layer	66
opts_list	67
opts_logical	68
opts_matrix	69
opts_mts	69
opts_numeric_version	70
opts_object	71
opts_octmode	71
opts_ordered	72
opts_package_version	73
opts_pairlist	73
opts_POSIXct	74
opts_POSIXlt	75
opts_quosure	75
opts_quosures	76
opts_R6	77
opts_R6ClassGenerator	78
opts_raw	78
opts_rowwise_df	79
opts_R_system_version	80
opts_S4	81
opts_S7_any	81
opts_S7_base_class	82
opts_S7_class	83
opts_S7_external_generic	83

opts_S7_generic	84
opts_S7_object	85
opts_S7_property	85
opts_S7_S3_class	86
opts_S7_union	87
opts_tbl_df	87
opts_ts	88
opts_vctrs_list_of	89
opts_weakref	89
opts_xml_document	90
opts_xts	90
opts_yearmon	91
opts_yearqtr	92
opts_zoo	92
opts_zooreg	93
other-opts	94
templates	96

Index	98
--------------	-----------

<i>.cstr_apply</i>	<i>.cstr_apply</i>
--------------------	--------------------

Description

Exported for custom constructor design. If recurse is TRUE (default), we recurse to construct args and insert their construction code in a fun(...) call returned as a character vector. If args already contains code rather than object to construct one should set recurse to FALSE.

Usage

```
.cstr_apply(
  args,
  fun = "list",
  ...,
  trailing_comma = FALSE,
  recurse = TRUE,
  implicit_names = FALSE,
  new_line = TRUE,
  one_liner = FALSE,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE
)
```

Arguments

<code>args</code>	A list of arguments to construct recursively, or code if <code>recurse = FALSE</code> . If elements are named, the arguments will be named in the generated code.
<code>fun</code>	The function name to use to build code of the form <code>"fun(...)"</code>
<code>...</code>	Options passed recursively to the further methods
<code>trailing_comma</code>	Boolean. Whether to leave a trailing comma after the last argument if the code is multiline, some constructors allow it (e.g. <code>tibble::tibble()</code>) and it makes for nicer diffs in version control.
<code>recurse</code>	Boolean. Whether to recursively generate the code to construct args. If <code>FALSE</code> arguments are expected to contain code.
<code>implicit_names</code>	When data is provided, compress calls of the form <code>f(a = a)</code> to <code>f(a)</code>
<code>new_line</code>	Boolean. Forwarded to <code>wrap()</code> to add a line between <code>"fun(" and ")"</code> , forced to <code>FALSE</code> if <code>one_liner</code> is <code>TRUE</code>
<code>one_liner</code>	Boolean. Whether to return a one line call.
<code>unicode_representation</code>	By default <code>"ascii"</code> , which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. <code>"latin"</code> is more lax and uses all latin characters (code point < 256). <code>"character"</code> shows all characters, but not emojis. Finally <code>"unicode"</code> displays all characters and emojis, which is what <code>dput()</code> does.
<code>escape</code>	Boolean. Whether to escape double quotes and backslashes. If <code>FALSE</code> we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on <code>unicode_representation</code> <code>escape = FALSE</code> cannot be applied on all strings.

Value

A character vector of code

Examples

```
a <- 1
.cstr_apply(list(a=a), "foo")
.cstr_apply(list(a=a), "foo", data = list(a=1))
.cstr_apply(list(a=a), "foo", data = list(a=1), implicit_names = TRUE)
.cstr_apply(list(b=a), "foo", data = list(a=1), implicit_names = TRUE)
.cstr_apply(list(a="c(1,2)"), "foo")
.cstr_apply(list(a="c(1,2)"), "foo", recurse = FALSE)
```

`.cstr_combine_errors` *Combine errors*

Description

Exported for custom constructor design. This function allows combining independent checks so information is given about all failing checks rather than the first one. All parameters except `...` are forwarded to `rlang::abort()`

Usage

```
.cstr_combine_errors(
  ...,
  class = NULL,
  call,
  header = NULL,
  body = NULL,
  footer = NULL,
  trace = NULL,
  parent = NULL,
  use_cli_format = NULL,
  .internal = FALSE,
  .file = NULL,
  .frame = parent.frame(),
  .trace_bottom = NULL
)
```

Arguments

<code>...</code>	check expressions
<code>class</code>	Subclass of the condition.
<code>call</code>	The execution environment of a currently running function, e.g. <code>call = caller_env()</code>. The corresponding function call is retrieved and mentioned in error messages as the source of the error. You only need to supply <code>call</code> when throwing a condition from a helper function which wouldn't be relevant to mention in the message. Can also be <code>NULL</code> or a defused function call to respectively not display any call or hard-code a code to display. For more information about error calls, see Including function calls in error messages.
<code>header</code>	An optional header to precede the errors
<code>body, footer</code>	Additional bullets.
<code>trace</code>	A trace object created by trace_back() .
<code>parent</code>	Supply parent when you rethrow an error from a condition handler (e.g. with try_fetch()).

- If `parent` is a condition object, a *chained error* is created, which is useful when you want to enhance an error with more details, while still retaining the original information.
- If `parent` is `NA`, it indicates an unchained rethrow, which is useful when you want to take ownership over an error and rethrow it with a custom message that better fits the surrounding context.
Technically, supplying `NA` lets `abort()` know it is called from a condition handler. This helps it create simpler backtraces where the condition handling context is hidden by default.

For more information about error calls, see [Including contextual information with error chains](#).

<code>use_cli_format</code>	Whether to format message lazily using <code>cli</code> if available. This results in prettier and more accurate formatting of messages. See <code>local_use_cli()</code> to set this condition field by default in your package namespace. If set to <code>TRUE</code> , message should be a character vector of individual and unformatted lines. Any newline character <code>"\\n"</code> already present in message is reformatted by <code>cli</code> 's paragraph formatter. See Formatting messages with cli .
<code>.internal</code>	If <code>TRUE</code> , a footer bullet is added to message to let the user know that the error is internal and that they should report it to the package authors. This argument is incompatible with <code>footer</code> .
<code>.file</code>	A connection or a string specifying where to print the message. The default depends on the context, see the <code>stdout</code> vs <code>stderr</code> section.
<code>.frame</code>	The throwing context. Used as default for <code>.trace_bottom</code> , and to determine the internal package to mention in internal errors when <code>.internal</code> is <code>TRUE</code> .
<code>.trace_bottom</code>	Used in the display of simplified backtraces as the last relevant call frame to show. This way, the irrelevant parts of backtraces corresponding to condition handling (<code>tryCatch()</code> , <code>try_fetch()</code> , <code>abort()</code> , etc.) are hidden by default. Defaults to <code>call</code> if it is an environment, or <code>.frame</code> otherwise. Without effect if <code>trace</code> is supplied.

Value

Returns `NULL` invisibly, called for side effects.

<code>.cstr_construct</code>	<i>Generic for object code generation</i>
------------------------------	---

Description

Exported for custom constructor design. `.cstr_construct()` is basically a naked `construct()`, without the checks, the style, the object post processing etc...

Usage

```
.cstr_construct(x, ..., data = NULL, classes = NULL)
```

Arguments

<code>x</code>	An object, for <code>construct_multi()</code> a named list or an environment.
<code>...</code>	Constructive options built with the <code>opts_*</code> () family of functions. See the "Constructive options" section below.
<code>data</code>	Named list or environment of objects we want to detect and mention by name (as opposed to deparsing them further). Can also contain unnamed nested lists, environments, or package names, in the latter case package exports and datasets will be considered. In case of conflict, the last provided name is considered.
<code>classes</code>	A character vector of classes for which to use idiomatic constructors when available, we can provide a package instead of all its classes, in the "{pkg}" form, and we can use a minus sign (inside the quotes) to exclude rather than include. By default we use idiomatic constructors whenever possible. The special values " <i>*none*</i> " and " <i>*base*</i> " can be used to restrict the idiomatic construction to the objects. See <code>construct_dput()</code> and <code>construct_base()</code> for wrappers around this feature.

Value

A character vector

<code>.cstr_options</code>	<i>Create constructive options</i>
----------------------------	------------------------------------

Description

Exported for custom constructor design.

Usage

```
.cstr_options(class, ...)
```

Arguments

<code>class</code>	A string. An S3 class.
<code>...</code>	Options to set

Value

An object of class `c(paste0("constructive_options_", class), "constructive_options")`

<code>.cstr_pipe</code>	<i>Insert a pipe between two calls</i>
-------------------------	--

Description

Exported for custom constructor design.

Usage

```
.cstr_pipe(x, y, ..., pipe = NULL, one_liner = FALSE, indent = TRUE)
```

Arguments

<code>x</code>	A character vector. The code for the left hand side call.
<code>y</code>	A character vector. The code for the right hand side call.
<code>...</code>	Implemented to collect unused arguments forwarded by the dots of the caller environment.
<code>pipe</code>	A string. The pipe to use, "plus" is useful for ggplot code.
<code>one_liner</code>	A boolean. Whether to paste x, the pipe and y together
<code>indent</code>	A boolean. Whether to indent y on a same line (provided that x and y are strings and one liners themselves)

Value

A character vector

Examples

```
.cstr_pipe("iris", "head(2)", pipe = "magrittr", one_liner = FALSE)
.cstr_pipe("iris", "head(2)", pipe = "magrittr", one_liner = TRUE)
```

<code>.cstr_repair_attributes</code>	<i>Repair attributes after idiomatic construction</i>
--------------------------------------	---

Description

Exported for custom constructor design. In the general case an object might have more attributes than given by the idiomatic construction. `.cstr_repair_attributes()` sets some of those attributes and ignores others.

Usage

```
.cstr_repair_attributes(
  x,
  code,
  ...,
  ignore = NULL,
  idiomatic_class = NULL,
  remove = NULL,
  flag_s4 = TRUE,
  repair_names = FALSE
)
```

Arguments

<code>x</code>	The object to construct
<code>code</code>	The code constructing the object before attribute repair
<code>...</code>	Forwarded to <code>.construct_apply()</code> when relevant
<code>ignore</code>	The attributes that shouldn't be repaired, i.e. we expect them to be set by the constructor already in code
<code>idiomatic_class</code>	The class of the objects that the constructor produces, if <code>x</code> is of class <code>idiomatic_class</code> there is no need to repair the class.
<code>remove</code>	Attributes that should be removed, should rarely be useful.
<code>flag_s4</code>	Boolean. Whether to use <code>asS4()</code> on the code of S4 objects, set to <code>FALSE</code> when a constructor that produces S4 objects was used.
<code>repair_names</code>	Boolean. Whether to repair the names attribute. Generally it is generated by the constructor but it is needed for some corner cases

Value

A character vector

`.cstr_wrap`

Wrap argument code in function call

Description

Exported for custom constructor design. Generally called through `.cstr_apply()`.

Usage

```
.cstr_wrap(args, fun, new_line = FALSE)
```

Arguments

<code>args</code>	A character vector containing the code of arguments.
<code>fun</code>	A string. The name of the function to use in the function call. Use <code>fun = ""</code> to wrap in parentheses.
<code>new_line</code>	Boolean. Whether to insert a new line between <code>"fun("</code> and the closing <code>)"</code> .

Value

A character vector.

<code>.env</code>	<i>Fetch environment from memory address</i>
-------------------	--

Description

This is designed to be used in constructed output. The `parents` and `...` arguments are not processed and only used to display additional information. If used on an improper memory address it will either fail (most likely) or the output will be erratic.

Usage

```
.env(address, parents = NULL, ...)
```

Arguments

<code>address</code>	Memory address of the environment
<code>parents, ...</code>	ignored

Value

The environment that the memory address points to.

<code>.xptr</code>	<i>Build a pointer from a memory address</i>
--------------------	--

Description

Base R doesn't provide utilities to build or manipulate external pointers (objects of type "externalptr"), so we provide our own. Objects defined with `.xptr()` are not stable across sessions,

Usage

```
.xptr(address)
```

Arguments

address Memory address

Value

The external pointer (type "externalptr") that the memory address points to.

compare_options	<i>Options for waldo::compare</i>
-----------------	-----------------------------------

Description

Builds options that will be passed to `waldo::compare()` down the line.

Usage

```
compare_options(
  ignore_srcref = TRUE,
  ignore_attr = FALSE,
  ignore_function_env = FALSE,
  ignore_formula_env = FALSE
)
```

Arguments

`ignore_srcref` Ignore differences in function srcrefs? TRUE by default since the `srcref` does not change the behaviour of a function, only its printed representation.

`ignore_attr` Ignore differences in specified attributes? Supply a character vector to ignore differences in named attributes. By default the "waldo_opts" attribute is listed in `ignore_attr` so that changes to it are not reported; if you customize `ignore_attr`, you will probably want to do this yourself.

For backward compatibility with `all.equal()`, you can also use TRUE, to all ignore differences in all attributes. This is not generally recommended as it is a blunt tool that will ignore many important functional differences.

`ignore_function_env, ignore_formula_env`

Ignore the environments of functions and formulas, respectively? These are provided primarily for backward compatibility with `all.equal()` which always ignores these environments.

Value

A list

construct

*Build code to recreate an object***Description**

- `construct()` builds the code to reproduce one object,
- `construct_multi()` builds the code to reproduce objects stored in a named list or environment.

Usage

```
construct(
  x,
  ...,
  data = NULL,
  pipe = NULL,
  check = NULL,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
  pedantic_encoding = FALSE,
  compare = compare_options(),
  one_liner = FALSE,
  template = getOption("constructive_opts_template"),
  classes = NULL
)

construct_multi(
  x,
  ...,
  data = NULL,
  pipe = NULL,
  check = NULL,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
  pedantic_encoding = FALSE,
  compare = compare_options(),
  one_liner = FALSE,
  template = getOption("constructive_opts_template"),
  classes = NULL,
  include_dotted = TRUE
)
```

Arguments

`x` An object, for `construct_multi()` a named list or an environment.

`...` Constructive options built with the `opts_*`() family of functions. See the "Constructive options" section below.

data	Named list or environment of objects we want to detect and mention by name (as opposed to deparsing them further). Can also contain unnamed nested lists, environments, or package names, in the latter case package exports and datasets will be considered. In case of conflict, the last provided name is considered.
pipe	Which pipe to use, either "base" or "magrittr". Defaults to "base" for R >= 4.2, otherwise to "magrittr".
check	Boolean. Whether to check if the created code reproduces the object using <code>waldo::compare()</code> .
unicode_representation	By default "ascii", which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. "latin" is more lax and uses all latin characters (code point < 256). "character" shows all characters, but not emojis. Finally "unicode" displays all characters and emojis, which is what <code>dput()</code> does.
escape	Boolean. Whether to escape double quotes and backslashes. If FALSE we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on <code>unicode_representation</code> <code>escape = FALSE</code> cannot be applied on all strings.
pedantic_encoding	Boolean. Whether to mark strings with the "unknown" encoding rather than an explicit native encoding ("UTF-8" or "latin1") when it's necessary to reproduce the binary representation exactly. This detail is normally of very little significance. The reason why we're not pedantic by default is that the constructed code might be different in the console and in snapshot tests and reprexes due to the latter rounding some angles, and it would be confusing for users.
compare	Parameters passed to <code>waldo::compare()</code> , built with <code>compare_options()</code> .
one_liner	Boolean. Whether to collapse the output to a single line of code.
template	A list of constructive options built with <code>opts_*()</code> functions, they will be overridden by <code>...</code> . Use it to set a default behavior for <code>{constructive}</code> .
classes	A character vector of classes for which to use idiomatic constructors when available, we can provide a package instead of all its classes, in the "{pkg}" form, and we can use a minus sign (inside the quotes) to exclude rather than include. By default we use idiomatic constructors whenever possible. The special values " <code>*none*</code> " and " <code>*base*</code> " can be used to restrict the idiomatic construction to the objects. See <code>construct_dput()</code> and <code>construct_base()</code> for wrappers around this feature.
include_dotted	Whether to include names starting with dots, this includes <code>.Random.seed</code> in the global environment and objects like <code>.Class</code> and <code>.Generic</code> in the execution environments of S3 methods.

Details

`construct_multi()` recognizes promises (also called lazy bindings), this means that for instance

`construct_multi(environment())` can be called when debugging a function and will construct unevaluated arguments using `delayedAssign()`.

Value

An object of class 'constructive'.

Constructive options

Constructive options provide a way to customize the output of 'construct()'. We can provide calls to 'opts_*()' functions to the '...' argument. Each of these functions targets a specific type or class and is documented on its own page.

- `opts_array`(constructor = c("array", "next"), ...)
- `opts_AsIs`(constructor = c("I", "next"), ...)
- `opts_atomic`(..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE)
- `opts_bibentry`(constructor = c("bibentry", "next"), ...)
- `opts_blob`(constructor = c("blob", "next"), ...)
- `opts_character`(constructor = c("default"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE, unicode_representation = c("ascii", "latin", "character", "unicode"), escape = FALSE)
- `opts_citationFooter`(constructor = c("citFooter", "next"), ...)
- `opts_citationHeader`(constructor = c("citHeader", "next"), ...)
- `opts_classGeneratorFunction`(constructor = c("setClass"), ...)
- `opts_classPrototypeDef`(constructor = c("prototype"), ...)
- `opts_classRepresentation`(constructor = c("getClassDef"), ...)
- `opts_complex`(constructor = c("default"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE)
- `opts_constructive_options`(constructor = c("opts", "next"), ...)
- `opts_CoordCartesian`(constructor = c("default", "coord_cartesian", "next", "environment"), ...)
- `opts_CoordFixed`(constructor = c("coord_fixed", "next", "environment"), ...)
- `opts_CoordFlip`(constructor = c("coord_flip", "next", "environment"), ...)
- `opts_CoordMap`(constructor = c("coord_map", "next", "environment"), ...)
- `opts_CoordMunch`(constructor = c("coord_munch", "next", "environment"), ...)
- `opts_CoordPolar`(constructor = c("coord_polar", "next", "environment"), ...)
- `opts_CoordQuickmap`(constructor = c("coord_quickmap", "next", "environment"), ...)
- `opts_CoordRadial`(constructor = c("coord_radial", "next"), ...)
- `opts_CoordSf`(constructor = c("coord_sf", "next", "environment"), ...)
- `opts_CoordTrans`(constructor = c("coord_trans", "next", "environment"), ...)
- `opts_CoordTransform`(constructor = c("coord_transform", "next"), ...)

- `opts_data.frame`(constructor = c("data.frame", "read.table", "next", "list"), ..., recycle = TRUE)
- `opts_data.table`(constructor = c("data.table", "next", "list"), ..., selfref = FALSE, recycle = TRUE)
- `opts_Date`(constructor = c("as.Date", "as_date", "date", "new_date", "as.Date.numeric", "as_date.numeric", "next", "double"), ..., origin = "1970-01-01")
- `opts_difftime`(constructor = c("as.difftime", "next"), ...)
- `opts_dm`(constructor = c("dm", "next", "list"), ...)
- `opts_dots`(constructor = c("default"), ...)
- `opts_double`(constructor = c("default"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE)
- `opts_element_blank`(constructor = c("element_blank", "next", "list"), ...)
- `opts_element_grob`(constructor = c("element_grob", "next", "list"), ...)
- `opts_element_line`(constructor = c("element_line", "next", "list"), ...)
- `opts_element_rect`(constructor = c("element_rect", "next", "list"), ...)
- `opts_element_render`(constructor = c("element_render", "next", "list"), ...)
- `opts_element_text`(constructor = c("element_text", "next", "list"), ...)
- `opts_ellmer_TypeArray`(constructor = c("type_array", "TypeArray", "next"), ...)
- `opts_ellmer_TypeBasic`(constructor = c("default", "TypeBasic", "next"), ...)
- `opts_ellmer_TypeEnum`(constructor = c("type_enum", "TypeEnum", "next"), ...)
- `opts_ellmer_TypeJsonSchema`(constructor = c("type_from_schema", "TypeJsonSchema", "next"), ...)
- `opts_ellmer_TypeObject`(constructor = c("type_object", "TypeObject", "next"), ...)
- `opts_environment`(constructor = c(".env", "list2env", "as.environment", "new.env", "topenv", "new_environment", "predefine"), ..., recurse = FALSE)
- `opts_error`(constructor = c("errorCondition", "next"), ...)
- `opts_expression`(constructor = c("default"), ...)
- `opts_externalptr`(constructor = c("default"), ...)
- `opts_FacetGrid`(constructor = c("facet_grid", "ggproto", "next", "environment"), ...)
- `opts_FacetNull`(constructor = c("facet_null", "next"), ...)
- `opts_FacetWrap`(constructor = c("facet_wrap", "ggproto", "next", "environment"), ...)
- `opts_factor`(constructor = c("factor", "as_factor", "new_factor", "next", "integer"), ...)
- `opts_formula`(constructor = c("default", "formula", "as.formula", "new_formula", "next"), ..., environment = TRUE)
- `opts_function`(constructor = c("function", "as.function", "new_function"), ..., environment = TRUE, srcref = FALSE, trim = NULL)
- `opts_ggplot`(constructor = c("ggplot", "next", "list"), ...)

- `opts_ggplot2_element_blank`(constructor = c("element_blank", "next"), ...)
- `opts_ggplot2_element_geom`(constructor = c("element_geom", "next"), ...)
- `opts_ggplot2_element_line`(constructor = c("element_line", "next"), ...)
- `opts_ggplot2_element_point`(constructor = c("element_point", "next"), ...)
- `opts_ggplot2_element_polygon`(constructor = c("element_polygon", "next"), ...)
- `opts_ggplot2_element_rect`(constructor = c("element_rect", "next"), ...)
- `opts_ggplot2_element_text`(constructor = c("element_text", "next"), ...)
- `opts_ggplot2_ggplot`(constructor = c("ggplot", "next", "list"), ...)
- `opts_ggplot2_labels`(constructor = c("labs", "next"), ...)
- `opts_ggplot2_mapping`(constructor = c("aes", "next", "list"), ...)
- `opts_ggplot2_margin`(constructor = c("margin", "next", "double"), ...)
- `opts_ggplot2_theme`(constructor = c("theme", "next", "list"), ...)
- `opts_ggproto`(constructor = c("default", "ggproto", "next", "environment"), ...)
- `opts_grouped_df`(constructor = c("default", "next", "list"), ...)
- `opts_Guide`(constructor = c("default", "next", "environment"), ...)
- `opts_GuideAxis`(constructor = c("guide_axis", "next"), ...)
- `opts_GuideAxisLogticks`(constructor = c("guide_axis_logticks", "next"), ...)
- `opts_GuideAxisStack`(constructor = c("guide_axis_stack", "next"), ...)
- `opts_GuideAxisTheta`(constructor = c("guide_axis_theta", "next"), ...)
- `opts_GuideBins`(constructor = c("guide_bins", "next"), ...)
- `opts_GuideColourbar`(constructor = c("guide_colorbar", "next"), ...)
- `opts_GuideColoursteps`(constructor = c("guide_colorsteps", "next"), ...)
- `opts_GuideCustom`(constructor = c("guide_custom", "next"), ...)
- `opts_GuideLegend`(constructor = c("guide_legend", "next"), ...)
- `opts_GuideNone`(constructor = c("guide_none", "next"), ...)
- `opts_Guides`(constructor = c("guides", "next"), ...)
- `opts_hexmode`(constructor = c("as.hexmode", "next"), ..., integer = FALSE)
- `opts_integer`(constructor = c("default"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE)
- `opts_integer64`(constructor = c("as.integer64", "next", "double"), ...)
- `opts_labels`(constructor = c("labs", "next", "list"), ...)
- `opts_language`(constructor = c("default"), ...)
- `opts_Layer`(constructor = c("default", "layer", "next", "environment"), ...)
- `opts_list`(constructor = c("list", "list2"), ..., trim = NULL, fill = c("vector", "new_list", "+", "...", "none"))
- `opts_logical`(constructor = c("default"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE)
- `opts_margin`(constructor = c("margin", "next", "double"), ...)

- `opts_matrix`(constructor = c("matrix", "array", "cbind", "rbind", "next"), ...)
- `opts_mts`(constructor = c("ts", "next", "atomic"), ...)
- `opts_noquote`(constructor = c("noquote", "next"), ...)
- `opts_NULL`(constructor = "NULL", ...)
- `opts_numeric_version`(constructor = c("numeric_version", "next", "list"), ...)
- `opts_object`(constructor = c("prototype", "S7_object"), ...)
- `opts_octmode`(constructor = c("as.octmode", "next"), ..., integer = FALSE)
- `opts_ordered`(constructor = c("ordered", "factor", "new_ordered", "next", "integer"), ...)
- `opts_package_version`(constructor = c("package_version", "next", "list"), ...)
- `opts_pairlist`(constructor = c("pairlist", "pairlist2"), ...)
- `opts_person`(constructor = c("person", "next"), ...)
- `opts_POSIXct`(constructor = c("as.POSIXct", ".POSIXct", "as_datetime", "as.POSIXct.numeric", "as_datetime.numeric", "next", "atomic"), ..., origin = "1970-01-01")
- `opts_POSIXlt`(constructor = c("as.POSIXlt", "next", "list"), ...)
- `opts_quosure`(constructor = c("new_quosure", "next", "language"), ...)
- `opts_quosures`(constructor = c("new_quosures", "next", "list"), ...)
- `opts_R_system_version`(constructor = c("R_system_version", "next", "list"), ...)
- `opts_R6`(constructor = c("R6Class", "next"), ...)
- `opts_R6ClassGenerator`(constructor = c("R6Class", "next"), ...)
- `opts_raw`(constructor = c("as.raw", "charToRaw"), ..., trim = NULL, fill = c("default", "rlang", "+", "...", "none"), compress = TRUE, representation = c("hexadecimal", "decimal"))
- `opts_rel`(constructor = c("rel", "next", "double"), ...)
- `opts_rowwise_df`(constructor = c("default", "next", "list"), ...)
- `opts_S4`(constructor = c("new", "prototype"), ...)
- `opts_S7_any`(constructor = c("class_any", "next"), ...)
- `opts_S7_base_class`(constructor = c("S7", "next"), ...)
- `opts_S7_class`(constructor = c("new_class", "next"), ...)
- `opts_S7_external_generic`(constructor = c("new_external_generic", "next"), ...)
- `opts_S7_generic`(constructor = c("new_generic", "next"), ...)
- `opts_S7_object`(constructor = c("S7_object", "next"), ...)
- `opts_S7_property`(constructor = c("new_property", "next"), ...)
- `opts_S7_S3_class`(constructor = c("new_S3_class", "next"), ...)
- `opts_S7_union`(constructor = c("default", "|", "new_union", "next"), ...)
- `opts_Scale`(constructor = c("default", "next", "environment"), ...)
- `opts_ScalesList`(constructor = c("ScalesList", "next", "list"), ...)
- `opts_simpleCondition`(constructor = c("simpleCondition", "next"), ...)

- `opts_simpleError`(constructor = c("simpleError", "next"), ...)
- `opts_simpleMessage`(constructor = c("simpleMessage", "next"), ...)
- `opts_simpleUnit`(constructor = c("unit", "next", "double"), ...)
- `opts_simpleWarning`(constructor = c("simpleWarning", "next"), ...)
- `opts_tbl_df`(constructor = c("tibble", "tribble", "next", "list"), ..., trailing_comma = TRUE, justify = c("left", "right", "centre", "none"), recycle = TRUE)
- `opts_theme`(constructor = c("theme", "next", "list"), ...)
- `opts_ts`(constructor = c("ts", "next", "atomic"), ...)
- `opts_uneval`(constructor = c("aes", "next", "list"), ...)
- `opts_vctrs_list_of`(constructor = c("list_of", "next", "list"), ...)
- `opts_waiver`(constructor = c("waiver", "next", "list"), ...)
- `opts_warning`(constructor = c("warningCondition", "next"), ...)
- `opts_weakref`(constructor = c("new_weakref"), ...)
- `opts_xml_document`(constructor = c("default", "next"), ..., simplify = TRUE)
- `opts_xts`(constructor = c("as.xts.matrix", "next"), ...)
- `opts_yearmon`(constructor = c("as.yearmon", "yearmon", "next"), ...)
- `opts_yearqtr`(constructor = c("as.yearqtr", "yearqtr", "next"), ...)
- `opts_zoo`(constructor = c("zoo", "next"), ...)
- `opts_zooreg`(constructor = c("zooreg", "next"), ...)

See Also

`construct_dput()` `construct_base()` `construct_clip()` `construct_dump()` `construct_reprex()`
`construct_diff()`

Examples

```
construct(head(cars))
construct(head(cars), opts_data.frame("read.table"))
construct(head(cars), opts_data.frame("next"))
construct(iris$Species)
construct(iris$Species, opts_atomic(compress = FALSE), opts_factor("new_factor"))
construct_multi(list(a = head(cars), b = iris$Species))
```

constructive-global_options
Global Options

Description

Set these options to tweak {constructive}'s global behavior, to set them permanently you can edit your .RProfile1, e.g. using `usethis::edit_r_profile()`.

Details

- Set `options(constructive_print_mode = <character>)` to change the default value of the `print_mode` argument, of `print.constructive`, where `<character>` is a vector of strings among the following :
 - "console" : The default behavior, the code is printed in the console
 - "script" : The code is copied to a new R script
 - "reprex" : The code is shown in the viewer as a reprex, the reprex (not only the code!) is also copied to the clipboard.
 - "clipboard" : The constructed code is copied to the clipboard, if combined with "reprex" this takes precedence (the reprex is showed in the viewer, the code without output is copied to the clipboard)
- Set `options(constructive_opts_template = <list>)` to set default constructive options, see documentation of the `template` arg in `?construct`
- Set `options(constructive_pretty = FALSE)` to disable syntax highlighting.

Relevant options from other packages::

- `cli.code_theme` can be used to configure the syntax highlighting theme used by {constructive}; see `cli::code_theme_list()` for more information.

construct_clip *Construct to clipboard*

Description

This is a simple wrapper for convenience, `construct_clip(x, ...)` is equivalent to `print(construct(x, ...), print_mode = "clipboard")` (an idiom that you might use to use the clipboard with other functions). For more flexible printing options see `?constructive_print_mode`.

Usage

```
construct_clip(
  x,
  ...,
  data = NULL,
  pipe = NULL,
  check = NULL,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
  pedantic_encoding = FALSE,
  compare = compare_options(),
  one_liner = FALSE,
  template = getOption("constructive_opts_template"),
  classes = NULL
)
```

Arguments

<code>x</code>	An object, for <code>construct_multi()</code> a named list or an environment.
<code>...</code>	Constructive options built with the <code>opts_*</code> () family of functions. See the "Constructive options" section below.
<code>data</code>	Named list or environment of objects we want to detect and mention by name (as opposed to deparsing them further). Can also contain unnamed nested lists, environments, or package names, in the latter case package exports and datasets will be considered. In case of conflict, the last provided name is considered.
<code>pipe</code>	Which pipe to use, either "base" or "magrittr". Defaults to "base" for R >= 4.2, otherwise to "magrittr".
<code>check</code>	Boolean. Whether to check if the created code reproduces the object using <code>waldo::compare()</code> .
<code>unicode_representation</code>	By default "ascii", which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. "latin" is more lax and uses all latin characters (code point < 256). "character" shows all characters, but not emojis. Finally "unicode" displays all characters and emojis, which is what <code>dput()</code> does.
<code>escape</code>	Boolean. Whether to escape double quotes and backslashes. If FALSE we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on <code>unicode_representation</code> <code>escape = FALSE</code> cannot be applied on all strings.
<code>pedantic_encoding</code>	Boolean. Whether to mark strings with the "unknown" encoding rather than an explicit native encoding ("UTF-8" or "latin1") when it's necessary to reproduce the binary representation exactly. This detail is normally of very little significance. The reason why we're not pedantic by default is that the constructed code

	might be different in the console and in snapshot tests and reprexes due to the latter rounding some angles, and it would be confusing for users.
compare	Parameters passed to <code>waldo::compare()</code> , built with <code>compare_options()</code> .
one_liner	Boolean. Whether to collapse the output to a single line of code.
template	A list of constructive options built with <code>opts_*()</code> functions, they will be overridden by <code>...</code> . Use it to set a default behavior for <code>{constructive}</code> .
classes	A character vector of classes for which to use idiomatic constructors when available, we can provide a package instead of all its classes, in the <code>"{pkg}"</code> form, and we can use a minus sign (inside the quotes) to exclude rather than include. By default we use idiomatic constructors whenever possible. The special values <code>"*none"</code> and <code>"*base"</code> can be used to restrict the idiomatic construction to the objects. See <code>construct_dput()</code> and <code>construct_base()</code> for wrappers around this feature.

Value

An object of class 'constructive', invisibly. Called for side effects.

Examples

```
## Not run:
construct_clip(head(cars))

## End(Not run)
```

construct_diff	<i>Display diff of object definitions</i>
----------------	---

Description

This calls `construct()` on two objects and compares the output using `diffobj::diffChr()`.

Usage

```
construct_diff(
  target,
  current,
  ...,
  data = NULL,
  pipe = NULL,
  check = TRUE,
  compare = compare_options(),
  one_liner = FALSE,
  template = getOption("constructive_opts_template"),
  classes = NULL,
  mode = c("sidebyside", "auto", "unified", "context"),
  interactive = TRUE
)
```

Arguments

target	the reference object
current	the object being compared to target
...	Constructive options built with the <code>opts_*</code> () family of functions. See the "Constructive options" section below.
data	Named list or environment of objects we want to detect and mention by name (as opposed to deparsing them further). Can also contain unnamed nested lists, environments, or package names, in the latter case package exports and datasets will be considered. In case of conflict, the last provided name is considered.
pipe	Which pipe to use, either "base" or "magrittr". Defaults to "base" for R >= 4.2, otherwise to "magrittr".
check	Boolean. Whether to check if the created code reproduces the object using <code>waldo::compare()</code> .
compare	Parameters passed to <code>waldo::compare()</code> , built with <code>compare_options()</code> .
one_liner	Boolean. Whether to collapse the output to a single line of code.
template	A list of constructive options built with <code>opts_*</code> () functions, they will be overridden by Use it to set a default behavior for {constructive}.
classes	A character vector of classes for which to use idiomatic constructors when available, we can provide a package instead of all its classes, in the "{pkg}" form, and we can use a minus sign (inside the quotes) to exclude rather than include. By default we use idiomatic constructors whenever possible. The special values " <i>*none*</i> " and " <i>*base*</i> " can be used to restrict the idiomatic construction to the objects. See <code>construct_dput()</code> and <code>construct_base()</code> for wrappers around this feature.
mode, interactive	passed to <code>diffobj::diffChr()</code>

Value

Returns NULL invisibly, called for side effects

Examples

```
## Not run:
# some object print the same though they're different
# `construct_diff()` shows how they differ :
df1 <- data.frame(a=1, b = "x")
df2 <- data.frame(a=1L, b = "x", stringsAsFactors = TRUE)
attr(df2, "some_attribute") <- "a value"
df1
df2
construct_diff(df1, df2)

# Those are made easy to compare
construct_diff(substr, substring)
construct_diff(month.abb, month.name)
```

```
# more examples borrowed from {waldo} package
construct_diff(c("a", "b", "c"), c("a", "B", "c"))
construct_diff(c("X", letters), c(letters, "X"))
construct_diff(list(factor("x")), list(1L))
construct_diff(df1, df2)
x <- list(a = list(b = list(c = list(structure(1, e = 1))))))
y <- list(a = list(b = list(c = list(structure(1, e = "a")))))
construct_diff(x, y)

## End(Not run)
```

construct_dput

Construct using only low level constructors

Description

- `construct_dput()` is a closer counterpart to `base::dput()` that doesn't use higher level constructors such as `data.frame()` and `factor()`.
- `construct_base()` uses higher constructors, but only for the classes maintained in the default base R packages. This includes `data.frame()` and `factor()`, the S4 constructors from the 'method' package etc, but not `data.table()` and other constructors for classes from other packages.

Usage

```
construct_dput(
  x,
  ...,
  data = NULL,
  pipe = NULL,
  check = NULL,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
  pedantic_encoding = FALSE,
  compare = compare_options(),
  one_liner = FALSE,
  template = getOption("constructive_opts_template")
)

construct_base(
  x,
  ...,
  data = NULL,
  pipe = NULL,
  check = NULL,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
```

```

    pedantic_encoding = FALSE,
    compare = compare_options(),
    one_liner = FALSE,
    template = getOption("constructive_opts_template")
  )

```

Arguments

<code>x</code>	An object, for <code>construct_multi()</code> a named list or an environment.
<code>...</code>	Constructive options built with the <code>opts_*</code> () family of functions. See the "Constructive options" section below.
<code>data</code>	Named list or environment of objects we want to detect and mention by name (as opposed to deparsing them further). Can also contain unnamed nested lists, environments, or package names, in the latter case package exports and datasets will be considered. In case of conflict, the last provided name is considered.
<code>pipe</code>	Which pipe to use, either "base" or "magrittr". Defaults to "base" for R >= 4.2, otherwise to "magrittr".
<code>check</code>	Boolean. Whether to check if the created code reproduces the object using <code>waldo::compare()</code> .
<code>unicode_representation</code>	By default "ascii", which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. "latin" is more lax and uses all latin characters (code point < 256). "character" shows all characters, but not emojis. Finally "unicode" displays all characters and emojis, which is what <code>dput()</code> does.
<code>escape</code>	Boolean. Whether to escape double quotes and backslashes. If FALSE we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on <code>unicode_representation</code> <code>escape = FALSE</code> cannot be applied on all strings.
<code>pedantic_encoding</code>	Boolean. Whether to mark strings with the "unknown" encoding rather than an explicit native encoding ("UTF-8" or "latin1") when it's necessary to reproduce the binary representation exactly. This detail is normally of very little significance. The reason why we're not pedantic by default is that the constructed code might be different in the console and in snapshot tests and repxes due to the latter rounding some angles, and it would be confusing for users.
<code>compare</code>	Parameters passed to <code>waldo::compare()</code> , built with <code>compare_options()</code> .
<code>one_liner</code>	Boolean. Whether to collapse the output to a single line of code.
<code>template</code>	A list of constructive options built with <code>opts_*</code> () functions, they will be overridden by <code>...</code> . Use it to set a default behavior for <code>{constructive}</code> .

Details

Both functions are valuable for object inspection, and might provide more stable snapshots, since supporting more classes in the package means the default output of `construct()` might change over time for some objects.

To use higher level constructor from the base package itself, excluding for instance `stats::ts()`, `utils::person()` or `methods::classGeneratorFunction()`, we can call `construct(x, classes = "{base}"`

Value

An object of class 'constructive'.

Examples

```
construct_dput(head(iris, 2))
construct_base(head(iris, 2))
```

construct_dump	<i>Dump Constructed Code to a File</i>
----------------	--

Description

An alternative to `base::dump()` using code built with **constructive**.

Usage

```
construct_dump(x, path, append = FALSE, ...)
```

Arguments

<code>x</code>	A named list or an environment.
<code>path</code>	File or connection to write to.
<code>append</code>	If FALSE, will overwrite existing file. If TRUE, will append to existing file. In both cases, if the file does not exist a new file is created.
<code>...</code>	Forwarded to <code>construct_multi()</code>

Value

Returns NULL invisibly, called for side effects.

construct_issues	<i>Show constructive issues</i>
------------------	---------------------------------

Description

Usually called without arguments right after an imperfect code generation, but can also be called on the 'constructive' object itself.

Usage

```
construct_issues(x = NULL)
```

Arguments

x	An object built by <code>construct()</code> , if <code>NULL</code> the latest encountered issues will be displayed
---	--

Value

A character vector with class "waldo_compare"

construct_reprex	<i>construct_reprex</i>
------------------	-------------------------

Description

`construct_reprex()` constructs all objects of the local environment, or a caller environment `n` steps above. If `n > 0` the function call is also included in a comment.

Usage

```
construct_reprex(..., n = 0, include_dotted = TRUE)
```

Arguments

...	Forwarded to <code>construct_multi()</code>
n	The number of steps to go up on the call stack
include_dotted	Whether to include names starting with dots, this includes <code>.Random.seed</code> in the global environment and objects like <code>.Class</code> and <code>.Generic</code> in the execution environments of S3 methods.

Details

construct_reprex() doesn't call the {reprex} package. construct_reprex() builds reproducible data while the reprex package build reproducible output once you have the data.

construct_reprex() wraps construct_multi() and is thus able to construct unevaluated arguments using delayedAssign(). This means we can construct reprexes for functions that use Non Standard Evaluation.

A useful trick is to use options(error = recover) to be able to inspect frames on error, and use construct_reprex() from there to reproduce the data state.

construct_reprex() might fail to reproduce the output of functions that refer to environments other than their caller environment. We believe these are very rare and that the simplicity is worth the rounded corners, but if you encounter these limitations please do open a ticket on our issue tracker at <https://github.com/cynkra/constructive/> and we might expand the feature.

Value

An object of class 'constructive'.

See Also

`construct_multi()`

construct_signature	<i>Construct a function's signature</i>
---------------------	---

Description

Construct a function's signature such as the one you can see right below in the 'Usage' section.

Usage

```
construct_signature(x, name = NULL, one_liner = FALSE, style = TRUE)
```

Arguments

x	A function
name	The name of the function, by default we use the symbol provided to x
one_liner	Boolean. Whether to collapse multi-line expressions on a single line using semi-colons.
style	Boolean. Whether to give a class "constructive_code" on the output for pretty printing.

Value

a string or a character vector, with a class "constructive_code" for pretty printing if style is TRUE

Examples

```
construct_signature(lm)
```

deparse_call	<i>Deparse a language object</i>
--------------	----------------------------------

Description

An alternative to `base::deparse()` and `rlang::expr_deparse()` that handles additional corner cases and fails when encountering tokens other than symbols and syntactic literals where cited alternatives would produce non syntactic code.

Usage

```
deparse_call(
  call,
  one_liner = FALSE,
  pipe = FALSE,
  style = TRUE,
  collapse = !style,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE,
  pedantic_encoding = FALSE
)
```

Arguments

<code>call</code>	A call.
<code>one_liner</code>	Boolean. Whether to collapse multi-line expressions on a single line using semi-colons.
<code>pipe</code>	Boolean. Whether to use the base pipe to disentangle nested calls. This works best on simple calls.
<code>style</code>	Boolean. Whether to give a class "constructive_code" on the output for pretty printing.
<code>collapse</code>	Boolean. Whether to collapse the output to a single string, won't be directly visible if <code>style</code> is TRUE.
<code>unicode_representation</code>	By default "ascii", which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. "latin" is more lax and uses all latin characters (code point < 256). "character" shows all characters, but not emojis. Finally "unicode" displays all characters and emojis, which is what <code>dput()</code> does.

escape	Boolean. Whether to escape double quotes and backslashes. If FALSE we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on <code>unicode_representation</code> <code>escape = FALSE</code> cannot be applied on all strings.
pedantic_encoding	Boolean. Whether to mark strings with the "unknown" encoding rather than an explicit native encoding ("UTF-8" or "latin1") when it's necessary to reproduce the binary representation exactly. This detail is normally of very little significance. The reason why we're not pedantic by default is that the constructed code might be different in the console and in snapshot tests and reprexes due to the latter rounding some angles, and it would be confusing for users.

Value

a string or a character vector, with a class "constructive_code" for pretty printing if `style` is TRUE.

Examples

```
expr <- quote(foo(bar({this; that}, 1)))
deparse_call(expr)
deparse_call(expr, one_liner = TRUE)
deparse_call(expr, pipe = TRUE)
deparse_call(expr, style = FALSE)
```

extend-constructive	<i>Extend constructive</i>
---------------------	----------------------------

Description

We export a collection of functions that can be used to design custom methods for `.cstr_construct()` or custom constructors for a given method.

- `.cstr_new_class()` : Open template to support a new class
- `.cstr_new_constructor()` : Open template to implement a new constructor
- `.cstr_construct()` : Low level generic for object construction code generation
- `.cstr_repair_attributes()` : Helper to repair attributes of objects
- `.cstr_options()` : Define and check options to pass to custom constructors
- `.cstr_apply()` : Build recursively the arguments passed to your constructor
- `.cstr_wrap()` : Wrap argument code in function code (rarely needed)
- `.cstr_pipe()` : Pipe a call to another (rarely needed)
- `.cstr_combine_errors()` : helper function report several errors at once when relevant

opts_array	<i>Constructive options for arrays</i>
------------	--

Description

These options will be used on arrays. Note that arrays can be built on top of vectors, lists or expressions. Canonical arrays have an implicit class "array" shown by `class()` but "array" is not part of the class attribute.

Usage

```
opts_array(constructor = c("array", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "array" (default): Use the `array()` function
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.

Value

An object of class <constructive_options/constructive_options_array>

opts_AsIs	<i>Constructive options for the class AsIs</i>
-----------	--

Description

These options will be used on objects of class `AsIs`. `AsIs` objects are created with `I()` which only prepends "AsIs" to the class attribute.

Usage

```
opts_AsIs(constructor = c("I", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "I" (default): Use the I() function
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried.

Value

An object of class <constructive_options/constructive_options_AsIs>

opts_atomic	<i>Constructive options for atomic types</i>
-------------	--

Description

These options will be used on atomic types ("logical", "integer", "numeric", "complex", "character" and "raw"). They can also be directly provided to atomic types through their own opts_*() function, and in this case the latter will have precedence.

Usage

```
opts_atomic(
  ...,
  trim = NULL,
  fill = c("default", "rlang", "+", "...", "none"),
  compress = TRUE
)
```

Arguments

...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements.
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.

Details

If trim is provided, depending on fill we will present trimmed elements as followed:

- "default" : Use default atomic constructors, so for instance c("a", "b", "c") might become c("a", character(2)).

- "rlang" : Use rlang atomic constructors, so for instance `c("a", "b", "c")` might become `c("a", rlang::new_character(2))`, these rlang constructors create vectors of NAs, so it's different from the default option.
- "+": Use unary +, so for instance `c("a", "b", "c")` might become `c("a", +2)`.
- "...": Use ..., so for instance `c("a", "b", "c")` might become `c("a", ...)`
- "none": Don't represent trimmed elements.

Depending on the case some or all of the choices above might generate code that cannot be executed. The 2 former options above are the most likely to succeed and produce an output of the same type and dimensions recursively. This would at least be the case for data frame.

Value

An object of class `<constructive_options/constructive_options_atomic>`

Examples

```
construct(iris, opts_atomic(trim = 2), check = FALSE) # fill = "default"
construct(iris, opts_atomic(trim = 2, fill = "rlang"), check = FALSE)
construct(iris, opts_atomic(trim = 2, fill = "+"), check = FALSE)
construct(iris, opts_atomic(trim = 2, fill = "..."), check = FALSE)
construct(iris, opts_atomic(trim = 2, fill = "none"), check = FALSE)
construct(iris, opts_atomic(trim = 2, fill = "none"), check = FALSE)
x <- c("a a", "a\u0000000A0a", "a\u0000002002a", "\U430 \U430")
```

opts_blob

Constructive options for class 'blob'

Description

These options will be used on objects of class 'blob'.

Usage

```
opts_blob(constructor = c("blob", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "blob" (default): Use `blob::blob()` on a raw object.
 - "new_blob" (default): Use `blob::new_blob()` on a list of raw objects.
- "as.blob": Use `blob::as_blob()` on a character vector

Use `opts_raw()` and `opts_character()` to tweak the construction of raw or character objects constructed as part of the blob construction.

Value

An object of class `<constructive_options/constructive_options_blob>`

opts_character	<i>Constructive options for type 'character'</i>
----------------	--

Description

These options will be used on objects of type 'character'. This type has a single native constructor, but some additional options can be set.

`unicode_representation` and `escape` are usually better set in the main function (`construct()` or other) so they apply not only on strings but on symbols and argument names as well.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_character(
  constructor = c("default"),
  ...,
  trim = NULL,
  fill = c("default", "rlang", "+", "...", "none"),
  compress = TRUE,
  unicode_representation = c("ascii", "latin", "character", "unicode"),
  escape = FALSE
)
```

Arguments

<code>constructor</code>	String. Method used to construct the object, often the name of a function.
<code>...</code>	Constructive options built with the <code>opts_*</code> () family of functions. See the "Constructive options" section below.
<code>trim</code>	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.

fill	String. Method to use to represent the trimmed elements. See ?opts_atomic
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.
unicode_representation	By default "ascii", which means only ASCII characters (code point < 128) will be used to construct strings and variable names. This makes sure that homographs (different spaces and other identically displayed unicode characters) are printed differently, and avoid possible unfortunate copy and paste auto conversion issues. "latin" is more lax and uses all latin characters (code point < 256). "character" shows all characters, but not emojis. Finally "unicode" displays all characters and emojis, which is what dput() does.
escape	Boolean. Whether to escape double quotes and backslashes. If FALSE we use single quotes to surround strings (including variable and element names) containing double quotes, and raw strings for strings that contain backslashes and/or a combination of single and double quotes. Depending on unicode_representation escape = FALSE cannot be applied on all strings.

Value

An object of class <constructive_options/constructive_options_character>

opts_classGeneratorFunction

Constructive options for class 'classGeneratorFunction'

Description

These options will be used on objects of class 'classGeneratorFunction'.

Usage

```
opts_classGeneratorFunction(constructor = c("setClass"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_classGeneratorFunction>

 opts_classPrototypeDef

Constructive options for class 'classPrototypeDef'

Description

These options will be used on objects of class 'classPrototypeDef'.

Usage

```
opts_classPrototypeDef(constructor = c("prototype"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_classPrototypeDef>

 opts_classRepresentation

Constructive options for class 'classRepresentation'

Description

These options will be used on objects of class 'classRepresentation'.

Usage

```
opts_classRepresentation(constructor = c("getClassDef"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_classRepresentation>

opts_complex	<i>Constructive options for type 'complex'</i>
--------------	--

Description

These options will be used on objects of type 'complex'. This type has a single native constructor, but some additional options can be set.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_complex(
  constructor = c("default"),
  ...,
  trim = NULL,
  fill = c("default", "rlang", "+", "...", "none"),
  compress = TRUE
)
```

Arguments

constructor	String. Method used to construct the object, often the name of a function.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements. See ?opts_atomic
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.

Value

An object of class <constructive_options/constructive_options_complex>

opts_constructive_options	<i>Constructive options for the class constructive_options</i>
---------------------------	--

Description

These options will be used on objects of class constructive_options.

Usage

```
opts_constructive_options(constructor = c("opts", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "opts" : Use the relevant constructive::opts_?() function.
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried.

Value

An object of class <constructive_options/constructive_options_constructive_options>

opts_CoordRadial	<i>Constructive options for class 'CoordRadial'</i>
------------------	---

Description

These options will be used on objects of class 'CoordRadial'.

Usage

```
opts_CoordRadial(constructor = c("coord_radial", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "coord_radial" (default): We build the object using ggplot2::coord_radial().
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_CoordRadial>

opts_CoordTransform *Constructive options for class 'CoordTransform'*

Description

These options will be used on objects of class 'CoordTransform'.

Usage

```
opts_CoordTransform(constructor = c("coord_transform", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "coord_transform" (default): We build the object using `ggplot2::coord_transform()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_CoordTransform>`

opts_data.frame *Constructive options for class 'data.frame'*

Description

These options will be used on objects of class 'data.frame'.

Usage

```
opts_data.frame(
  constructor = c("data.frame", "read.table", "next", "list"),
  ...,
  recycle = TRUE
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
recycle	Boolean. For the "data.frame" constructor. Whether to recycle scalars to compress the output.

Details

Depending on constructor, we construct the object as follows:

- "data.frame" (default): Wrap the column definitions in a `data.frame()` call. If some columns are lists or data frames, we wrap the column definitions in `tibble::tibble()`, then use `as.data.frame()`.
- "read.table": We build the object using `read.table()` if possible, or fall back to `data.frame()`.
- "next": Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list": Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_data.frame>`

opts_data.table	<i>Constructive options for class 'data.table'</i>
-----------------	--

Description

These options will be used on objects of class 'data.table'.

Usage

```
opts_data.table(
  constructor = c("data.table", "next", "list"),
  ...,
  selfref = FALSE,
  recycle = TRUE
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
selfref	Boolean. Whether to include the <code>.internal.selfref</code> attribute. It's probably not useful, hence the default, <code>waldo::compare()</code> is used to assess the output fidelity and doesn't check it, but if you really need to generate code that builds an object identical() to the input you'll need to set this to <code>TRUE.#'</code>
recycle	Boolean. Whether to recycle scalars to compress the output.

Details

Depending on constructor, we construct the object as follows:

- "data.table" (default): Wrap the column definitions in a `data.table()` call.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_data.table>`

opts_Date	<i>Constructive options class 'Date'</i>
-----------	--

Description

These options will be used on objects of class 'date'.

Usage

```
opts_Date(
  constructor = c("as.Date", "as_date", "date", "new_date", "as.Date.numeric",
    "as_date.numeric", "next", "double"),
  ...,
  origin = "1970-01-01"
)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object
origin	Origin to be used, ignored when irrelevant.

Details

Depending on constructor, we construct the object as follows:

- "as.Date" (default): We wrap a character vector with `as.Date()`, if the date is infinite it cannot be converted to character and we wrap a numeric vector and provide an `origin` argument.
- "as_date" : Similar as above but using `lubridate::as_date()`, the only difference is that we never need to supply `origin`.
- "date" : Similar as above but using `lubridate::date()`, it doesn't support infinite dates so we fall back on `lubridate::as_date()` when we encounter them.
- "new_date" : We wrap a numeric vector with `vctrs::new_date()`

- "as.Date.numeric" : We wrap a numeric vector with `as.Date()` and use the provided origin
- "as_date.numeric" : Same as above but using `lubridate::as_date()` and use the provided origin
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "double" : We define as an double vector and repair attributes

If the data is not appropriate for a constructor we fall back to another one appropriately.

Value

An object of class `<constructive_options/constructive_options_Date>`

opts_dm	<i>Constructive options class 'dm'</i>
---------	--

Description

These options will be used on objects of class 'dm'.

Usage

```
opts_dm(constructor = c("dm", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "dm" (default): We use `dm::dm()` and other functions from **dm** to adjust the content.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_dm>`

opts_dots	<i>Constructive options for type '...'</i>
-----------	--

Description

These options will be used on objects of type '...'. These are rarely encountered in practice. By default this function is useless as nothing can be set, this is provided in case users want to extend the method with other constructors.

Usage

```
opts_dots(constructor = c("default"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "default" : We use the construct (function(...) get("\...\"))(a = x, y) which we evaluate in the correct environment.

Value

An object of class <constructive_options/constructive_options_dots>

opts_double	<i>Constructive options for type 'double'</i>
-------------	---

Description

These options will be used on objects of type 'double'. This type has a single native constructor, but some additional options can be set.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_double(
  constructor = c("default"),
  ...,
  trim = NULL,
  fill = c("default", "rlang", "+", "...", "none"),
  compress = TRUE
)
```

Arguments

constructor	String. Method used to construct the object, often the name of a function.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements. See ?opts_atomic
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.

Value

An object of class <constructive_options/constructive_options_double>

opts_ellmer_TypeArray *Constructive options for class 'ellmer::TypeArray'*

Description

These options will be used on objects of class 'ellmer::TypeArray'.

Usage

```
opts_ellmer_TypeArray(constructor = c("type_array", "TypeArray", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "TypeArray" (default): We build the object using `ellmer::TypeArray()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_ellmer::TypeArray'>

opts_ellmer_TypeBasic *Constructive options for class 'ellmer::TypeBasic'*

Description

These options will be used on objects of class 'ellmer::TypeBasic'.

Usage

```
opts_ellmer_TypeBasic(constructor = c("default", "TypeBasic", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "TypeBasic" (default): We build the object using `ellmer::TypeBasic()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_ellmer::TypeBasic>

opts_ellmer_TypeEnum *Constructive options for class 'ellmer::TypeEnum'*

Description

These options will be used on objects of class 'ellmer::TypeEnum'.

Usage

```
opts_ellmer_TypeEnum(constructor = c("type_enum", "TypeEnum", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "TypeEnum" (default): We build the object using `ellmer::TypeEnum()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_ellmer::TypeEnum>`

opts_ellmer_TypeJsonSchema

Constructive options for class 'ellmer::TypeJsonSchema'

Description

These options will be used on objects of class `'ellmer::TypeJsonSchema'`.

Usage

```
opts_ellmer_TypeJsonSchema(
  constructor = c("type_from_schema", "TypeJsonSchema", "next"),
  ...
)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "TypeJsonSchema" (default): We build the object using `ellmer::TypeJsonSchema()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_ellmer::TypeJsonSchema>`

 opts_ellmer_TypeObject

Constructive options for class 'ellmer::TypeObject'

Description

These options will be used on objects of class 'ellmer::TypeObject'.

Usage

```
opts_ellmer_TypeObject(
  constructor = c("type_object", "TypeObject", "next"),
  ...
)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "TypeObject" (default): We build the object using `ellmer::TypeObject()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_ellmer::TypeObject>

 opts_environment

Constructive options for type 'environment'

Description

Environments use reference semantics, they cannot be copied. An attempt to copy an environment would indeed yield a different environment and `identical(env, copy)` would be `FALSE`.

Moreover most environments have a parent (exceptions are `emptyenv()` and some rare cases where the parent is `NULL`) and thus to copy the environment we'd have to have a way to point to the parent, or copy it too.

For this reason environments are **constructive**'s cryptonite. They make some objects impossible to reproduce exactly. And since every function or formula has one they're hard to avoid.

Usage

```
opts_environment(
  constructor = c(".env", "list2env", "as.environment", "new.env", "topenv",
    "new_environment", "predefine"),
  ...,
  recurse = FALSE
)
```

Arguments

constructor	String. Name of the function used to construct the environment, see Constructors section.
...	Additional options used by user defined constructors through the opts object
recurse	Boolean. Only considered if constructor is "list2env" or "new_environment". Whether to attempt to recreate all parent environments until a known environment is found, if FALSE (the default) we will use toplevel() to find a known ancestor to set as the parent.

Details

In some case we can build code that points to a specific environment, namely:

- .GlobalEnv, .BaseNamespaceEnv, baseenv() and emptyenv() are used to construct the global environment, the base namespace, the base package environment and the empty environment
- Namespaces are constructed using asNamespace("pkg")
- Package environments are constructed using as.environment("package:pkg")
- "imports" environments are constructed with parent.env(asNamespace("pkg"))
- "lazydata" environments are constructed with getNamespaceInfo("pkg", "lazydata")

By default For other environments we use **constructive**'s function constructive::.env(), it fetches the environment from its memory address and provides as additional information the sequence of parents until we reach a special environment (those enumerated above). The advantage of this approach is that it's readable and that the object is accurately reproduced. The inconvenient is that it's not stable between sessions. If an environment has a NULL parent it's always constructed with constructive::.env(), whatever the choice of the constructor.

Often however we wish to be able to reproduce from scratch a similar environment, so that we might run the constructed code later in a new session. We offer different different options to do this, with different trade-offs regarding accuracy and verbosity.

{constructive} will not signal any difference if it can reproduce an equivalent environment, defined as containing the same values and having a same or equivalent parent.

See also the ignore_function_env argument in ?compare_options, which disables the check of environments of function.

Value

An object of class <constructive_options/constructive_options_environment>

Constructors

We might set the constructor argument to:

- ".env" (default): use `constructive::.env()` to construct the environment from its memory address.
- "list2env": We construct the environment as a list then use `base::list2env()` to convert it to an environment and assign it a parent. By default we use as a parent the first special environment we find when going through ancestors, so we can print code that doesn't use `.env()`. If `recurse` is `TRUE` the parent will be built recursively so all ancestors will be created until we meet a known environment, this might be verbose and will fail if environments are nested too deep or have a circular relationship. If the environment is empty we use `new.env(parent=)` for a more economic syntax.
- "new_environment" : Similar to the above, but using `rlang::new_environment()`.
- "new.env" : All environments will be recreated with the code `"base::new.env()"`, without argument, effectively creating an empty environment child of the local (often global) environment. This is enough in cases where the environment doesn't matter (or matters as long as it inherits from the local environment), as is often the case with formulas. `recurse` is ignored.
- "as.environment" : we attempt to construct the environment as a list and use `base::as.environment()` on top of it, as in `as.environment(list(a=1, b=2))`, it will contain the same variables as the original environment but the parent will be the `emptyenv()`. `recurse` is ignored.
- "topenv" : we construct `base::topenv(x)`, see `?topenv`. `recurse` is ignored. This is the most accurate we can be when constructing only special environments.
- "predefine" : Building environments from scratch using the above methods can be verbose, sometimes redundant and sometimes even impossible due to circularity (e.g. an environment referencing itself). With "predefine" we define the environments and their content above the object returning call, using placeholder names `..env.1..`, `..env.2..` etc. The caveat is that the created code won't be a single call and will create objects in the workspace. `recurse` is ignored.

opts_externalptr

Constructive options for type 'externalptr'

Description

These options will be used on objects of type 'externalptr'. By default this function is useless as nothing can be set, this is provided in case users want to extend the method with other constructors.

Usage

```
opts_externalptr(constructor = c("default"), ...)
```

Arguments

constructor String. Name of the function used to construct the object.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "default" : We use a special function from the constructive

Value

An object of class <constructive_options/constructive_options_externalptr>

opts_FacetNull	<i>Constructive options for class 'FacetNull'</i>
----------------	---

Description

These options will be used on objects of class 'FacetNull'.

Usage

```
opts_FacetNull(constructor = c("facet_null", "next"), ...)
```

Arguments

constructor String. Name of the function used to construct the object.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "facet_null" (default): We build the object using `ggplot2::facet_null()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_FacetNull>

opts_factor	<i>Constructive options for class 'factor'</i>
-------------	--

Description

These options will be used on objects of class 'factor'.

Usage

```
opts_factor(
  constructor = c("factor", "as_factor", "new_factor", "next", "integer"),
  ...
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "factor" (default): Build the object using `factor()`, levels won't be defined explicitly if they are in alphabetical order (locale dependent!)
- "as_factor" : Build the object using `forcats::as_factor()` whenever possible, i.e. when levels are defined in order of appearance in the vector. Otherwise falls back to "factor" constructor.
- "new_factor" : Build the object using `vctrs::new_factor()`. Levels are always defined explicitly.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "integer" : We define as an integer vector and repair attributes.

Value

An object of class `<constructive_options/constructive_options_factor>`

opts_formula	<i>Constructive options for formulas</i>
--------------	--

Description

These options will be used on formulas, defined as calls to `~`, regardless of their "class" attribute.

Usage

```
opts_formula(
  constructor = c("default", "formula", "as.formula", "new_formula", "next"),
  ...,
  environment = TRUE
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
environment	Boolean. Whether to attempt to construct the environment, if it makes a difference to construct it.

Depending on constructor, we construct the formula as follows:

- "default": We construct the formula in the most common way using the `~` operator.
- "formula" : deparse the formula as a string and use `base::formula()` on top of it.
- "as.formula" : Same as above, but using `base::as.formula()`.
- "new_formula" : extract both sides of the formula as separate language objects and feed them to `rlang::new_formula()`, along with the reconstructed environment if relevant.

Value

An object of class `<constructive_options/constructive_options_formula>`

opts_function	<i>Constructive options for functions</i>
---------------	---

Description

These options will be used on functions, i.e. objects of type "closure", "special" and "builtin".

Usage

```
opts_function(
  constructor = c("function", "as.function", "new_function"),
  ...,
  environment = TRUE,
  srcref = FALSE,
  trim = NULL
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
environment	Boolean. Whether to reconstruct the function's environment.
srcref	Boolean. Whether to attempt to reconstruct the function's srcref.
trim	NULL or integerish. Maximum of lines showed in the body before it's trimmed, replacing code with ... Note that it will necessarily produce code that doesn't reproduce the input, but it will parse and evaluate without failure.

Details

Depending on constructor, we construct the object as follows:

- "function" (default): Build the object using a standard function() {} definition. This won't set the environment by default, unless environment is set to TRUE. If a srcref is available, if this srcref matches the function's definition, and if trim is left NULL, the code is returned from using the srcref, so comments will be shown in the output of construct(). In the rare case where the ast body of the function contains non syntactic nodes this constructor cannot be used and falls back to the "as.function" constructor.
- "as.function": Build the object using a as.function() call. back to data.frame().
- "new_function": Build the object using a rlang::new_function() call.

Value

An object of class <constructive_options/constructive_options_function>

 opts_ggplot

Constructive options for class 'ggplot'

Description

These options will be used on objects of class 'ggplot'.

Usage

```
opts_ggplot(constructor = c("ggplot", "next", "list"), ...)
```

Arguments

constructor String. Name of the function used to construct the object, see Details section.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "ggplot" (default): Use `ggplot2::ggplot()`
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_ggplot>`

opts_ggplot2_ggplot *Constructive options for class 'ggplot2::ggplot'*

Description

These options will be used on objects of class `'ggplot2::ggplot'`.

Usage

```
opts_ggplot2_ggplot(constructor = c("ggplot", "next", "list"), ...)
```

Arguments

constructor String. Name of the function used to construct the object, see Details section.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "ggplot" (default): Use `ggplot2::ggplot()`
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_ggplot2::ggplot>`

opts_ggplot2_labels *Constructive options for class 'ggplot2::labels'*

Description

These options will be used on objects of class 'ggplot2::labels'.

Usage

```
opts_ggplot2_labels(constructor = c("labs", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "labs" (default): We build the object using `ggplot2::labs()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_ggplot2::labels>

opts_grouped_df *Constructive options for class 'grouped_df'*

Description

These options will be used on objects of class 'grouped_df'.

Usage

```
opts_grouped_df(constructor = c("default", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : We define as an list object and repair attributes.

Value

An object of class `<constructive_options/constructive_options_factor>`

opts_GuideAxis	<i>Constructive options for class 'GuideAxis'</i>
----------------	---

Description

These options will be used on objects of class 'GuideAxis'.

Usage

```
opts_GuideAxis(constructor = c("guide_axis", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_axis" (default): We build the object using `ggplot2::guide_axis()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideAxis>`

 opts_GuideAxisLogticks

Constructive options for class 'GuideAxisLogticks'

Description

These options will be used on objects of class 'GuideAxisLogticks'.

Usage

```
opts_GuideAxisLogticks(constructor = c("guide_axis_logticks", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_axis_logticks" (default): We build the object using `ggplot2::guide_axis_logticks()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideAxisLogticks>`

 opts_GuideAxisStack

Constructive options for class 'GuideAxisStack'

Description

These options will be used on objects of class 'GuideAxisStack'.

Usage

```
opts_GuideAxisStack(constructor = c("guide_axis_stack", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_axis_stack" (default): We build the object using `ggplot2::guide_axis_stack()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideAxisStack>`

opts_GuideAxisTheta	<i>Constructive options for class 'GuideAxisTheta'</i>
---------------------	--

Description

These options will be used on objects of class 'GuideAxisTheta'.

Usage

```
opts_GuideAxisTheta(constructor = c("guide_axis_theta", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_axis_theta" (default): We build the object using `ggplot2::guide_axis_theta()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideAxisTheta>`

opts_GuideBins	<i>Constructive options for class 'GuideBins'</i>
----------------	---

Description

These options will be used on objects of class 'GuideBins'.

Usage

```
opts_GuideBins(constructor = c("guide_bins", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_bins" (default): We build the object using `ggplot2::guide_bins()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_GuideBins>

opts_GuideColourbar	<i>Constructive options for class 'GuideColourbar'</i>
---------------------	--

Description

These options will be used on objects of class 'GuideColourbar'.

Usage

```
opts_GuideColourbar(constructor = c("guide_colorbar", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_colorbar" (default): We build the object using `ggplot2::guide_colorbar()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideColourbar>`

opts_GuideColoursteps *Constructive options for class 'GuideColoursteps'*

Description

These options will be used on objects of class 'GuideColoursteps'.

Usage

```
opts_GuideColoursteps(constructor = c("guide_colorsteps", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_colorsteps" (default): We build the object using `ggplot2::guide_colorsteps()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideColoursteps>`

opts_GuideCustom	<i>Constructive options for class 'GuideCustom'</i>
------------------	---

Description

These options will be used on objects of class 'GuideCustom'.

Usage

```
opts_GuideCustom(constructor = c("guide_custom", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_custom" (default): We build the object using `ggplot2::guide_custom()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideCustom>`

opts_GuideLegend	<i>Constructive options for class 'GuideLegend'</i>
------------------	---

Description

These options will be used on objects of class 'GuideLegend'.

Usage

```
opts_GuideLegend(constructor = c("guide_legend", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guide_legend" (default): We build the object using `ggplot2::guide_legend()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideLegend>`

opts_GuideNone	<i>Constructive options for class 'GuideNone'</i>
----------------	---

Description

These options will be used on objects of class 'GuideNone'.

Usage

```
opts_GuideNone(constructor = c("guide_none", "next"), ...)
```

Arguments

- | | |
|-------------|--|
| constructor | String. Name of the function used to construct the object. |
| ... | Additional options used by user defined constructors through the opts object |

Details

Depending on constructor, we construct the object as follows:

- "guide_none" (default): We build the object using `ggplot2::guide_none()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_GuideNone>`

opts_Guides	<i>Constructive options for class 'Guides'</i>
-------------	--

Description

These options will be used on objects of class 'Guides'.

Usage

```
opts_Guides(constructor = c("guides", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "guides" (default): We build the object using `ggplot2::guides()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_Guides>

opts_hexmode	<i>Constructive options for class 'hexmode'</i>
--------------	---

Description

These options will be used on objects of class 'hexmode'.

Usage

```
opts_hexmode(constructor = c("as.hexmode", "next"), ..., integer = FALSE)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object
integer	Whether to use <code>as.hexmode()</code> on integer rather than character

Details

Depending on constructor, we construct the object as follows:

- "as.hexmode" (default): We build the object using `as.hexmode()`
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_hexmode>`

opts_integer	<i>Constructive options for type 'integer'</i>
--------------	--

Description

These options will be used on objects of type 'integer'. This type has a single native constructor, but some additional options can be set.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_integer(
  constructor = c("default"),
  ...,
  trim = NULL,
  fill = c("default", "rlang", "+", "...", "none"),
  compress = TRUE
)
```

Arguments

constructor	String. Method used to construct the object, often the name of a function.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements. See <code>?opts_atomic</code>
compress	Boolean. If TRUE instead of <code>c()</code> Use <code>seq()</code> , <code>rep()</code> when relevant to simplify the output.

Value

An object of class `<constructive_options/constructive_options_integer>`

opts_integer64	<i>Constructive options for class 'integer64'</i>
----------------	---

Description

These options will be used on objects of class 'integer64'.

Usage

```
opts_integer64(constructor = c("as.integer64", "next", "double"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as.integer64" (default): Build the object using `as.integer64()` on a character vector.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "double" : We define as an atomic vector and repair attributes.

We don't recommend the "next" and "double" constructors for this class as they give incorrect results on negative or NA "integer64" objects due to some quirks in the implementation of the 'bit64' package.

Value

An object of class `<constructive_options/constructive_options_integer64>`

opts_language	<i>Constructive options for type 'language'</i>
---------------	---

Description

These options will be used on objects of type 'language'. By default this function is useless as nothing can be set, this is provided in case users want to extend the method with other constructors.

Usage

```
opts_language(constructor = c("default"), ...)
```

Arguments

constructor String. Name of the function used to construct the object.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "default" : We use constructive's deparsing algorithm on attributeless calls, and use `as.call()` on other language elements when attributes need to be constructed.

Value

An object of class `<constructive_options/constructive_options_language>`

opts_Layer	<i>Constructive options for class 'Layer' (ggplot2)</i>
------------	---

Description

These options will be used on objects of class 'Layer'.

Usage

```
opts_Layer(constructor = c("default", "layer", "next", "environment"), ...)
```

Arguments

constructor String. Name of the function used to construct the object, see Details section.
 ... Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "default" : We attempt to use the function originally used to create the plot.
- "layer" : We use the `ggplot2::layer()` function
- "environment" : Reconstruct the object using the general environment method (which can be itself tweaked using `opts_environment()`)

The latter constructor is the only one that reproduces the object exactly since Layers are environments and environments can't be exactly copied (see `?opts_environment`)

Value

An object of class `<constructive_options/constructive_options_Layer>`

opts_list

*Constructive options for type 'list'***Description**

These options will be used on objects of type 'list'.

Usage

```
opts_list(
  constructor = c("list", "list2"),
  ...,
  trim = NULL,
  fill = c("vector", "new_list", "+", "...", "none")
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements.

Details

Depending on constructor, we construct the object as follows:

- "list" (default): Build the object by calling `list()`.
- "list2": Build the object by calling `rlang::list2()`, the only difference with the above is that we keep a trailing comma when the list is not trimmed and the call spans several lines.

If trim is provided, depending on fill we will present trimmed elements as followed:

- "vector" (default): Use `vector()`, so for instance `list("a", "b", "c")` might become `c(list("a"), vector("list", 2))`.
- "new_list": Use `rlang::new_list()`, so for instance `list("a", "b", "c")` might become `c(list("a"), rlang::new_list(2))`.
- "+": Use unary `+`, so for instance `list("a", "b", "c")` might become `list("a", +2)`.
- "...": Use `...`, so for instance `list("a", "b", "c")` might become `list("a", ...)`
- "none": Don't represent trimmed elements.

When trim is used the output is parsable but might not be possible to evaluate, especially with `fill = "..."`. In that case you might want to set `check = FALSE`

Value

An object of class <constructive_options/constructive_options_list>

opts_logical	<i>Constructive options for type 'logical'</i>
--------------	--

Description

These options will be used on objects of type 'logical'. This type has a single native constructor, but some additional options can be set.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_logical(  
  constructor = c("default"),  
  ...,  
  trim = NULL,  
  fill = c("default", "rlang", "+", "...", "none"),  
  compress = TRUE  
)
```

Arguments

constructor	String. Method used to construct the object, often the name of a function.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements. See ?opts_atomic
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.

Value

An object of class <constructive_options/constructive_options_logical>

opts_matrix	<i>Constructive options for matrices</i>
-------------	--

Description

Matrices are atomic vectors, lists, or objects of type "expression" with a "dim" attributes of length 2.

Usage

```
opts_matrix(constructor = c("matrix", "array", "cbind", "rbind", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "matrix" : We use matrix()
- "array" : We use array()
- "cbind","rbind" : We use cbind() or "rbind()", this makes named columns and rows easier to read.
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried. This will usually be equivalent to "array"
- "atomic" : We define as an atomic vector and repair attributes

Value

An object of class <constructive_options/constructive_options_matrix>

opts_mts	<i>Constructive options for time-series objets</i>
----------	--

Description

Depending on constructor, we construct the object as follows:

- "ts" : We use ts()
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried. This will usually be equivalent to "atomic"
- "atomic" : We define as an atomic vector and repair attributes

Usage

```
opts_mts(constructor = c("ts", "next", "atomic"), ...)
```

Arguments

constructor String. Name of the function used to construct the object.
 ... Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_mts>

opts_numeric_version *Constructive options for numeric_version*

Description

Depending on constructor, we construct the object as follows:

- "numeric_version" : We use numeric_version()
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried. This will usually be equivalent to "list"
- "list" : We define as a list and repair attributes

Usage

```
opts_numeric_version(constructor = c("numeric_version", "next", "list"), ...)
```

Arguments

constructor String. Name of the function used to construct the object.
 ... Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_numeric_version>

opts_object	<i>Constructive options for class 'object'</i>
-------------	--

Description

These options will be used on objects of class 'object'. The 'object' type is particular in that it is an internal type in base R, but can only be produced at time of writing through the 'S7' package. Well this is not completely true since those can be built from S4 objects that we remove the S4 flag from by using `asS3(x, complete = FALSE)` but we don't propose this for now.

Usage

```
opts_object(constructor = c("prototype", "S7_object"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "S7_object" (default): We build the object using `S7::S7_object()`. At the time of writing, this is currently the only way to create these objects.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_object>

opts_octmode	<i>Constructive options for class 'octmode'</i>
--------------	---

Description

These options will be used on objects of class 'octmode'.

Usage

```
opts_octmode(constructor = c("as.octmode", "next"), ..., integer = FALSE)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object
integer	Whether to use <code>as.octmode()</code> on integer rather than character

Details

Depending on constructor, we construct the object as follows:

- "as.octmode" (default): We build the object using `as.octmode()`
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_octmode>`

opts_ordered	<i>Constructive options for class 'ordered'</i>
--------------	---

Description

These options will be used on objects of class 'ordered'.

Usage

```
opts_ordered(
  constructor = c("ordered", "factor", "new_ordered", "next", "integer"),
  ...
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "ordered" (default): Build the object using `ordered()`, levels won't be defined explicitly if they are in alphabetical order (locale dependent!)
- "factor" : Same as above but build the object using `factor()` and `ordered = TRUE`.
- "new_ordered" : Build the object using `vctrs::new_ordered()`. Levels are always defined explicitly.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "integer" : We define as an integer vector and repair attributes

Value

An object of class `<constructive_options/constructive_options_ordered>`

opts_package_version *Constructive options for package_version*

Description

Depending on constructor, we construct the object as follows:

- "package_version" : We use package_version()
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried. This will usually be equivalent to "array"
- "list" : We define as a list and repair attributes

Usage

```
opts_package_version(constructor = c("package_version", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_package_version>

opts_pairlist *Constructive options for pairlists*

Description

Depending on constructor, we construct the object as follows:

- "pairlist" (default): Build the object using a pairlist() call.
- "pairlist2" : Build the object using a rlang::pairlist2() call.

Usage

```
opts_pairlist(constructor = c("pairlist", "pairlist2"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_pairlist>

opts_POSIXct

*Constructive options for class 'POSIXct'***Description**

These options will be used on objects of class 'POSIXct'.

Usage

```
opts_POSIXct(
  constructor = c("as.POSIXct", ".POSIXct", "as_datetime", "as.POSIXct.numeric",
    "as_datetime.numeric", "next", "atomic"),
  ...,
  origin = "1970-01-01"
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
origin	Origin to be used, ignored when irrelevant.

Details

Depending on constructor, we construct the object as follows:

- "as.POSIXct" (default): Build the object using a `as.POSIXct()` call on a character vector.
- ".POSIXct" : Build the object using a `.POSIXct()` call on a numeric vector.
- "as_datetime" : Build the object using a `lubridate::as_datetime()` call on a character vector.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "atomic" : We define as an atomic vector and repair attributes.

If the data is not appropriate for a constructor we fall back to another one appropriately. In particular corrupted POSIXct objects such as those defined on top of integers (or worse) are all constructed with the ".POSIXct" constructor.

Value

An object of class `<constructive_options/constructive_options_POSIXct>`

opts_POSIXlt	<i>Constructive options for class 'POSIXlt'</i>
--------------	---

Description

These options will be used on objects of class 'POSIXlt'.

Usage

```
opts_POSIXlt(constructor = c("as.POSIXlt", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as.POSIXlt" (default): Build the object using a `as.POSIXlt()` call on a character vector.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : We define as a list and repair attributes.

Value

An object of class <constructive_options/constructive_options_POSIXlt>

opts_quosure	<i>Constructive options for class 'quosure'</i>
--------------	---

Description

These options will be used on objects of class 'quosure'.

Usage

```
opts_quosure(constructor = c("new_quosure", "next", "language"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new_quosure" (default): Build the object using a new_quosure() call on a character vector.
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried.
- "language" : We define as an language object and repair attributes.

Value

An object of class <constructive_options/constructive_options_quosure>

opts_quosures	<i>Constructive options for class 'quosures'</i>
---------------	--

Description

These options will be used on objects of class 'quosures'.

Usage

```
opts_quosures(constructor = c("new_quosures", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as_quosures" (default): Build the object using a as_quosures() call on a character vector.
- "next" : Use the constructor for the next supported class. Call .class2() on the object to see in which order the methods will be tried.
- "list" : We define as an list object and repair attributes.

Value

An object of class <constructive_options/constructive_options_quosures>

opts_R6

*Constructive options for class 'R6'***Description**

These options will be used on objects of class 'R6'.

Usage

```
opts_R6(constructor = c("R6Class", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "R6Class" (default): We build the object using `R6Class()$new()`, see details.
- "next" : Use the constructor for the next supported class.

Objects of class "R6" are harder to construct than "R6ClassGenerator" objects, because 'constructive' doesn't know by default the constructor (i.e. class generator) that was used to build them. So what we do is we build a class generator that generates this object by default. This is why the generated code is in the form `R6Class()$new()`.

Another layer of complexity is added when the object features an `initialize()` method, we cannot implement it in the class generator because it might change the behavior of `$new()` and return a wrong result (or fail). For this reason the `initialize()` method when it exists is repaired as an extra step.

`construct_diff()` works well to inspect the differences between two R6 objects where alternatives like `waldo::compare()` or `base::all.equal()` don't return anything informative.

Value

An object of class `<constructive_options/constructive_options_R6>`

opts_R6ClassGenerator *Constructive options for class 'R6ClassGenerator'*

Description

These options will be used on objects of class 'R6ClassGenerator'.

Usage

```
opts_R6ClassGenerator(constructor = c("R6Class", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "R6Class" (default): We build the object using R6Class().
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_R6ClassGenerator>

opts_raw *Constructive options for type 'raw'*

Description

These options will be used on objects of type 'raw'.

Depending on constructor, we construct the object as follows:

- "as.raw" (default): Use as.raw(), or raw() when relevant
- "charToRaw" : Use charToRaw() on a string, if the a raw vector contains a zero we fall back to the "as.raw" constructor.

To set options on all atomic types at once see [opts_atomic\(\)](#).

Usage

```
opts_raw(  
  constructor = c("as.raw", "charToRaw"),  
  ...,  
  trim = NULL,  
  fill = c("default", "rlang", "+", "...", "none"),  
  compress = TRUE,  
  representation = c("hexadecimal", "decimal")  
)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object
trim	NULL or integerish. Maximum of elements showed before it's trimmed. Note that it will necessarily produce code that doesn't reproduce the input. This code will parse without failure but its evaluation might fail.
fill	String. Method to use to represent the trimmed elements. See ?opts_atomic
compress	Boolean. If TRUE instead of c() Use seq(), rep() when relevant to simplify the output.
representation	For "as.raw" constructor. Respectively generate output in the formats as.raw(0x10) or as.raw(16)

Value

An object of class <constructive_options/constructive_options_raw>

opts_rowwise_df	<i>Constructive options for class 'rowwise_df'</i>
-----------------	--

Description

These options will be used on objects of class 'rowwise_df'.

Usage

```
opts_rowwise_df(constructor = c("default", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : We define as an list object and repair attributes.

Value

An object of class `<constructive_options/constructive_options_rowwise_df>`

opts_R_system_version *Constructive options for R_system_version*

Description

Depending on constructor, we construct the object as follows:

- "R_system_version" : We use `R_system_version()`
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried. This will usually be equivalent to "list"
- "list" : We define as a list and repair attributes

Usage

```
opts_R_system_version(constructor = c("R_system_version", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Value

An object of class `<constructive_options/constructive_options_R_system_version>`

opts_S4	<i>Constructive options for class 'S4'</i>
---------	--

Description

These options will be used on objects of class 'S4'.

Usage

```
opts_S4(constructor = c("new", "prototype"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new" (default): We build the function using new() if possible. If the class has a "initialize" method we have no practical way to reverse-engineer the inputs so we fall back to the "prototype" constructor
- "prototype" : We start from getClass("S4")@prototype and add attributes.

Value

An object of class <constructive_options/constructive_options_S4>

opts_S7_any	<i>Constructive options for class 'S7_any'</i>
-------------	--

Description

These options will be used on objects of class 'S7_any'.

Usage

```
opts_S7_any(constructor = c("class_any", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "class_any" (default): We build the object using `S7::class_any()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_S7_any>`

opts_S7_base_class	<i>Constructive options for class 'S7_base_class'</i>
--------------------	---

Description

These options will be used on objects of class `'S7_base_class'`.

Usage

```
opts_S7_base_class(constructor = c("S7", "next"), ...)
```

Arguments

- | | |
|-------------|--|
| constructor | String. Name of the function used to construct the object. |
| ... | Additional options used by user defined constructors through the opts object |

Details

Depending on constructor, we construct the object as follows:

- "S7" (default): We build the object using `S7()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_S7_base_class>`

opts_S7_class	<i>Constructive options for class 'S7_class'</i>
---------------	--

Description

These options will be used on objects of class 'S7_class'.

Usage

```
opts_S7_class(constructor = c("new_class", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new_class" (default): We build the object using `S7::new_class()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_S7_class>

opts_S7_external_generic	<i>Constructive options for class 'S7_external_generic'</i>
--------------------------	---

Description

These options will be used on objects of class 'S7_external_generic'.

Usage

```
opts_S7_external_generic(constructor = c("new_external_generic", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new_external_generic" (default): We build the object using `S7::new_external_generic()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_S7_external_generic>`

opts_S7_generic	<i>Constructive options for class 'S7_generic'</i>
-----------------	--

Description

These options will be used on objects of class 'S7_generic'.

Usage

```
opts_S7_generic(constructor = c("new_generic", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new_generic" (default): We build the object using `S7::new_generic()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_S7_generic>`

opts_S7_object	<i>Constructive options for class 'S7_object'</i>
----------------	---

Description

These options will be used on objects of class 'S7_object'. This class is unusual in that it can be applied on objects of different internal types, objects of length 1 class "S7_object" are of type "object" while for instance objects of class c("S7_class", "S7_object") are closures. For closures we fall back to the next method.

Usage

```
opts_S7_object(constructor = c("S7_object", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "S7_object" (default): We build the object using `S7::S7_object()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_S7_object>

opts_S7_property	<i>Constructive options for class 'S7_property'</i>
------------------	---

Description

These options will be used on objects of class 'S7_property'.

Usage

```
opts_S7_property(constructor = c("new_property", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "new_property" (default): We build the object using S7::new_property().
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_S7_property>

opts_S7_S3_class	<i>Constructive options for class 'S7_S3_class'</i>
------------------	---

Description

These options will be used on objects of class 'S7_S3_class'.

Usage

```
opts_S7_S3_class(constructor = c("new_S3_class", "next"), ...)
```

Arguments

- | | |
|-------------|--|
| constructor | String. Name of the function used to construct the object. |
| ... | Additional options used by user defined constructors through the opts object |

Details

Depending on constructor, we construct the object as follows:

- "new_S3_class" (default): We build the object using S7::new_S3_class().
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_S7_S3_class>

opts_S7_union	<i>Constructive options for class 'S7_union'</i>
---------------	--

Description

These options will be used on objects of class 'S7_union'.

Usage

```
opts_S7_union(constructor = c("default", "|", "new_union", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "default" : We build the object using its name if it's a "class_union" object provided by the 'S7' package, or fall back to the "|" constructor.
- "|" : We build the object using the | operator.
- "new_union" (default): We build the object using `S7::new_union()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_S7_union>

opts_tbl_df	<i>Constructive options for tibbles</i>
-------------	---

Description

These options will be used on objects of class 'tbl_df', also known as tibbles.

Usage

```
opts_tbl_df(
  constructor = c("tibble", "tribble", "next", "list"),
  ...,
  trailing_comma = TRUE,
  justify = c("left", "right", "centre", "none"),
  recycle = TRUE
)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object
trailing_comma	Boolean. Whether to leave a trailing comma at the end of the constructor call calls
justify	String. Justification for columns if constructor is "tribble"
recycle	Boolean. For the "tribble" constructor. Whether to recycle scalars to compress the output.

Details

Depending on constructor, we construct the object as follows:

- "tribble" (default): Wrap the column definitions in a `tibble::tibble()` call.
- "tribble" : We build the object using `tibble::tribble()` if possible, and fall back to `tibble::tibble()`.
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried.
- "list" : Use `list()` and treat the class as a regular attribute.

Value

An object of class `<constructive_options/constructive_options_tbl_df>`

opts_ts

Constructive options for time-series objects

Description

Depending on constructor, we construct the object as follows:

- "ts" : We use `ts()`
- "next" : Use the constructor for the next supported class. Call `.class2()` on the object to see in which order the methods will be tried. This will usually be equivalent to "atomic"
- "atomic" : We define as an atomic vector and repair attributes

Usage

```
opts_ts(constructor = c("ts", "next", "atomic"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Value

An object of class `<constructive_options/constructive_options_ts>`

opts_vctr_list_of	<i>Constructive options for class 'data.table'</i>
-------------------	--

Description

These options will be used on objects of class 'data.table'.

Usage

```
opts_vctr_list_of(constructor = c("list_of", "next", "list"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object, see Details section.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "list_of" (default): Wrap the column definitions in a list_of() call.
- "list" : Use list() and treat the class as a regular attribute.

Value

An object of class <constructive_options/constructive_options_vctr_list_of>

opts_weakref	<i>Constructive options for the class weakref</i>
--------------	---

Description

These options will be used on objects of type weakref. weakref objects are rarely encountered and there is no base R function to create them. However **rlang** has a new_weakref function that we can use.

Usage

```
opts_weakref(constructor = c("new_weakref"), ...)
```

Arguments

constructor	String. Name of the constructor.
...	Additional options used by user defined constructors through the opts object

Value

An object of class <constructive_options/constructive_options_array>

opts_xml_document	<i>Constructive options for class 'xml_document'</i>
-------------------	--

Description

These options will be used on objects of class 'xml_document'.

Usage

```
opts_xml_document(constructor = c("default", "next"), ..., simplify = TRUE)
```

Arguments

constructor	String. Name of the constructor, often the function used to construct the object.
...	Additional options used by user defined constructors through the opts object
simplify	Whether to remove the "meta http-equiv" and "!DOCTYPE" tags from the input if they're the default ones.

Details

Depending on constructor, we construct the object as follows:

- "default" (default): We build the object using `xml2::read_xml()` or `xml2::read_html()` on a string.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_xml_document>`

opts_xts	<i>Constructive options for class 'xts'</i>
----------	---

Description

These options will be used on objects of class 'xts'.

Usage

```
opts_xts(constructor = c("as.xts.matrix", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as.xts.matrix" (default): We build the object using `xts::as.xts.matrix()`.
- "as.xts.data.frame": We build the object using `xts::as.xts.data.frame()`, this is probably the most readable option but couldn't be made the default constructor because it requires the 'xts' package to be installed .
- "xts": We build the object using `xts::xts()`.
- ".xts": We build the object using `xts::.xts()`.
- "next": Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_xts>

opts_yearmon	<i>Constructive options for class 'yearmon'</i>
--------------	---

Description

These options will be used on objects of class 'yearmon'.

Usage

```
opts_yearmon(constructor = c("as.yearmon", "yearmon", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as.yearmon" (default): We build the object using `zoo::as.yearmon()` on a string in the format "2000 Q3".
- "yearmon" : We build the object using `zoo::yearmon()` on a double in the format 2000.5
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_yearmon>

opts_yearqtr	<i>Constructive options for class 'yearqtr'</i>
--------------	---

Description

These options will be used on objects of class 'yearqtr'.

Usage

```
opts_yearqtr(constructor = c("as.yearqtr", "yearqtr", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "as.yearqtr" (default): We build the object using `zoo::as.yearqtr()` on a string in the format "2000 Q3".
- "yearqtr" : We build the object using `zoo::yearqtr()` on a double in the format 2000.5
- "next" : Use the constructor for the next supported class.

Value

An object of class <constructive_options/constructive_options_yearqtr>

opts_zoo	<i>Constructive options for class 'zoo'</i>
----------	---

Description

These options will be used on objects of class 'zoo'.

Usage

```
opts_zoo(constructor = c("zoo", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "zoo" (default): We build the object using `zoo : : zoo()`.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_zoo>`

opts_zooreg	<i>Constructive options for class 'zooreg'</i>
-------------	--

Description

These options will be used on objects of class 'zooreg'.

Usage

```
opts_zooreg(constructor = c("zooreg", "next"), ...)
```

Arguments

constructor	String. Name of the function used to construct the object.
...	Additional options used by user defined constructors through the opts object

Details

Depending on constructor, we construct the object as follows:

- "zooreg" (default): We build the object using `zoo : : zooreg()`, using the start and frequency arguments.
- "next" : Use the constructor for the next supported class.

Value

An object of class `<constructive_options/constructive_options_zooreg>`

other-opts

*Other Opts Functions***Description**

These `opts_*`() functions are not extensively documented yet. Hopefully the signature is self explanatory, if not please [raise an issue](#)

Usage

```
opts_NULL(constructor = "NULL", ...)

opts_bibentry(constructor = c("bibentry", "next"), ...)

opts_citationFooter(constructor = c("citFooter", "next"), ...)

opts_citationHeader(constructor = c("citHeader", "next"), ...)

opts_difftime(constructor = c("as.difftime", "next"), ...)

opts_error(constructor = c("errorCondition", "next"), ...)

opts_expression(constructor = c("default"), ...)

opts_CoordCartesian(
  constructor = c("default", "coord_cartesian", "next", "environment"),
  ...
)

opts_CoordFixed(constructor = c("coord_fixed", "next", "environment"), ...)

opts_CoordFlip(constructor = c("coord_flip", "next", "environment"), ...)

opts_CoordMap(constructor = c("coord_map", "next", "environment"), ...)

opts_CoordMunch(constructor = c("coord_munch", "next", "environment"), ...)

opts_CoordPolar(constructor = c("coord_polar", "next", "environment"), ...)

opts_CoordQuickmap(
  constructor = c("coord_quickmap", "next", "environment"),
  ...
)

opts_CoordSf(constructor = c("coord_sf", "next", "environment"), ...)

opts_CoordTrans(constructor = c("coord_trans", "next", "environment"), ...)
```

```
opts_FacetGrid(  
  constructor = c("facet_grid", "ggproto", "next", "environment"),  
  ...  
)  
  
opts_FacetWrap(  
  constructor = c("facet_wrap", "ggproto", "next", "environment"),  
  ...  
)  
  
opts_Guide(constructor = c("default", "next", "environment"), ...)  
  
opts_Scale(constructor = c("default", "next", "environment"), ...)  
  
opts_ScalesList(constructor = c("ScalesList", "next", "list"), ...)  
  
opts_element_blank(constructor = c("element_blank", "next", "list"), ...)  
  
opts_element_grob(constructor = c("element_grob", "next", "list"), ...)  
  
opts_element_line(constructor = c("element_line", "next", "list"), ...)  
  
opts_element_rect(constructor = c("element_rect", "next", "list"), ...)  
  
opts_element_render(constructor = c("element_render", "next", "list"), ...)  
  
opts_element_text(constructor = c("element_text", "next", "list"), ...)  
  
opts_ggplot2_element_blank(constructor = c("element_blank", "next"), ...)  
  
opts_ggplot2_element_geom(constructor = c("element_geom", "next"), ...)  
  
opts_ggplot2_element_line(constructor = c("element_line", "next"), ...)  
  
opts_ggplot2_element_point(constructor = c("element_point", "next"), ...)  
  
opts_ggplot2_element_polygon(constructor = c("element_polygon", "next"), ...)  
  
opts_ggplot2_element_rect(constructor = c("element_rect", "next"), ...)  
  
opts_ggplot2_element_text(constructor = c("element_text", "next"), ...)  
  
opts_ggplot2_mapping(constructor = c("aes", "next", "list"), ...)  
  
opts_ggplot2_margin(constructor = c("margin", "next", "double"), ...)  
  
opts_ggplot2_theme(constructor = c("theme", "next", "list"), ...)
```

```

opts_ggproto(constructor = c("default", "ggproto", "next", "environment"), ...)
opts_labels(constructor = c("labs", "next", "list"), ...)
opts_margin(constructor = c("margin", "next", "double"), ...)
opts_rel(constructor = c("rel", "next", "double"), ...)
opts_theme(constructor = c("theme", "next", "list"), ...)
opts_uneval(constructor = c("aes", "next", "list"), ...)
opts_waiver(constructor = c("waiver", "next", "list"), ...)
opts_noquote(constructor = c("noquote", "next"), ...)
opts_person(constructor = c("person", "next"), ...)
opts_simpleCondition(constructor = c("simpleCondition", "next"), ...)
opts_simpleError(constructor = c("simpleError", "next"), ...)
opts_simpleMessage(constructor = c("simpleMessage", "next"), ...)
opts_simpleUnit(constructor = c("unit", "next", "double"), ...)
opts_simpleWarning(constructor = c("simpleWarning", "next"), ...)
opts_warning(constructor = c("warningCondition", "next"), ...)

```

Arguments

constructor	String. Method used to construct the object, often the name of a function.
...	Additional options used by user defined constructors through the opts object

templates

Extend constructive

Description

`.cstr_new_class()` and `.cstr_new_constructor()` open new unsaved scripts, optionally commented, that can be used as templates to define new constructors. If the class is already supported and you want to implement a new constructor, use `.cstr_new_constructor()`, otherwise use `.cstr_new_class()`.

Usage

```
.cstr_new_class(  
  class = c("CLASS", "PARENT_CLASS"),  
  constructor = "PKG::CONSTRUCTOR",  
  commented = FALSE  
)  
  
.cstr_new_constructor(  
  class = c("CLASS", "PARENT_CLASS"),  
  constructor = "PKG::CONSTRUCTOR",  
  commented = FALSE  
)
```

Arguments

class	Class to support, provide the full class() vector.
constructor	Name of the constructor, usually the name of the function you can use to build the object. If not you might need to adjust the script.
commented	Boolean. Whether to include comments in the template.

Details

We suggest the following workflow (summarized in a message when you call the functions):

- Call `usethis::use_package("\constructive", "\Suggests")` one time at any point, this will add a soft dependency on 'constructive' so it's only needed to install it when you use it.
- Call `.cstr_new_class()` or `.cstr_new_constructor()`, with `commented = TRUE` for more guidance.
- Save the scripts unchanged in the "R" folder of your package.
- `devtools::document()`: this will register the S3 methods.
- Try `construct()` on your new object, it should print a call to your chosen constructor.
- Tweak the code, in particular the definition of args.

The README of the example extension package '[constructive.example](#)' guides you through the process. See also {constructive}'s own code and `vignette("extend-constructive")` for more details.

Value

Both functions return NULL invisibly and are called for side effects

Index

`.cstr_apply`, [4](#), [30](#)
`.cstr_combine_errors`, [6](#), [30](#)
`.cstr_construct`, [7](#), [30](#)
`.cstr_new_class`, [30](#)
`.cstr_new_class (templates)`, [96](#)
`.cstr_new_constructor`, [30](#)
`.cstr_new_constructor (templates)`, [96](#)
`.cstr_options`, [8](#), [30](#)
`.cstr_pipe`, [9](#), [30](#)
`.cstr_repair_attributes`, [9](#), [30](#)
`.cstr_wrap`, [10](#), [30](#)
`.env`, [11](#)
`.xptr`, [11](#)

`cli::code_theme_list()`, [20](#)
`compare_options`, [12](#)
`construct`, [13](#)
`construct_base (construct_dput)`, [24](#)
`construct_base()`, [19](#)
`construct_clip`, [20](#)
`construct_clip()`, [19](#)
`construct_diff`, [22](#)
`construct_diff()`, [19](#)
`construct_dput`, [24](#)
`construct_dput()`, [19](#)
`construct_dump`, [26](#)
`construct_dump()`, [19](#)
`construct_issues`, [27](#)
`construct_multi (construct)`, [13](#)
`construct_multi()`, [28](#)
`construct_reprex`, [27](#)
`construct_reprex()`, [19](#)
`construct_signature`, [28](#)
`constructive-global_options`, [20](#)
`constructive_opts_template`
 (`constructive-global_options`),
 [20](#)
`constructive_pretty`
 (`constructive-global_options`),
 [20](#)

`constructive_print_mode`
 (`constructive-global_options`),
 [20](#)

`defused function call`, [6](#)
`deparse_call`, [29](#)

`extend-constructive`, [30](#)

Formatting messages with `cli`, [7](#)

Including contextual information with
 error chains, [7](#)
Including function calls in error
 messages, [6](#)

`local_use_cli()`, [7](#)

`opts_array`, [15](#), [31](#)
`opts_AsIs`, [15](#), [31](#)
`opts_atomic`, [15](#), [32](#), [34](#), [37](#), [43](#), [64](#), [68](#), [78](#)
`opts_bibentry`, [15](#)
`opts_bibentry (other-opts)`, [94](#)
`opts_blob`, [15](#), [33](#)
`opts_character`, [15](#), [34](#)
`opts_citationFooter`, [15](#)
`opts_citationFooter (other-opts)`, [94](#)
`opts_citationHeader`, [15](#)
`opts_citationHeader (other-opts)`, [94](#)
`opts_classGeneratorFunction`, [15](#), [35](#)
`opts_classPrototypeDef`, [15](#), [36](#)
`opts_classRepresentation`, [15](#), [36](#)
`opts_complex`, [15](#), [37](#)
`opts_constructive_options`, [15](#), [37](#)
`opts_CoordCartesian`, [15](#)
`opts_CoordCartesian (other-opts)`, [94](#)
`opts_CoordFixed`, [15](#)
`opts_CoordFixed (other-opts)`, [94](#)
`opts_CoordFlip`, [15](#)
`opts_CoordFlip (other-opts)`, [94](#)
`opts_CoordMap`, [15](#)

opts_CoordMap (other-opts), 94
 opts_CoordMunch, 15
 opts_CoordMunch (other-opts), 94
 opts_CoordPolar, 15
 opts_CoordPolar (other-opts), 94
 opts_CoordQuickmap, 15
 opts_CoordQuickmap (other-opts), 94
 opts_CoordRadial, 15, 38
 opts_CoordSf, 15
 opts_CoordSf (other-opts), 94
 opts_CoordTrans, 15
 opts_CoordTrans (other-opts), 94
 opts_CoordTransform, 15, 39
 opts_data.frame, 16, 39
 opts_data.table, 16, 40
 opts_Date, 16, 41
 opts_difftime, 16
 opts_difftime (other-opts), 94
 opts_dm, 16, 42
 opts_dots, 16, 43
 opts_double, 16, 43
 opts_element_blank, 16
 opts_element_blank (other-opts), 94
 opts_element_grob, 16
 opts_element_grob (other-opts), 94
 opts_element_line, 16
 opts_element_line (other-opts), 94
 opts_element_rect, 16
 opts_element_rect (other-opts), 94
 opts_element_render, 16
 opts_element_render (other-opts), 94
 opts_element_text, 16
 opts_element_text (other-opts), 94
 opts_ellmer_TypeArray, 16, 44
 opts_ellmer_TypeBasic, 16, 45
 opts_ellmer_TypeEnum, 16, 45
 opts_ellmer_TypeJsonSchema, 16, 46
 opts_ellmer_TypeObject, 16, 47
 opts_environment, 16, 47
 opts_error, 16
 opts_error (other-opts), 94
 opts_expression, 16
 opts_expression (other-opts), 94
 opts_externalptr, 16, 49
 opts_FacetGrid, 16
 opts_FacetGrid (other-opts), 94
 opts_FacetNull, 16, 50
 opts_FacetWrap, 16
 opts_FacetWrap (other-opts), 94
 opts_factor, 16, 51
 opts_formula, 16, 52
 opts_function, 16, 52
 opts_ggplot, 16, 53
 opts_ggplot2_element_blank, 17
 opts_ggplot2_element_blank
 (other-opts), 94
 opts_ggplot2_element_geom, 17
 opts_ggplot2_element_geom (other-opts),
 94
 opts_ggplot2_element_line, 17
 opts_ggplot2_element_line (other-opts),
 94
 opts_ggplot2_element_point, 17
 opts_ggplot2_element_point
 (other-opts), 94
 opts_ggplot2_element_polygon, 17
 opts_ggplot2_element_polygon
 (other-opts), 94
 opts_ggplot2_element_rect, 17
 opts_ggplot2_element_rect (other-opts),
 94
 opts_ggplot2_element_text, 17
 opts_ggplot2_element_text (other-opts),
 94
 opts_ggplot2_ggplot, 17, 54
 opts_ggplot2_labels, 17, 55
 opts_ggplot2_mapping, 17
 opts_ggplot2_mapping (other-opts), 94
 opts_ggplot2_margin, 17
 opts_ggplot2_margin (other-opts), 94
 opts_ggplot2_theme, 17
 opts_ggplot2_theme (other-opts), 94
 opts_ggproto, 17
 opts_ggproto (other-opts), 94
 opts_grouped_df, 17, 55
 opts_Guide, 17
 opts_Guide (other-opts), 94
 opts_GuideAxis, 17, 56
 opts_GuideAxisLogticks, 17, 57
 opts_GuideAxisStack, 17, 57
 opts_GuideAxisTheta, 17, 58
 opts_GuideBins, 17, 59
 opts_GuideColourbar, 17, 59
 opts_GuideColoursteps, 17, 60
 opts_GuideCustom, 17, 61
 opts_GuideLegend, 17, 61

opts_GuideNone, [17, 62](#)
 opts_Guides, [17, 63](#)
 opts_hexmode, [17, 63](#)
 opts_integer, [17, 64](#)
 opts_integer64, [17, 65](#)
 opts_labels, [17](#)
 opts_labels (other-opts), [94](#)
 opts_language, [17, 65](#)
 opts_Layer, [17, 66](#)
 opts_list, [17, 67](#)
 opts_logical, [17, 68](#)
 opts_margin, [17](#)
 opts_margin (other-opts), [94](#)
 opts_matrix, [18, 69](#)
 opts_mts, [18, 69](#)
 opts_noquote, [18](#)
 opts_noquote (other-opts), [94](#)
 opts_NULL, [18](#)
 opts_NULL (other-opts), [94](#)
 opts_numeric_version, [18, 70](#)
 opts_object, [18, 71](#)
 opts_octmode, [18, 71](#)
 opts_ordered, [18, 72](#)
 opts_package_version, [18, 73](#)
 opts_pairlist, [18, 73](#)
 opts_person, [18](#)
 opts_person (other-opts), [94](#)
 opts_POSIXct, [18, 74](#)
 opts_POSIXlt, [18, 75](#)
 opts_quosure, [18, 75](#)
 opts_quosures, [18, 76](#)
 opts_R6, [18, 77](#)
 opts_R6ClassGenerator, [18, 78](#)
 opts_R_system_version, [18, 80](#)
 opts_raw, [18, 78](#)
 opts_rel, [18](#)
 opts_rel (other-opts), [94](#)
 opts_rowwise_df, [18, 79](#)
 opts_S4, [18, 81](#)
 opts_S7_any, [18, 81](#)
 opts_S7_base_class, [18, 82](#)
 opts_S7_class, [18, 83](#)
 opts_S7_external_generic, [18, 83](#)
 opts_S7_generic, [18, 84](#)
 opts_S7_object, [18, 85](#)
 opts_S7_property, [18, 85](#)
 opts_S7_S3_class, [18, 86](#)
 opts_S7_union, [18, 87](#)
 opts_Scale, [18](#)
 opts_Scale (other-opts), [94](#)
 opts_ScalesList, [18](#)
 opts_ScalesList (other-opts), [94](#)
 opts_simpleCondition, [18](#)
 opts_simpleCondition (other-opts), [94](#)
 opts_simpleError, [19](#)
 opts_simpleError (other-opts), [94](#)
 opts_simpleMessage, [19](#)
 opts_simpleMessage (other-opts), [94](#)
 opts_simpleUnit, [19](#)
 opts_simpleUnit (other-opts), [94](#)
 opts_simpleWarning, [19](#)
 opts_simpleWarning (other-opts), [94](#)
 opts_tbl_df, [19, 87](#)
 opts_theme, [19](#)
 opts_theme (other-opts), [94](#)
 opts_ts, [19, 88](#)
 opts_uneval, [19](#)
 opts_uneval (other-opts), [94](#)
 opts_vctrs_list_of, [19, 89](#)
 opts_waiver, [19](#)
 opts_waiver (other-opts), [94](#)
 opts_warning, [19](#)
 opts_warning (other-opts), [94](#)
 opts_weakref, [19, 89](#)
 opts_xml_document, [19, 90](#)
 opts_xts, [19, 90](#)
 opts_yearmon, [19, 91](#)
 opts_yearqtr, [19, 92](#)
 opts_zoo, [19, 92](#)
 opts_zooreg, [19, 93](#)
 other-opts, [94](#)
 templates, [96](#)
 trace_back(), [6](#)
 try_fetch(), [6, 7](#)
 tryCatch(), [7](#)