

# Package ‘VC2copula’

February 22, 2024

**Title** Extend the 'copula' Package with Families and Models from 'VineCopula'

**Version** 0.1.5

**Description** Provides new classes for (rotated) BB1, BB6, BB7, BB8, and Tawn copulas, extends the existing Gumbel and Clayton families with rotations, and allows to set up a vine copula model using the 'copula' API. Corresponding objects from the 'VineCopula' API can easily be converted.

**License** GPL-3

**Encoding** UTF-8

**URL** <https://github.com/tnagler/VC2copula>

**BugReports** <https://github.com/tnagler/VC2copula/issues>

**Depends** copula ( $\geq$  1.1-2)

**Imports** VineCopula ( $\geq$  2.3.0), methods

**LinkingTo** VineCopula

**Suggests** lattice, testthat ( $\geq$  2.1.0)

**RoxygenNote** 7.2.3

**Language** en-US

**NeedsCompilation** yes

**Author** Thomas Nagler [aut, cre],  
Benedikt Graeler [ctb]

**Maintainer** Thomas Nagler <[mail@tnagler.com](mailto:mail@tnagler.com)>

**Repository** CRAN

**Date/Publication** 2024-02-22 14:00:02 UTC

## R topics documented:

|                           |   |
|---------------------------|---|
| BB1Copula . . . . .       | 2 |
| BB1Copula-class . . . . . | 3 |
| BB6Copula . . . . .       | 4 |

|                                  |           |
|----------------------------------|-----------|
| BB6Copula-class . . . . .        | 5         |
| BB7Copula . . . . .              | 5         |
| BB7Copula-class . . . . .        | 6         |
| BB8Copula . . . . .              | 7         |
| BB8Copula-class . . . . .        | 8         |
| BiCop2copula . . . . .           | 9         |
| ddCopula . . . . .               | 10        |
| fitCopula . . . . .              | 12        |
| joeBiCopula . . . . .            | 13        |
| joeBiCopula-class . . . . .      | 14        |
| surClaytonCopula . . . . .       | 15        |
| surClaytonCopula-class . . . . . | 15        |
| surGumbelCopula . . . . .        | 16        |
| surGumbelCopula-class . . . . .  | 17        |
| tawnT1Copula . . . . .           | 17        |
| tawnT1Copula-class . . . . .     | 18        |
| tawnT2Copula . . . . .           | 19        |
| tawnT2Copula-class . . . . .     | 20        |
| vineCopula . . . . .             | 20        |
| vineCopula-class . . . . .       | 21        |
| <b>Index</b>                     | <b>22</b> |

---

BB1Copula

*Constructors for BB1 copulas*


---

### Description

Constructs an object of the [BB1Copula](#) (survival sur, 90 degree rotated r90 and 270 degree rotated r270) family for given parameters.

### Usage

```
BB1Copula(param = c(1, 1))
```

```
surBB1Copula(param = c(1, 1))
```

```
r90BB1Copula(param = c(-1, -1))
```

```
r270BB1Copula(param = c(-1, -1))
```

### Arguments

param            The parameter param defines the copula through theta and delta.

### Value

One of the respective BB1 copula classes ([BB1Copula](#), [surBB1Copula](#), [r90BB1Copula](#), [r270BB1Copula](#)).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

**Examples**

```
library(copula)

persp(BB1Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB1Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB1Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB1Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

---

BB1Copula-class

*BB1 copula models*


---

**Description**

Wrapper classes representing the BB1, survival BB1, 90 degree and 270 degree rotated BB1 copula families (Joe 1997) from [VineCopula-package\(\)](#).

**Objects from the Classes**

Objects can be created by calls of the form `new("BB1Copula", ...)`, `new("surBB1Copula", ...)`, `new("r90BB1Copula", ...)` and `new("r270BB1Copula", ...)` or by the functions [BB1Copula\(\)](#), [surBB1Copula\(\)](#), [r90BB1Copula\(\)](#) and [r270BB1Copula\(\)](#).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB6Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

**Examples**

```
showClass("BB1Copula")
```

---

**BB6Copula***Constructors for BB6 copulas*

---

**Description**

Constructs an object of the [BB6Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

**Usage**

```
BB6Copula(param = c(1, 1))
```

```
surBB6Copula(param = c(1, 1))
```

```
r90BB6Copula(param = c(-1, -1))
```

```
r270BB6Copula(param = c(-1, -1))
```

**Arguments**

`param`            The parameter `param` defines the copula through `theta` and `delta`.

**Value**

One of the respective BB6 copula classes ([BB6Copula](#), [surBB6Copula](#), [r90BB6Copula](#), [r270BB6Copula](#)).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

**Examples**

```
library(copula)

persp(BB6Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB6Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB6Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB6Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

---

|                 |                          |
|-----------------|--------------------------|
| BB6Copula-class | <i>BB6 copula models</i> |
|-----------------|--------------------------|

---

### Description

Wrapper classes representing the BB6, survival BB6, 90 degree and 270 degree rotated BB6 copula families (Joe 1997) from [VineCopula-package\(\)](#).

### Objects from the Classes

Objects can be created by calls of the form `new("BB6Copula", ...)`, `new("surBB6Copula", ...)`, `new("r90BB6Copula", ...)` and `new("r270BB6Copula", ...)` or by the functions [BB6Copula\(\)](#), [surBB6Copula\(\)](#), [r90BB6Copula\(\)](#) and [r270BB6Copula\(\)](#).

### References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

### See Also

See also [BB6Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

### Examples

```
showClass("BB6Copula")
```

---

|           |                                     |
|-----------|-------------------------------------|
| BB7Copula | <i>Constructors for BB7 copulas</i> |
|-----------|-------------------------------------|

---

### Description

Constructs an object of the [BB7Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

### Usage

```
BB7Copula(param = c(1, 1))
```

```
surBB7Copula(param = c(1, 1))
```

```
r90BB7Copula(param = c(-1, -1))
```

```
r270BB7Copula(param = c(-1, -1))
```

**Arguments**

param            The parameter param defines the copula through theta and delta.

**Value**

One of the respective BB7 copula classes ([BB7Copula](#), [surBB7Copula](#), [r90BB7Copula](#), [r270BB7Copula](#)).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

**Examples**

```
library(copula)

persp(BB7Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(surBB7Copula(c(1, 1.5)), dCopula, zlim = c(0, 10))
persp(r90BB7Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
persp(r270BB7Copula(c(-1, -1.5)), dCopula, zlim = c(0, 10))
```

---

|                 |                          |
|-----------------|--------------------------|
| BB7Copula-class | <i>BB7 copula models</i> |
|-----------------|--------------------------|

---

**Description**

Wrapper classes representing the BB7, survival BB7, 90 degree and 270 degree rotated BB7 copula families (Joe 1997) from [VineCopula-package\(\)](#).

**Objects from the Classes**

Objects can be created by calls of the form `new("BB7Copula", ...)`, `new("surBB7Copula", ...)`, `new("r90BB7Copula", ...)` and `new("r270BB7Copula", ...)` or by the functions [BB7Copula\(\)](#), [surBB7Copula\(\)](#), [r90BB7Copula\(\)](#) and [r270BB7Copula\(\)](#).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB7Copula](#), [BB7Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

**Examples**

```
showClass("BB7Copula")
```

---

BB8Copula

*Constructors for BB8 copulas*

---

**Description**

Constructs an object of the [BB8Copula](#) (survival `sur`, 90 degree rotated `r90` and 270 degree rotated `r270`) family for given parameters.

**Usage**

```
BB8Copula(param = c(1, 1))
```

```
surBB8Copula(param = c(1, 1))
```

```
r90BB8Copula(param = c(-1, -1))
```

```
r270BB8Copula(param = c(-1, -1))
```

**Arguments**

`param`            The parameter `param` defines the copula through `theta` and `delta`.

**Value**

One of the respective BB8 copula classes ([BB8Copula](#), [surBB8Copula](#), [r90BB8Copula](#), [r270BB8Copula](#)).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also [BB6Copula\(\)](#), [BB7Copula\(\)](#), [BB8Copula\(\)](#) and [joeCopula\(\)](#) for further wrapper functions to the [VineCopula-package\(\)](#).

## Examples

```
library(copula)

persp(BB8Copula(c(2, 0.9)), dCopula, zlim = c(0, 10))
persp(surBB8Copula(c(2, 0.9)), dCopula, zlim = c(0, 10))
persp(r90BB8Copula(c(-2, -0.9)), dCopula, zlim = c(0, 10))
persp(r270BB8Copula(c(-2, -0.9)), dCopula, zlim = c(0, 10))
```

---

BB8Copula-class

*BB8 copula models*

---

## Description

Wrapper classes representing the BB8, survival BB8, 90 degree and 270 degree rotated BB8 copula families (Joe 1997) from [VineCopula-package\(\)](#).

## Objects from the Classes

Objects can be created by calls of the form `new("BB8Copula", ...)`, `new("surBB8Copula", ...)`, `new("r90BB8Copula", ...)` and `new("r270BB8Copula", ...)` or by the functions [BB8Copula\(\)](#), [surBB8Copula\(\)](#), [r90BB8Copula\(\)](#) and [r270BB8Copula\(\)](#).

## References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

## See Also

See also [BB8Copula](#), [BB8Copula](#), [BB8Copula](#) and [joeCopula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

## Examples

```
showClass("BB8Copula")
```



**Description**

A VineCopula family index along with its parameters is used to construct a corresponding [copula](#) object.

**Usage**

```
BiCop2copula(family, par, par2 = 0, obj = NULL)
```

```
copulaFromFamilyIndex(family, par, par2 = 0)
```

**Arguments**

|        |   |
|--------|---|
| family | a family index as defined in <a href="#">VineCopula-package()</a> .               |
| par    | first parameter.  |
| par2   | second parameter.   |
| obj    | <a href="#">BiCop()</a> object containing the family and parameter specification. |

**Details**

If the family and parameter specification is stored in a `[BiCop()]` object `obj`, the alternative version

```
BiCop2copula(u1, u2, obj)
```

can be used.

**Value**

An object inheriting [copula](#) corresponding to the specific family.

**Examples**

```
# normalCopula with parameter 0.5
BiCop2copula(1, 0.5)

# rotated Tawn T2 copula
BiCop2copula(224, -2, 0.5)
```

ddCopula

*Partial Derivatives of Copulas***Description**

Similar to `dCopula()` and `pCopula()` the function `dduCopula` evaluates the partial derivative  $\frac{\partial}{\partial u}C(u, v)$  and the function `ddvCopula` evaluates the partial derivative  $\frac{\partial}{\partial v}C(u, v)$  of the provided copula.

**Usage**

```

dduCopula(u, copula, ...)

## S4 method for signature 'matrix,normalCopula'
dduCopula(u, copula)

## S4 method for signature 'numeric,normalCopula'
dduCopula(u, copula, ...)

## S4 method for signature 'matrix,normalCopula'
ddvCopula(u, copula)

## S4 method for signature 'numeric,normalCopula'
ddvCopula(u, copula, ...)

## S4 method for signature 'matrix,tCopula'
dduCopula(u, copula)

## S4 method for signature 'numeric,tCopula'
dduCopula(u, copula, ...)

## S4 method for signature 'matrix,tCopula'
ddvCopula(u, copula)

## S4 method for signature 'numeric,tCopula'
ddvCopula(u, copula, ...)

## S4 method for signature 'matrix,gumbelCopula'
dduCopula(u, copula)

## S4 method for signature 'numeric,gumbelCopula'
dduCopula(u, copula, ...)

## S4 method for signature 'matrix,gumbelCopula'
ddvCopula(u, copula)

## S4 method for signature 'numeric,gumbelCopula'
ddvCopula(u, copula, ...)

```

```
## S4 method for signature 'matrix,claytonCopula'  
dduCopula(u, copula)  
  
## S4 method for signature 'numeric,claytonCopula'  
dduCopula(u, copula, ...)  
  
## S4 method for signature 'matrix,claytonCopula'  
ddvCopula(u, copula)  
  
## S4 method for signature 'numeric,claytonCopula'  
ddvCopula(u, copula, ...)  
  
## S4 method for signature 'matrix,indepCopula'  
dduCopula(u, copula)  
  
## S4 method for signature 'numeric,indepCopula'  
dduCopula(u, copula, ...)  
  
## S4 method for signature 'matrix,indepCopula'  
ddvCopula(u, copula)  
  
## S4 method for signature 'numeric,indepCopula'  
ddvCopula(u, copula, ...)  
  
## S4 method for signature 'matrix,frankCopula'  
dduCopula(u, copula)  
  
## S4 method for signature 'numeric,frankCopula'  
dduCopula(u, copula, ...)  
  
## S4 method for signature 'matrix,frankCopula'  
ddvCopula(u, copula)  
  
## S4 method for signature 'numeric,frankCopula'  
ddvCopula(u, copula, ...)
```

### Arguments

|        |   |
|--------|---|
| u      | Pairs of values for which the partial derivative should be evaluated. |
| copula | The copula object representing the family member of interest.         |
| ...    | additional arguments can be passed on to the underlying functions.    |

### Value

A vector of the evaluated partial derivatives of the same length as rows in u.

**Examples**

```

library(copula)

BB1Cop <- BB1Copula()
BB1CopSmpl <- rCopula(100, BB1Cop)

# conditional probabilities of a Gaussian copula given u
BB1GivenU <- dduCopula(BB1CopSmpl, BB1Cop)

# vs. conditional probabilities of a Gaussian copula given v
BB1GivenV <- ddvCopula(BB1CopSmpl[, c(2, 1)], BB1Cop)

plot(BB1GivenU, BB1GivenV)
abline(0, 1)

```

---

|           |  |
|-----------|--|
| fitCopula | <i>A dedicated method to use the estimation routines from the VineCopula package</i> |
|-----------|--|

---

**Description**

Bivariate copulas are estimated based on [BiCopEst](#) and vine copulas through [RVineStructureSelect](#) or [RVineCopSelect](#) depending on the method argument.

**Usage**

```
BCfitCopula(copula, data, method = "ml")
```

**Arguments**

|        |  |
|--------|--|
| copula | an object of the desired copula class  |
| data   | a matrix holding the U(0,1) distributed data columns   |
| method | for BIVARIATE copulas either "ml" or "itau" for maximum likelihood estimation or inverse tau estimation (for one parameter families) respectively. See <a href="#">BiCopEst</a> for details. In case of a VINE copulas a list with names entries StructureSelect (default: FALSE), indeptest (default: FALSE), familyset (default: 'NA') and indeptest (default: FALSE). See <a href="#">RVineStructureSelect</a> or <a href="#">RVineCopSelect</a> for details. |

**Value**

an object of class [fitCopula](#) as in the copula package.

**Examples**

```
u <- rCopula(1000, tawnT1Copula(c(3, 0.5)))  
fitCopula(tawnT1Copula(), u)
```

---

joeBiCopula

*Constructors for Joe copulas*

---

**Description**

Constructs an object of the (survival `surJoeBiCopula`, 90 degree rotated `r90JoeBiCopula` and 270 degree rotated `r270JoeBiCopula`) family for a given parameter. Note that package `copula-package()` provides a class `joeCopula` as well.

**Usage**

```
joeBiCopula(param = 2)  
surJoeBiCopula(param = 2)  
r90JoeBiCopula(param = -2)  
r270JoeBiCopula(param = -2)
```

**Arguments**

`param`            The parameter `param` defines the copula through `theta`.

**Value**

One of the respective Joe copula classes (`joeBiCopula`, `surJoeBiCopula`, `r90JoeBiCopula`, `r270JoeBiCopula`).

**References**

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

**See Also**

See also `BB1Copula()`, `BB6Copula()`, `BB7Copula()` and `BB8Copula()` for further wrapper functions to the `VineCopula-package()`.

## Examples

```
library(copula)

persp(surJoeBiCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90JoeBiCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270JoeBiCopula(-1.5), dCopula, zlim = c(0, 10))
```

---

joeBiCopula-class      *Joe copula models*

---

## Description

Wrapper classes representing the bivariate Joe, survival Joe, 90 degree and 270 degree rotated Joe copula families (Joe 1997) from [VineCopula-package\(\)](#). Note that package [copula-package\(\)](#) provides a class [joeCopula](#) as well.

## Objects from the Classes

Objects can be created by calls of the form `new("joeBiCopula", ...)`, `new("surJoeBiCopula", ...)`, `new("r90JoeBiCopula", ...)` and `new("r270JoeBiCopula", ...)` or by the functions [joeBiCopula\(\)](#), [surJoeBiCopula\(\)](#), [r90JoeBiCopula\(\)](#) and [r270JoeBiCopula\(\)](#).

## References

Joe, H., (1997). Multivariate Models and Dependence Concepts. Monogra. Stat. Appl. Probab. 73, London: Chapman and Hall.

## See Also

See also [BB1Copula](#), [BB6Copula](#), [BB7Copula](#) and [BB8Copula](#) for further wrapper classes to the [VineCopula-package\(\)](#).

## Examples

```
showClass("surJoeBiCopula")
```

---

|                  |  |
|------------------|--|
| surClaytonCopula | <i>Constructors for survival and rotated Clayton Copulas</i> |
|------------------|--|

---

**Description**

These are wrappers to functions from [VineCopula-package\(\)](#)

**Usage**

```
surClaytonCopula(param = 1)
```

```
r90ClaytonCopula(param = -1)
```

```
r270ClaytonCopula(param = -1)
```

**Arguments**

param            A single parameter defining the Copula.

**Value**

An object of class [surClaytonCopula](#), [r90ClaytonCopula](#) or [r270ClaytonCopula](#) respectively.

**Examples**

```
library(copula)

persp(surClaytonCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90ClaytonCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270ClaytonCopula(-1.5), dCopula, zlim = c(0, 10))
```

---

|                        |   |
|------------------------|---|
| surClaytonCopula-class | <i>Survival and rotated Clayton copula models</i> |
|------------------------|---|

---

**Description**

A class representing rotated versions of the Clayton copula family (survival, 90 and 270 degree rotated).

**Objects from the Class**

Objects can be created by calls of the form `new("surClaytonCopula", ...)`, `new("r90ClaytonCopula", ...)` and `new("r270ClaytonCopula", ...)` or by the function [surClaytonCopula\(\)](#), [r90ClaytonCopula\(\)](#) and [r270ClaytonCopula\(\)](#) respectively.

**See Also**

[VineCopula-package\(\)](#)

**Examples**

```
library(copula)

persp(surClaytonCopula(.5), dCopula, zlim = c(0, 10))
persp(r90ClaytonCopula(-.5), dCopula, zlim = c(0, 10))
persp(r270ClaytonCopula(-.5), dCopula, zlim = c(0, 10))
```

---

surGumbelCopula

*Constructors for survival and rotated Gumbel Copulas*

---

**Description**

These are wrappers to functions from [VineCopula-package\(\)](#)

**Usage**

```
surGumbelCopula(param = 1)

r90GumbelCopula(param = -1)

r270GumbelCopula(param = -1)
```

**Arguments**

param            A single parameter defining the Copula.

**Value**

An object of class [surGumbelCopula](#), [r90GumbelCopula](#) or [r270GumbelCopula](#) respectively.

**Examples**

```
library(copula)

persp(surGumbelCopula(1.5), dCopula, zlim = c(0, 10))
persp(r90GumbelCopula(-1.5), dCopula, zlim = c(0, 10))
persp(r270GumbelCopula(-1.5), dCopula, zlim = c(0, 10))
```



---

surGumbelCopula-class *Survival and rotated Gumbel copula models*

---

### Description

A class representing rotated versions of the Gumbel copula family (survival, 90 and 270 degree rotated).

### Objects from the Class

Objects can be created by calls of the form `new("surGumbelCopula", ...)`, `new("r90GumbelCopula", ...)` and `new("r270GumbelCopula", ...)` or by the function `surGumbelCopula()`, `r90GumbelCopula()` and `r270GumbelCopula()` respectively.

### See Also

[VineCopula-package\(\)](#)

### Examples

```
library(copula)

persp(surGumbelCopula(5), dCopula, zlim = c(0, 10))
persp(r90GumbelCopula(-5), dCopula, zlim = c(0, 10))
persp(r270GumbelCopula(-5), dCopula, zlim = c(0, 10))
```

---

tawnT1Copula *Constructor for Tawn copulas (type 1)*

---

### Description

Constructs an object of the [tawnT1Copula](#) (survival sur, 90 degree rotated r90 and 270 degree rotated r270) family for given parameters.

### Usage

```
tawnT1Copula(param = c(2, 0.5))

surTawnT1Copula(param = c(2, 0.5))

r90TawnT1Copula(param = c(-2, 0.5))

r270TawnT1Copula(param = c(-2, 0.5))
```

**Arguments**

param            The parameter param defines the copula through param1 and param2.

**Value**

One of the Tawn type 1 copula classes ([tawnT1Copula](#), [surTawnT1Copula](#), [r90TawnT1Copula](#), [r270TawnT1Copula](#)).

**See Also**

[tawnT1Copula\(\)](#) and the package [VineCopula-package\(\)](#) for implementation details.

**Examples**

```
library(copula)

persp(tawnT1Copula(), dCopula, zlim = c(0, 10))
persp(surTawnT1Copula(), dCopula, zlim = c(0, 10))
persp(r90TawnT1Copula(), dCopula, zlim = c(0, 10))
persp(r270TawnT1Copula(), dCopula, zlim = c(0, 10))
```

---

tawnT1Copula-class      *Tawn copula models (type 1)*

---

**Description**

S4-class representation of the Tawn Copula family of type 1 and rotated versions there of.

**Objects from the Class**

Objects can be created by calls of the form `new("tawnT1Copula", ...)`, or through the explicit constructors [tawnT1Copula\(\)](#), [surTawnT1Copula\(\)](#), [r90TawnT1Copula\(\)](#) and [r270TawnT1Copula\(\)](#) respectively.

**See Also**

[tawnT1Copula](#) and the package [VineCopula-package\(\)](#) for implementation details.

**Examples**

```
showClass("tawnT1Copula")
```

---

|              |  |
|--------------|--|
| tawnT2Copula | <i>Constructor for Tawn copulas (type 2)</i> |
|--------------|--|

---

### Description

Constructs an object of the [tawnT2Copula](#) (survival sur, 90 degree rotated r90 and 270 degree rotated r270) family for given parameters.

### Usage

```
tawnT2Copula(param = c(2, 0.5))  
surTawnT2Copula(param = c(2, 0.5))  
r90TawnT2Copula(param = c(-2, 0.5))  
r270TawnT2Copula(param = c(-2, 0.5))
```

### Arguments

param            The parameter param defines the copula through param1 and param2.

### Value

One of the Tawn type 2 copula classes ([tawnT2Copula](#), [surTawnT2Copula](#), [r90TawnT2Copula](#), [r270TawnT2Copula](#)).

### See Also

[tawnT2Copula\(\)](#) and the package [VineCopula-package\(\)](#) for implementation details.

### Examples

```
library(copula)  
  
persp(tawnT2Copula(), dCopula, zlim = c(0, 10))  
persp(surTawnT2Copula(), dCopula, zlim = c(0, 10))  
persp(r90TawnT2Copula(), dCopula, zlim = c(0, 10))  
persp(r270TawnT2Copula(), dCopula, zlim = c(0, 10))
```

---

|                    |                                    |
|--------------------|------------------------------------|
| tawnT2Copula-class | <i>Tawn copula models (type 2)</i> |
|--------------------|------------------------------------|

---

### Description

S4-class representation of the Tawn Copula family of type 2 and rotated versions there of.

### Objects from the Class

Objects can be created by calls of the form `new("tawnT2Copula", ...)`, or through the explicit constructors `tawnT2Copula()`, `surTawnT2Copula()`, `r90TawnT2Copula()` and `r270TawnT2Copula()` respectively.

### See Also

`tawnT2Copula` and the package `VineCopula-package()` for implementation details.

### Examples

```
showClass("tawnT2Copula")
```

---

|            |  |
|------------|--|
| vineCopula | <i>Constructor of the Class <code>vineCopula</code>.</i> |
|------------|--|

---

### Description

Constructs an instance of the `vineCopula` class.

### Usage

```
vineCopula(RVM, type = "CVine")
```

### Arguments

|      |   |
|------|---|
| RVM  | An object of class <code>RVineMatrix</code> generated from <code>RVineMatrix</code> in the package <code>VineCopula-package</code> or an integer (e.g. 4L) defining the dimension (an independent Gaussian C-vine of this dimension will be constructed). |
| type | A predefined type if only the dimension is provided and ignored otherwise, the default is a canonical vine  |

### Value

An instance of the `vineCopula` class.

**Author(s)**

Benedikt Graeler

**References**

Aas, K., C. Czado, A. Frigessi, and H. Bakken (2009). Pair-copula constructions of multiple dependence Insurance: Mathematics and Economics 44 (2), 182-198.

**Examples**

```
# a C-vine of independent copulas
vine <- vineCopula(4L, "CVine")

library(copula)
library(lattice)

cloud(V1 ~ V2 + V3, as.data.frame(rCopula(500, vine)))
```

---

vineCopula-class      *Class "vineCopula"*

---

**Description**

A class representing vine copulas in a object oriented implementations. Many functions go back to the package [VineCopula-package](#)

**Objects from the Class**

Objects can be created by calls of the form `new("vineCopula", ...)` or through the function [vineCopula](#).

**Author(s)**

Benedikt Graeler

**References**

Aas, K., C. Czado, A. Frigessi, and H. Bakken (2009). Pair-copula constructions of multiple dependence Insurance: Mathematics and Economics 44 (2), 182-198.

**See Also**

[RVineMatrix](#) from package [VineCopula-package](#)

**Examples**

```
showClass("vineCopula")
```

# Index

## \* classes

- BB1Copula-class, 3
- BB6Copula-class, 5
- BB7Copula-class, 6
- BB8Copula-class, 8
- joeBiCopula-class, 14
- surClaytonCopula-class, 15
- surGumbelCopula-class, 17
- tawnT1Copula-class, 18
- tawnT2Copula-class, 20
- vineCopula-class, 21

## \* conditional

- ddCopula, 10

## \* copula

- BB1Copula, 2
- surClaytonCopula, 15
- surGumbelCopula, 16
- tawnT1Copula, 17
- tawnT2Copula, 19

## \* derivative

- ddCopula, 10

## \* distribution

- BB1Copula, 2
- tawnT1Copula, 17
- tawnT2Copula, 19
- vineCopula, 20

## \* multivariate

- vineCopula, 20

## \* partial

- ddCopula, 10

## \* probabilities

- ddCopula, 10

- BB1Copula, 2, 2, 14
- BB1Copula(), 3, 13
- BB1Copula-class, 3
- BB6Copula, 3, 4, 4, 5, 14
- BB6Copula(), 3–7, 13
- BB6Copula-class, 5
- BB7Copula, 3, 5, 5, 6, 7, 14

- BB7Copula(), 3, 4, 6, 7, 13

- BB7Copula-class, 6

- BB8Copula, 3, 5, 7, 7, 8, 14

- BB8Copula(), 3, 4, 6–8, 13

- BB8Copula-class, 8

- BCfitCopula (fitCopula), 12

- BiCop(), 9

- BiCop2copula, 9

- BiCopEst, 12

- copula, 9

- copulaFromFamilyIndex (BiCop2copula), 9

- dCopula(), 10

- ddCopula, 10

- dduCopula (ddCopula), 10

- dduCopula, matrix, BB1Copula-method (BB1Copula-class), 3

- dduCopula, matrix, BB6Copula-method (BB6Copula-class), 5

- dduCopula, matrix, BB7Copula-method (BB7Copula-class), 6

- dduCopula, matrix, BB8Copula-method (BB8Copula-class), 8

- dduCopula, matrix, claytonCopula-method (ddCopula), 10

- dduCopula, matrix, frankCopula-method (ddCopula), 10

- dduCopula, matrix, gumbelCopula-method (ddCopula), 10

- dduCopula, matrix, indepCopula-method (ddCopula), 10

- dduCopula, matrix, joeBiCopula-method (joeBiCopula-class), 14

- dduCopula, matrix, normalCopula-method (ddCopula), 10

- dduCopula, matrix, r270BB1Copula-method (BB1Copula-class), 3

- dduCopula, matrix, r270BB6Copula-method (BB6Copula-class), 5

- dduCopula, matrix, r270BB7Copula-method (BB7Copula-class), 6
- dduCopula, matrix, r270BB8Copula-method (BB8Copula-class), 8
- dduCopula, matrix, r270ClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, matrix, r270GumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, matrix, r270JoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, matrix, r270TawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, matrix, r270TawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, matrix, r90BB1Copula-method (BB1Copula-class), 3
- dduCopula, matrix, r90BB6Copula-method (BB6Copula-class), 5
- dduCopula, matrix, r90BB7Copula-method (BB7Copula-class), 6
- dduCopula, matrix, r90BB8Copula-method (BB8Copula-class), 8
- dduCopula, matrix, r90ClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, matrix, r90GumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, matrix, r90JoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, matrix, r90TawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, matrix, r90TawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, matrix, surBB1Copula-method (BB1Copula-class), 3
- dduCopula, matrix, surBB6Copula-method (BB6Copula-class), 5
- dduCopula, matrix, surBB7Copula-method (BB7Copula-class), 6
- dduCopula, matrix, surBB8Copula-method (BB8Copula-class), 8
- dduCopula, matrix, surClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, matrix, surGumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, matrix, surJoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, matrix, surTawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, matrix, surTawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, matrix, tawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, matrix, tawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, matrix, tCopula-method (ddCopula), 10
- dduCopula, numeric, BB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, claytonCopula-method (ddCopula), 10
- dduCopula, numeric, frankCopula-method (ddCopula), 10
- dduCopula, numeric, gumbelCopula-method (ddCopula), 10
- dduCopula, numeric, indepCopula-method (ddCopula), 10
- dduCopula, numeric, joeBiCopula-method (joeBiCopula-class), 14
- dduCopula, numeric, normalCopula-method (ddCopula), 10
- dduCopula, numeric, r270BB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, r270BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, r270BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, r270BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, r270ClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, numeric, r270GumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, numeric, r270JoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, numeric, r270TawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, numeric, r270TawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, numeric, r90BB1Copula-method (BB1Copula-class), 3

- dduCopula, numeric, r90BB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, r90BB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, r90BB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, r90ClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, numeric, r90GumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, numeric, r90JoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, numeric, r90TawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, numeric, r90TawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, numeric, surBB1Copula-method (BB1Copula-class), 3
- dduCopula, numeric, surBB6Copula-method (BB6Copula-class), 5
- dduCopula, numeric, surBB7Copula-method (BB7Copula-class), 6
- dduCopula, numeric, surBB8Copula-method (BB8Copula-class), 8
- dduCopula, numeric, surClaytonCopula-method (surClaytonCopula-class), 15
- dduCopula, numeric, surGumbelCopula-method (surGumbelCopula-class), 17
- dduCopula, numeric, surJoeBiCopula-method (joeBiCopula-class), 14
- dduCopula, numeric, surTawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, numeric, surTawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, numeric, tawnT1Copula-method (tawnT1Copula-class), 18
- dduCopula, numeric, tawnT2Copula-method (tawnT2Copula-class), 20
- dduCopula, numeric, tCopula-method (ddCopula), 10
- ddvCopula (ddCopula), 10
- ddvCopula, matrix, BB1Copula-method (BB1Copula-class), 3
- ddvCopula, matrix, BB6Copula-method (BB6Copula-class), 5
- ddvCopula, matrix, BB7Copula-method (BB7Copula-class), 6
- ddvCopula, matrix, BB8Copula-method (BB8Copula-class), 8
- ddvCopula, matrix, claytonCopula-method (ddCopula), 10
- ddvCopula, matrix, frankCopula-method (ddCopula), 10
- ddvCopula, matrix, gumbelCopula-method (ddCopula), 10
- ddvCopula, matrix, indepCopula-method (ddCopula), 10
- ddvCopula, matrix, joeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, matrix, normalCopula-method (ddCopula), 10
- ddvCopula, matrix, r270BB1Copula-method (BB1Copula-class), 3
- ddvCopula, matrix, r270BB6Copula-method (BB6Copula-class), 5
- ddvCopula, matrix, r270BB7Copula-method (BB7Copula-class), 6
- ddvCopula, matrix, r270BB8Copula-method (BB8Copula-class), 8
- ddvCopula, matrix, r270ClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, matrix, r270GumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, matrix, r270JoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, matrix, r270TawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, matrix, r270TawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, matrix, r90BB1Copula-method (BB1Copula-class), 3
- ddvCopula, matrix, r90BB6Copula-method (BB6Copula-class), 5
- ddvCopula, matrix, r90BB7Copula-method (BB7Copula-class), 6
- ddvCopula, matrix, r90BB8Copula-method (BB8Copula-class), 8
- ddvCopula, matrix, r90ClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, matrix, r90GumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, matrix, r90JoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, matrix, r90TawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, matrix, r90TawnT2Copula-method (tawnT2Copula-class), 20



- (tawnT2Copula-class), 20
- ddvCopula, matrix, surBB1Copula-method (BB1Copula-class), 3
- ddvCopula, matrix, surBB6Copula-method (BB6Copula-class), 5
- ddvCopula, matrix, surBB7Copula-method (BB7Copula-class), 6
- ddvCopula, matrix, surBB8Copula-method (BB8Copula-class), 8
- ddvCopula, matrix, surClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, matrix, surGumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, matrix, surJoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, matrix, surTawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, matrix, surTawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, matrix, tawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, matrix, tawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, matrix, tCopula-method (ddCopula), 10
- ddvCopula, numeric, BB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, BB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, BB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, BB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, claytonCopula-method (ddCopula), 10
- ddvCopula, numeric, frankCopula-method (ddCopula), 10
- ddvCopula, numeric, gumbelCopula-method (ddCopula), 10
- ddvCopula, numeric, indepCopula-method (ddCopula), 10
- ddvCopula, numeric, joeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, numeric, normalCopula-method (ddCopula), 10
- ddvCopula, numeric, r270BB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, r270BB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, r270BB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, r270BB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, r270ClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, numeric, r270GumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, numeric, r270JoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, numeric, r270TawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, numeric, r270TawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, numeric, r90BB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, r90BB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, r90BB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, r90BB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, r90ClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, numeric, r90GumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, numeric, r90JoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, numeric, r90TawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, numeric, r90TawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, numeric, surBB1Copula-method (BB1Copula-class), 3
- ddvCopula, numeric, surBB6Copula-method (BB6Copula-class), 5
- ddvCopula, numeric, surBB7Copula-method (BB7Copula-class), 6
- ddvCopula, numeric, surBB8Copula-method (BB8Copula-class), 8
- ddvCopula, numeric, surClaytonCopula-method (surClaytonCopula-class), 15
- ddvCopula, numeric, surGumbelCopula-method (surGumbelCopula-class), 17
- ddvCopula, numeric, surJoeBiCopula-method (joeBiCopula-class), 14
- ddvCopula, numeric, surTawnT1Copula-method (tawnT1Copula-class), 18

- (tawnT1Copula-class), 18
- ddvCopula, numeric, surTawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, numeric, tawnT1Copula-method (tawnT1Copula-class), 18
- ddvCopula, numeric, tawnT2Copula-method (tawnT2Copula-class), 20
- ddvCopula, numeric, tCopula-method (ddCopula), 10
- fitCopula, 12, 12
- fitCopula, vineCopula-method (vineCopula-class), 21
- getKendallDistr, BB1Copula-method (BB1Copula-class), 3
- getKendallDistr, BB6Copula-method (BB6Copula-class), 5
- getKendallDistr, BB7Copula-method (BB7Copula-class), 6
- getKendallDistr, BB8Copula-method (BB8Copula-class), 8
- getKendallDistr, joeBiCopula-method (joeBiCopula-class), 14
- joeBiCopula, 13, 13
- joeBiCopula(), 14
- joeBiCopula-class, 14
- joeCopula, 3, 5, 7, 8, 13, 14
- joeCopula(), 3, 4, 6, 7
- kendallDistribution, BB1Copula-method (BB1Copula-class), 3
- kendallDistribution, BB6Copula-method (BB6Copula-class), 5
- kendallDistribution, BB7Copula-method (BB7Copula-class), 6
- kendallDistribution, BB8Copula-method (BB8Copula-class), 8
- kendallDistribution, joeBiCopula-method (joeBiCopula-class), 14
- pCopula(), 10
- r270BB1Copula, 2
- r270BB1Copula (BB1Copula), 2
- r270BB1Copula(), 3
- r270BB1Copula-class (BB1Copula-class), 3
- r270BB6Copula, 4
- r270BB6Copula (BB6Copula), 4
- r270BB6Copula(), 5
- r270BB6Copula-class (BB6Copula-class), 5
- r270BB7Copula, 6
- r270BB7Copula (BB7Copula), 5
- r270BB7Copula(), 6
- r270BB7Copula-class (BB7Copula-class), 6
- r270BB8Copula, 7
- r270BB8Copula (BB8Copula), 7
- r270BB8Copula(), 8
- r270BB8Copula-class (BB8Copula-class), 8
- r270ClaytonCopula, 15
- r270ClaytonCopula (surClaytonCopula), 15
- r270ClaytonCopula(), 15
- r270ClaytonCopula-class (surClaytonCopula-class), 15
- r270GumbelCopula, 16
- r270GumbelCopula (surGumbelCopula), 16
- r270GumbelCopula(), 17
- r270GumbelCopula-class (surGumbelCopula-class), 17
- r270JoeBiCopula, 13
- r270JoeBiCopula (joeBiCopula), 13
- r270JoeBiCopula(), 14
- r270JoeBiCopula-class (joeBiCopula-class), 14
- r270TawnT1Copula, 18
- r270TawnT1Copula (tawnT1Copula), 17
- r270TawnT1Copula(), 18
- r270TawnT1Copula-class (tawnT1Copula-class), 18
- r270TawnT2Copula, 19
- r270TawnT2Copula (tawnT2Copula), 19
- r270TawnT2Copula(), 20
- r270TawnT2Copula-class (tawnT2Copula-class), 20
- r90BB1Copula, 2
- r90BB1Copula (BB1Copula), 2
- r90BB1Copula(), 3
- r90BB1Copula-class (BB1Copula-class), 3
- r90BB6Copula, 4
- r90BB6Copula (BB6Copula), 4
- r90BB6Copula(), 5
- r90BB6Copula-class (BB6Copula-class), 5
- r90BB7Copula, 6
- r90BB7Copula (BB7Copula), 5
- r90BB7Copula(), 6
- r90BB7Copula-class (BB7Copula-class), 6
- r90BB8Copula, 7

- r90BB8Copula (BB8Copula), 7
- r90BB8Copula(), 8
- r90BB8Copula-class (BB8Copula-class), 8
- r90ClaytonCopula, 15
- r90ClaytonCopula (surClaytonCopula), 15
- r90ClaytonCopula(), 15
- r90ClaytonCopula-class
  - (surClaytonCopula-class), 15
- r90GumbelCopula, 16
- r90GumbelCopula (surGumbelCopula), 16
- r90GumbelCopula(), 17
- r90GumbelCopula-class
  - (surGumbelCopula-class), 17
- r90JoeBiCopula, 13
- r90JoeBiCopula (joeBiCopula), 13
- r90JoeBiCopula(), 14
- r90JoeBiCopula-class
  - (joeBiCopula-class), 14
- r90TawnT1Copula, 18
- r90TawnT1Copula (tawnT1Copula), 17
- r90TawnT1Copula(), 18
- r90TawnT1Copula-class
  - (tawnT1Copula-class), 18
- r90TawnT2Copula, 19
- r90TawnT2Copula (tawnT2Copula), 19
- r90TawnT2Copula(), 20
- r90TawnT2Copula-class
  - (tawnT2Copula-class), 20
- RVineCopSelect, 12
- RVineMatrix, 20, 21
- RVineStructureSelect, 12
  
- surBB1Copula, 2
- surBB1Copula (BB1Copula), 2
- surBB1Copula(), 3
- surBB1Copula-class (BB1Copula-class), 3
- surBB6Copula, 4
- surBB6Copula (BB6Copula), 4
- surBB6Copula(), 5
- surBB6Copula-class (BB6Copula-class), 5
- surBB7Copula, 6
- surBB7Copula (BB7Copula), 5
- surBB7Copula(), 6
- surBB7Copula-class (BB7Copula-class), 6
- surBB8Copula, 7
- surBB8Copula (BB8Copula), 7
- surBB8Copula(), 8
- surBB8Copula-class (BB8Copula-class), 8
- surClaytonCopula, 15, 15
- surClaytonCopula(), 15
- surClaytonCopula-class, 15
- surGumbelCopula, 16, 16
- surGumbelCopula(), 17
- surGumbelCopula-class, 17
- surJoeBiCopula, 13
- surJoeBiCopula (joeBiCopula), 13
- surJoeBiCopula(), 14
- surJoeBiCopula-class
  - (joeBiCopula-class), 14
- surTawnT1Copula, 18
- surTawnT1Copula (tawnT1Copula), 17
- surTawnT1Copula(), 18
- surTawnT1Copula-class
  - (tawnT1Copula-class), 18
- surTawnT2Copula, 19
- surTawnT2Copula (tawnT2Copula), 19
- surTawnT2Copula(), 20
- surTawnT2Copula-class
  - (tawnT2Copula-class), 20
  
- tawnT1Copula, 17, 17, 18
- tawnT1Copula(), 18
- tawnT1Copula-class, 18
- tawnT2Copula, 19, 19, 20
- tawnT2Copula(), 19, 20
- tawnT2Copula-class, 20
  
- vineCopula, 20, 20, 21
- vineCopula-class, 21